

CELON MPB

Issued on 03/24/2022 - Rel. # 7 on 03/24/2022

1 / 15

In conformity to Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/enterprise

1.1. Product identifier

Product name : CELON MPB Product code: refer to sales department

1.2. Relevant identified uses of the substance or mixture and uses advised against

Detergent Sectors of use: Industrial Manufacturing[SU3], Manufacture of food products[SU4] Product category: Washing and Cleaning Products (including solvent based products) Process categories: Use in batch and other process (syn- thesis) where opportunity for exposure arises[PROC4], Transfer of substance or mixture (charging and discharging) at dedicated facilities[PROC8B], Treatment of articles by dipping and pouring [PROC13] Not recommended uses

Do not use for purposes other than those listed

1.3. Details of the supplier of the safety data sheet

AEB SpA - Via Vittorio Arici 104 S.Polo - 25134 Brescia (BS) Italy Tel. +39.030.2307.1 Fax +39.030.2307281 E-mail: info@aeb-group.com - Internet: www.aeb-group.com E-mail tecnico competente/technical dept.: sds@aeb-group.com

AEB USA 111 N Cluff Avenue Lodi CA 95240 (USA) Tel: +1 2096258139 Fax: +1 2092248953 Email: info@aebusa.com - Internet: www.aeb-group.com

AEB AFRICA (PTY) LTD 18 Track Crescent, Cor. Station Road Montague Gardens 7441 Cape Town (South Africa) Tel.: +27 215512700 - Fax: +27 (0) 215511919 Email: info@aeb.co.za - Internet: www.aeb-group.com

AEB OCEANIA PTY LTD 178A Wakaden Street Griffith NSW 2680 T: 1300 704 971 Email: aeboceania@aeb-group.com - Internet: www.aeb-group.com

Produced by



CELON MPB

Issued on 03/24/2022 - Rel. # 7 on 03/24/2022

In conformity to Regulation (EU) 2020/878

1.4. Emergency telephone number

AEB SpA Centralino/Switchboard: +39.030.2307.1 - (h 8.30-12.00 13.30-18.00 GMT +1; Lingua/Language: Italiano, English)

AEB USA

Switchboard: +1 2096258139 (GMT -8; Language: English)

AEB AFRICA (PTY) LTD Switchboard: +27 215512700 (GMT +1; Language: English, Afrikaans)

AEB OCEANIA PTY LTD Switchboard: +61 1300 704 971 (GMT +9; Language: English)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) No 1272/2008:

Pictograms: GHS05, GHS07

Hazard Class and Category Code(s): Met. Corr. 1, Skin Corr. 1A, Eye Dam. 1, Acute Tox. 4

Hazard statement Code(s): H290 - May be corrosive to metals. H314 - Causes severe skin burns and eye damage. H318 - Causes serious eye damage. H332 - Harmful if inhaled.

The product can be corrosive to metals Harmful product: do not inhale Corrosive product: causes severe skin burns and eye damage. If brought into contact with eyes, the product causes serious damages to eyes, such as an opaque cornea or injury to iris.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008:

Pictogram, Signal Word Code(s): GHS05, GHS07 - Danger

Hazard statement Code(s):H290 - May be corrosive to metals.H314 - Causes severe skin burns and eye damage.H332 - Harmful if inhaled.





CELON MPB

Issued on 03/24/2022 - Rel. # 7 on 03/24/2022

#3/15

In conformity to Regulation (EU) 2020/878

Supplemental Hazard statement Code(s): EUH071 - Corrosive to the respiratory tract.

Precautionary statements: Prevention P260 - Do not breathe vapours/spray. P280 - Wear protective gloves/clothing and eye/face protection. Response P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

nitric acid, L-lactic acid.

Contains (Reg.EC 648/2004): /

2.3. Other hazards

The substance / mixture does NOT contain substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

Do not ingest. Keep out of reach of children.

SECTION 3. Composition/information on ingredients

3.1 Substances

Irrilevant

3.2 Mixtures

Refer to paragraph 16 for full text of hazard statements

Substance	Concentration[w/w]	Classification	Index	CAS	EINECS	REACh
Nitric acid (B)	>= 20 < 26%	EUH071; Ox. Liq. 2, H272; Met. Corr. 1, H290; Skin Corr. 1A, H314; Acute Tox. 3, H331 Limits: Skin Corr. 1A, H314 %C >=20; Skin Corr. 1B, H314 5<= %C <20; Ox. Liq. 2, H272 %C >=99; Ox. Liq. 3, H272 65<= %C <99; ATE inhal = 2,65 mg/ I/4 h	007-004-00-1	7697-37-2	231-714-2	01-2119487 297-23-XXX X
L-lactic acid	>= 1 < 2,5%	EUH071; Skin Corr. 1C, H314; Eye Dam.	607-743-00-5	79-33-4	201-196-2	01-2119474 164-39-XX

Geowin SDS rel. 10



CELON MPB

Issued on 03/24/2022 - Rel. # 7 on 03/24/2022

#4/15

In conformity to Regulation (EU) 2020/878

Substance	Concentration[w/w]	Classification	Index	CAS	EINECS	REACh
		1, H318				XX

SECTION 4. First aid measures

4.1. Description of first aid measures

Inhalation:

Ventilate the area. Move immediately the contaminated patient from the area and keep him at rest in a well ventilated room. CALL A PHYSICIAN.

Direct contact with skin (of the pure product) .:

Take off immediately contaminated clothing.

In case of contact with skin, wash immediately with watrer.

Immediately consult a physician.

Direct contact with eyes (of the pure product).:

Wash immediately and thoroughly with running water, keeping eyelids open for at least 10 minutes, then protect your eyes with a dry sterile gauze. Seek medical advice immediately

Do not use eye drops or ointments of any kind before the examination or advice from an oculist.

Ingestion:

Give medicine paraffine oil; do not give milk or animal / vegetal fats in general.

Rinse mouth immediately.

Absolutely do not induce vomiting or emesis. Seek medical advice immediately.

4.2. Most important symptoms and effects, both acute and delayed

Ingestion can cause chemical burns in the mouth and throat. Contact with skin may cause burns. In contact with eyes it causes very strong irritation, including redness and tearing. Inhalation can cause respiratory failure of an asthmatic nature; irritation of the mucous membranes and the respiratory tract can cause nausea and difficulty in breathing.

4.3. Indication of any immediate medical attention and special treatment needed

If you feel unwell, consult a physician and, if possible, show this MSDS.

Symptomatic treatment

SECTION 5. Firefighting measures

5.1. Extinguishing media

Suggested extinguishing media:

Water spray, CO2, foam, dry chemical, depending on the materials involved in the fire.

Extinguishing media to avoid:

Water jets. Use water jets only to cool the surfaces of the containers exposed to fire.



CELON MPB

Issued on 03/24/2022 - Rel. # 7 on 03/24/2022

5 / 15

In conformity to Regulation (EU) 2020/878

5.2. Special hazards arising from the substance or mixture

No data available.

5.3. Advice for firefighters

Use protection for the breathing apparatus

Safety helmet and full protective clothing.

The water spray can be used to protect the people involved in the extinction.

You may also use self-contained breathing apparatus, especially when working in confined and poorly ventilated areas. Keep containers cool with water spray

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel: Leave the area surrounding the spill or release. Do not smoke Wear mask, gloves and protective clothing.

6.1.2 For emergency responders:Eliminate all open flames and possible sources of ignition.Not smoking. Provide adequate ventilation.Evacuate the danger area and, if necessary, consult an expert.

6.2. Environmental precautions

Contain spills with earth or sand.

If the product has entered a watercourse, sewers or has contaminated soil or vegetation, notify the authorities. Dispose of the waste material in compliance with the regulations

6.3. Methods and material for containment and cleaning up

6.3.1 Containment:

Rapidly recover the product, wear a mask and protective clothing (for specifications refer to section 8.2. SDS) Recover the product for reuse, if possible, or for removal. Possibly absorb it with inert materia or sucked it. Prevent it from entering the sewer system.

6.3.2 Cleaning up: After wiping up, wash with water the area and materials involved

6.3.3 Other information: None in particular.

6.4. Reference to other sections

Refer to paragraphs 8 and 13 for more information

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid contact and inhalation of vapors Wear protective gloves/clothing and eye/face protection.



CELON MPB

Issued on 03/24/2022 - Rel. # 7 on 03/24/2022

In conformity to Regulation (EU) 2020/878

Handle the product after consulting all other sections of this safety data sheet. At work do not eat or drink. See also paragraph 8 below.

7.2. Conditions for safe storage, including any incompatibilities

Keep in original container closed tightly. Do not store in open or unlabelled containers. Keep containers upright and safe by avoiding the possibility of falls or collisions. Store in a cool and dry place, away from heat sources and direct exposure to sunlight.

7.3. Specific end use(s)

Industrial Manufacturing:

Handle with extreme caution. Store in a well-ventilated place and away from heat sources (7-30 ° C), in the original, tightly closed container

Manufacture of food products:

Handle with extreme caution. Store in a well-ventilated place and away from heat sources (7-30 ° C), in the original, tightly closed container

See the annex exposure scenario.

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

_____ Related to contained substances: Nitric acid: Limit value - Eight hours $(ppm)/(mg/m^3)$ Australia: 2/5.2 Austria: x/x Belgio: x/x Canada – Ontario: 2/x Canada - Québec: 2/5.2 Denmark: 1/2,6 European Union: x/x Finland: 0.5/1.3 France: x/x Germany (AGS): x/x Hungary: x/x Ireland: x/x Italy: x/x Japan – JSOH: 2/5.2 Latvia: 0.78/2 New Zealand: 2/5.2 Poland: x/1.4 Romania: x/x Singapore: 2/5.2 South Korea: 2/5 Spain: x/x Sweden: 0.5/1.3 Switzerland: 2/5 The Netherlands: x/x Turkey: x/x USA - NIOSH: 2/5 USA - OSHA: 2/5



CELON MPB

Issued on 03/24/2022 - Rel. # 7 on 03/24/2022

In conformity to Regulation (EU) 2020/878

#7/15

United Kingdom: x/x Slovakia: x/x Norway: 2/5 Limit value - Short term $(ppm)/(mg/m^3)$ Australia: 4/10 Austria: 1/2.6 Belgio: 1/2.6 (1) Canada - Ontario: 4/x Canada - Québec: 4/10 Denmark: 4(1)/10(1) European Union: 1(1)/2.6(1) Finland: 1 (1)/2.6 (1) France: 1/2.6 Germany (AGS):1 (1)/2.6 (1) Hungary: x/2.6 Ireland: 1 (1)/2.6 (1) Italy: 1(1)/2.6(1) Japan - JSOH: x/x Latvia: 1 (1)/2.6 (1) New Zealand: 4/10 Poland: x/2.6 Romania: 1(1)/2,6(1) Singapore: 4/10 South Korea: 4/10 Spain: 1/2.6 Sweden: 1 (1)/2.6 (1) Switzerland: 2/5 The Netherlands: x/1.3 Turkey: 1 (1)/2.6 (1) USA - NIOSH: 4 (1)/10 (1) USA – OSHA: x/x United Kingdom: 1/2.6 Slovakia: 1/2.6 Norway: 2/5

Remarks

European Union: Bold-type: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] ~ (for references see bibliography) Finland - Belgium - Germany (AGS)- Latvia - Sweden - Turkey - USA - NIOSH: : (1) 15 minutes average values France: Italic type: Indicative statutory limit values Ireland, Denmark: (1) 15 minutes average period Poland: nitric acid (V)

Tipo OEL: ACGIH - TWA(8h): 2 ppm - STEL: 4 ppm - Note: URT and eye irr, dental erosion

Argentina: CMP 2 ppm - CMP/CP-CMC-C 4 ppm - PM 63,02 (irritation, corrosion, edema polmon) Czech Republic: PEL 1 mg/m3 - NPK-P 2,5 mg/m3 - Poznámky: x - Prepocet: 0,382 Portugal : 8 horas x/x Curta duração: 2,6 mg/m3/ 1 ppm

- Substance: Nitric acid DNEL Local effects Long term Workers inhalation = 2,6 (mg/m3)



CELON MPB

Issued on 03/24/2022 - Rel. # 7 on 03/24/2022

8 / 15

In conformity to Regulation (EU) 2020/878

Local effects Long term Consumers inhalation = 1,3 (mg/m3) Local effects Short term Workers inhalation = 2,6 (mg/m3) Local effects Short term Consumers inhalation = 1,3 (mg/m3)

8.2. Exposure controls

Appropriate engineering controls: Industrial Manufacturing: No specific monitoring foreseen (act according to good practice and specific rules for the type of risk associated)

Manufacture of food products: No specific monitoring foreseen (act according to good practice and specific rules for the type of risk associated)

8.2.2 Individual protection measures:

(a) Eye / face protection Wear protective goggles (EN 166).

(b) Skin protection

(i) Hand protection

When handling the pure product use chemical resistant protective gloves (EN 374-1/EN374-2/EN374).

(ii) Other

During working operation wear protective clothing (generic workwear / antacid, safety shoes or other protective equipment) according to the instructions of the employer.

(c) Respiratory protection

Not needed for normal use.

In case of insufficient ventilation or emergency, use mask with gas filters and inorganic vapors - Grey , Class 3 , B (EN 405) unless otherwise provided by the employer and / or assessments of environmental investigations hygienistic.

(d) Thermal hazards No hazard to report

Environmental exposure controls: Use according to good working practices and avoid to disperse the product into the environment.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical and chemical properties	Value	Determination method
Appearance	clear liquid	
Colour	light yellow	
Odour	not determined as it is considered not relevant for the characterization of the product	
Odour threshold	not determined as it is considered not relevant for the characterization of the product	
рН	<2 (20°V ; sol. 3 %) ; <2 (20°C ; sol. 100 %)	



CELON MPB

Issued on 03/24/2022 - Rel. # 7 on 03/24/2022

#9/15

In conformity to Regulation (EU) 2020/878

Physical and chemical properties	Value	Determination method
Melting point/freezing point	not determined as it is considered not relevant for the characterization of the product	
Initial boiling point and boiling range	not determined as it is considered not relevant for the characterization of the product	
Flash point	not determined as considered not relevant for the characterization of the product	
Evaporation rate	not determined as it is considered not relevant for the characterization of the product	
Flammability (solid, gas)	not determined as it is considered not relevant for the characterization of the product	
Upper/lower flammability or explosive limits	not determined as it is considered not relevant for the characterization of the product	
Vapour pressure	not determined as it is considered not relevant for the characterization of the product	
Vapour density	not determined as it is considered not relevant for the characterization of the product	
Relative density	1,15 ± 0,05 (20 °C)	
Solubility	not determined as it is considered not relevant for the characterization of the product	
Water solubility	Soluble	
Partition coefficient: n-octanol/water	not determined as it is considered not relevant for the characterization of the product	
Auto-ignition temperature	not determined as it is considered not relevant for the characterization of the product	
Decomposition temperature	not determined as it is considered not relevant for the characterization of the product	
Viscosity	not determined as it is considered not relevant for the characterization of the product	
Explosive properties	not determined as it is considered not relevant for the characterization of the product	
Oxidising properties	not determined as it is considered not relevant for the characterization of the product	

9.2. Other information

No data available.

SECTION 10. Stability and reactivity

10.1. Reactivity

Acid, non-pyrophoric product.

10.2. Chemical stability

Stable at room temperature and under normal conditions of use



CELON MPB

Issued on 03/24/2022 - Rel. # 7 on 03/24/2022

10 / 15

In conformity to Regulation (EU) 2020/878

10.3. Possibility of hazardous reactions

Reacts exothermically with water. Reacts vigorously with reducing agents, strong bases, organic materials and chlorides. The reaction with the most common metals can release oxygen.

10.4. Conditions to avoid

Direct heat sources and the provisions of 10.3

10.5. Incompatible materials

Reducing agents. Alkalis. Metals. Combustible materials.

10.6. Hazardous decomposition products

hydrogen, irritating gases

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

ATE(mix) oral = ∞ ATE(mix) dermal = ∞ ATE(mix) inhal = 10,5 mg/l/4 h

(a) acute toxicity: Harmful product: do not inhale Nitric acid: Ingestion - LD50 rat (mg / kg / 24h bw): nd Skin contact - LC50 rat / rabbit (mg / kg / 24h bw): nd Inhalation - LD50 rat (mg / I / 4h):> 2.65 L-lactic acid: Ingestion-rat LD50 (mg/kg/24h bw): 3543 Skin contact-LC50 rat/coniglio (mg/kg/bw 24h bw): > 2000

Inhalation-rat LD50 (mg/l/4h): > 7.94 (b) skincorrosion/irritation: Corrosive product: causes severe skin burns and eye damage. Nitric acid: Corrosive L-lactic acid: Corrosive Nitric acid: Irritating L-lactic acid: OECD 404, in vivo, solution Rabbits (88%) Result: irritant (c) serious eye damage/irritation: Corrosive product: causes severe skin burns and eye damage. - If brought into contact with eyes, the product causes serious damages to eyes, such as an opaque cornea or injury to iris. Nitric acid: Corrosive L-lactic acid: Couses serious eye damage Nitric acid: Causes serious eye damage Nitric acid: Causes serious eye damage Nitric acid: Irritating L-lactic acid: CEET, Ex vivo, solution (88%) Result: severe eye irritation (d) respiratoryorskinsensitisation: Nitric acid: Not available



CELON MPB

Issued on 03/24/2022 - Rel. # 7 on 03/24/2022

11 / 15

In conformity to Regulation (EU) 2020/878

L-lactic acid: Non-sensitizing

(e) germ cell mutagenicity: Nitric acid: Not mutagenic

L-lactic acid: Non-mutagenic

(f) carcinogenicity: Nitric acid: Non-conclusive data

L-lactic acid: Non-carcinogenic

(g) eproductivetoxicity: Nitric acid: Test: NOAEL - Route: Oral - Species: Rat> 1500 mg / kg bw / day - Source: ECHA - Study Report 2002 - Notes: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

L-lactic acid: Non-toxic for reproduction

(h) specific target organ toxicity (STOT) single exposure: Nitric acid: NOAEL - Route: Oral - Species: Rat = 1500 mg / kg bw / day - Source: ECHA - Study Report 2002 - Notes: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test) Test: NOAEC - Route: Inhalation - Species: Rat> 2.15 ppm - Source: ECHA - Study Report 2006 (WoE) - Notes: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)

L-lactic acid: Not available

(i) specific target organ toxicity (STOT) repeated exposureNitric acid: Not available

L-lactic acid: Not available

(j) aspiration hazard: Nitric acid: Not available

L-lactic acid: Not available

11.2. Information on other hazards

No data available.

SECTION 12. Ecological information

12.1. Toxicity

Related to contained substances:

Nitric acid:

Acute toxicity - LC50 fish (mg / I / 96h): 4650

Acute toxicity - EC50 crustaceans (mg / I / 48h): Median lethal pH (48h) 4.4-4.7 for Ceriodaphnia dubia (US EPA guideline). This study shows that the pH rather than the anion (nitrate) is causing the toxic effects in daphnids. This is confirmed by two additional studies with sodium nitrate (24h EC50 8609 mg / L for Daphnia magna, similar to OECD TG 202) and potassium nitrate (48h EC50 490 mg / L for Daphnia magna, no guideline followed). The read-across rationale can be found in the category approach document in Section 13 of IUCLID and is fully incorporated in the CSR. Acute toxicity ErC50 algae (mg / I / 72-96h): nd

L-lactic acid: Acute toxicity - fish (Lepomis macrochirus) LC50 (mg / I / 96h): 130 Acute toxicity - crustaceans (Daphnia magna) EC50 (mg / I / 48h): 130 Acute toxicity algae ErC50 (Pseudokirchnerella subcapitata) (mg / I / 72): ~ 3500 Chronic toxicity algae NOEC (Pseudokirchnerella subcapitata) (mg / I / 72): 1900

Use according to good working practices and avoid to disperse the product into the environment.

12.2. Persistence and degradability



CELON MPB

Issued on 03/24/2022 - Rel. # 7 on 03/24/2022

In conformity to Regulation (EU) 2020/878

L-lactic acid: Easily biodegradable (100%)

12.3. Bioaccumulative potential

Related to contained substances: Nitric acid: Not bioaccumilable

L-lactic acid: Non bioaccumulative Log Pow: -0.72 - -0.54 (20 ° C)

12.4. Mobility in soil

Related to contained substances: Nitric acid: Not available

L-lactic acid: Weak adsorption

12.5. Results of PBT and vPvB assessment

No PBT/vPvB ingredient is present

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No adverse effects

Regulation (EC) No 2006/907 - 2004/648

The (I) surfactant (s) content (s) in this preparation complies (comply) with (i) the biodegradability criteria as laid down in Regulation CE/648/2004 on detergents. All data are held at the disposal of the competent authorities of Member States and will be provided, at their direct request or at the request of a detergent manufacturer, to those authorities.

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Do not reuse empty containers. Dispose of them in accordance with the regulations in force. Any remaining product should be disposed of according to applicable regulations by addressing to authorized companies. Recover if possible. Operate according to local or national regulations

SECTION 14. Transport information

Geowin SDS rel. 10



CELON MPB

Issued on 03/24/2022 - Rel. # 7 on 03/24/2022

In conformity to Regulation (EU) 2020/878

14.1. UN number or ID number

ADR/RID/IMDG/ICAO-IATA: 3264

If subject to the following characteristics is ADR exempt: Combination packagings: per inner packaging 1 L per package 30 Kg Inner packaging placed in skrink-wrapped or stretch-wrapped trays: per inner packaging 1 L per package 20 Kg

14.2. UN proper shipping name

ADR/RID/IMDG: LIQUIDO INORGANICO CORROSIVO, ACIDO, N.A.S. (Acido nitrico in miscela) ADR/RID/IMDG: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric acid in mixture) ICAO-IATA: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric acid in mixture)

14.3. Transport hazard class(es)

ADR/RID/IMDG/ICAO-IATA: Class : 8 ADR/RID/IMDG/ICAO-IATA: Label : 8 ADR: Tunnel restriction code : E ADR/RID/IMDG/ICAO-IATA: Limited quantities : 1 L IMDG - EmS : F-A, S-B

14.4. Packing group

ADR/RID/IMDG/ICAO-IATA: II

14.5. Environmental hazards

ADR/RID/ICAO-IATA: Product is not environmentally hazardous IMDG: Marine polluting agent : No

14.6. Special precautions for user

The transport must be carried out by authorized vehicles for the transport of dangerous goods in accordance with the requirements of the applicable Edition of the agreement A.D.R. and national provisions. The transport must be carried out in the original packaging and in packages that are made from materials resistant to content and not likely to generate with this dangerous reactions. The process of loading and unloading of dangerous goods have received adequate training on the risks presented by prepared and on possible procedures to be taken in the event of emergency situations

14.7. Maritime transport in bulk according to IMO instruments

Transport in bulk is not foreseen

SECTION 15. Regulatory information

Geowin SDS rel. 10







CELON MPB

Issued on 03/24/2022 - Rel. # 7 on 03/24/2022

14 / 15

In conformity to Regulation (EU) 2020/878

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions relating to the product or contained substances (All. XVII Reg. EC 1907/2006): not applicable Substances in Candidate List (art. 59 Reg. EC 1907/2006): the product does not contain SVHC in a proportion $\ge 0.1\%$. Substances subject to authorisation (Ann. XIV Reg. CEC 1907/2006): the product does not contain SVHC in a proportion $\ge 0.1\%$. Reg. EC 648/04: see 2.2 Reg. (EU) n. 1169/2011: see 2.2 Reg (UE) 528/2012: see.to 2.2

REGULATION (EU) No 1357/2014 - waste: HP8 - Corrosive

15.2. Chemical safety assessment

No chemical safety assessment was carried out by the supplier

SECTION 16. Other information

16.1. Other information

Points modified compared to previous release: 2.2. Label elements

Description of hazard statements set out in paragraph 3

H272 = May intensify fire; oxidiser.

H290 = May be corrosive to metals.

H314 = Causes severe skin burns and eye damage.

H331 = Toxic if inhaled.

H318 = Causes serious eye damage.

Classification based on data of all mixture components

Main normative references:

Reg. (CE) n. 1907 del 18/12/06 REACH (Registration, Evaluation and Authorisation of CHemicals) et seq.
Reg. (CE) 1272/2008 CLP (Classification Labelling and Packaging) et seq.
Regulation (EC) n. 648 of 31/03/04 (on detergents) et seq.
Regulation (UE) n. 1169/2011 (on the provision of food information to consumers)
Directive 2012/18/EU (on the control of major-accident hazards involving dangerous substances) et seq.
Regulation (UE) 528/2012 (Biocides) et seq.

Procedure used to classify under CLP mixture (Reg . EC 1272/2008):

Physical hazards: On the basis of experimental data H314 Skin. Corr. 1A: On the basis of experimental data / Calculation Method Other hazards: Calculation Method

Training required: This document must be submitted to the employer to determine the possible need for appropriate training for workers to ensure protection of human health and the environment.

n.a.: not applicable
n.d.: not available
ADR: Accord europèen relative au transport International des merchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
ATE: Acute Toxicity Estimat
BFC: BioconCentration Factor
BOD: Biochemical Oxigen Demand
CAS: Chemical Abstract Service number



CELON MPB

Issued on 03/24/2022 - Rel. # 7 on 03/24/2022

15 / 15

In conformity to Regulation (EU) 2020/878

CAP: Centre AntiPoison CE/EC number EINECS (European Inventory of existing Commercial Substances) e ELINCS (European List of notified Chemical Substances) CL50/LC50: Lethal Concentration 50 DL50/LD50: Lethal Dose 50 COD: Chemical Oxygen Demand DNEL: Derived No Effect Level EC50: half maximal Effective Concentration ERC: Enviroment Release Classes EU/UE: European Union IATA: International Air Transport Association ICAO: International Civil Aviation Organization IMDG: International Maritime Dangerous Goods code Kow: Octanol water partition coefficient NOEC: No Observed Effect Concentration **OEL: Occupational Exposure Limit** PBT: Persistent Bioaccumulative and Toxic PC: Product Categories PNEC: Predicted No Effect Concentration **PROC:** Process Categories RID: Règlement concernent le transport International ferroviaire des merchandises dangereuses (Regulations concerning International rail transport of dangerous goods) STOT: Target Organ Systemic Toxicity STOT (RE): Repeated Exposure STOT (SE): Single Exposure STP: Sewage Treatment Plants SU: Sector of Use SVCH: Substance of Very High Concern TLV: Threshold Limit Value vPvB: Very Persistent Very Bioaccumulative

References and Sources:

- ECHA Registered Substances:
- https://echa.europa.eu/web/guest/information-on-chemicals/registered-substances
- SDS supplier
- · GESTIS DNEL Database: http://www.dguv.de/ifa/gestis/gestis-dnel-datenbank/index-2.jsp
- · GESTIS International Limit Value: http://limitvalue.ifa.dguv.de

This msds was made in good faith by technical Office on the basis of the information available at the date of the last revision. The person in charge must regularly inform the employees about the specific risks they encounter when using this substance/product. The information contained here relate only to the substance/the preparation indicated and may not apply if the product is used improperly or in combination with others. Nothing contained herein shall be construed as a guarantee, either express or implied. It is the responsibility of the user to ensure the opportunities and completeness of the information contained herein for their own particular use.

*** this tab annuls and replaces any previous edition. (IIXX)

Changes to the previous edition: Label elements

Geowin SDS rel. 10

SUMI Safe Use of Mixtures Information



AISE_SUMI_IS_4_2

Version 1.1, August 2018

Industrial uses; Automated task; Semi-automated task; Dedicated equipment

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

The SUMI applies to industrial uses where products are used in closed process where opportunity for exposure arises. This Safe Use Information is based on the **AISE_SWED_IS_4_2**.

Operational Conditions

Maximum duration	480 minutes per day.
Range of application /	Indoor Use.
Process conditions	Process carried out at room temperature.
	In case of dilution, tap water at a maximum temperature of 45°C is used.
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per
	hour). No LEV required.

Risk Management Measures

Measures related to	Wear suitable gloves.
personal protective equipment (PPE), hygiene and health evaluation	See section 8 of the SDS of this product for specifications.
	Training of workers in relation to proper use and maintenance of PPEs must be ensured.
Environmental	Prevent that undiluted product reaches surface waters.
measures	If appropriate AISE SPERC 8a.1.a.v2 may apply : wide dispersive use resulting in release to municipal sewage treatment plant.

Additional good practice advice

Don't eat or drink. Don't smoke. Don't use in proximity of open flame.	
Wash hands after use. Avoid contact with damaged skin. Do not mix with other products.	
Spillage instructions	Dilute with fresh water and mop up.
Hygiene practices	Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS.

Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

Disclaimer

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling.

If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself.

Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product.

This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk.

A.I.S.E. disclaims any liability to any person or entity for any loss, damage no matter of what kind (actual, consequential, punitive or otherwise), injury, claim, liability or other cause of any kind or character based upon or resulting from the use (even partly) of the content of this document.

CELON MPB

SUMI Safe Use of Mixtures Information



AISE_SUMI_IS_8b_1

Version 1.1, August 2018

Transfer and dilution of concentrated product by using dedicated dosing system

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

This SUMI applies to industrial uses where products are transferred to or diluted in a dedicated dosing system. This Safe Use Information is based on the AISE_SWED_IS_8b_1_L and AISE_SWED_IS_8b_1_S

Operational Conditions

Maximum duration	60 minutes per day.
Range of application /	Indoor Use.
Process conditions	Process carried out at room temperature.
	In case of dilution, tap water at a maximum temperature of 45°C is used.
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per
	hour). No LEV required.

Risk Management Measures

Measures related to	Wear suitable gloves.
personal protective	See section 8 of the SDS of this product for specifications.
equipment (PPE),	
hygiene and health	
evaluation	
	Training of workers in relation to proper use and maintenance of PPEs
	must be ensured.
Environmental	Prevent that undiluted product reaches surface waters.
measures	If appropriate AISE SPERC 8a.1.a.v2 may apply: wide dispersive use
	resulting in release to municipal sewage treatment plant.

Additional good practice advice

Don't eat or drink. Don't smoke. Don't use in proximity of open flame.	
Wash hands after use. Avoid contact with damaged skin. Do not mix with other products.	
Spillage instructions	Dilute with fresh water and mop up.
Hygiene practices	Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS.

Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

Disclaimer

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling.

If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself.

Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product.

This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk.

A.I.S.E. disclaims any liability to any person or entity for any loss, damage no matter of what kind (actual, consequential, punitive or otherwise), injury, claim, liability or other cause of any kind or character based upon or resulting from the use (even partly) of the content of this document.

CELON MPB

SUMI Safe Use of Mixtures Information



AISE_SUMI_IS_13_3_G

Version 1.1, August 2018

Industrial uses; Treatment of articles by dipping or pouring

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

This SUMI applies to industrial uses where articles are treated by dipping or pouring. This Safe Use Information is based on the **AISE_SWED_IS_13_3**.

Operational Conditions

Maximum duration	480 minutes per day.
Range of application /	Indoor Use.
Process conditions	Process carried out at room temperature.
	In case of dilution, tap water at a maximum temperature of 45°C is used.
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per
	hour). No LEV required.

Risk Management Measures

Measures related to	Wear suitable gloves and eye protection.
personal protective equipment (PPE),	See section 8 of the SDS of this product for specifications.
hygiene and health evaluation	
	Training of workers in relation to proper use and maintenance of PPEs must be ensured.
Environmental	Prevent that undiluted product reaches surface waters.
measures	If appropriate AISE SPERC 8a.1.a.v2 may apply: wide dispersive use
	resulting in release to municipal sewage treatment plant.

Additional good practice advice

Don't eat or drink. Don't smoke. Don't use in proximity of open flame.	
Wash hands after use. Avoid contact with damaged skin. Do not mix with other products.	
Spillage instructions	Dilute with fresh water and mop up.
Hygiene practices	Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS.

Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

Disclaimer

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling.

If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself.

Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product.

This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk.

A.I.S.E. disclaims any liability to any person or entity for any loss, damage no matter of what kind (actual, consequential, punitive or otherwise), injury, claim, liability or other cause of any kind or character based upon or resulting from the use (even partly) of the content of this document.

WORKING ISTRUCTION TABLE



This tab provides instructions for appropriate and safe use of products and proper management of emergency situations for cleaning staff/users.

Attached to MSDS rel#7 03/24/2022

Use description	Use in batch and other process (synthesis) where opportunity for exposure arises [PROC4]; Transfer of substance or mixture (charging and discharging) at dedicated facilities [PROC8b]; Application with rollers or brushes [PROC10]; Treatment of articles by dipping and pouring [PROC13]
Product name	CELON MPB
Classification of the product (100%)	H290 - May be corrosive to metals. H314 - Causes severe skin burns and eye damage. H318 - Causes serious eye damage. H332 - Harmful if inhaled. EUH071 - Corrosive to the respiratory tract.
Classification of the diluted product (maximum use concentration)	At maximux concentration of use (3%) the product is classified: H314 - Causes severe skin burns and eye damage. H318 - Causes serious eye damage.
Handling of the product (100%)	Avoid contact and inhalation of vapors Wear protective gloves/protective clothing/eye protection/face protection. At work do not eat or drink.
Handling of the diluted product	Avoid contact and inhalation of vapors Wear protective gloves/protective clothing/eye protection/face protection. At work do not eat or drink.
DPI required concentrated use, spillage)	Chemical resistant protective gloves (EN 374-1/EN374-2/EN374-3), safety glasses (EN 166).
Diluited product	Chemical resistant protective gloves (EN 374-1/EN374-2/EN374-3), safety glasses (EN 166).

In case of emergency (accidents involving exposure to the product)	Immediately inform the customer. Immediately inform the employer. Contact Poisons Centres tel. number in 1.4 section of the MSDS
Accidental release large quantities measures: concentrated product	Wear mask,gloves, glasses and protective clothing (for specifications refer to section 8.2. SDS) Possibly absorb it with inert materia or sucked it. After wiping up, wash with water the area and materials involved
Diluited product	Wear mask, gloves, glasses and protective clothing. Wash with water the area and materials involved
Storage of the product	Keep in original container closed tightly. Do not store in open or unlabelled containers. Keep containers upright and safe by avoiding the possibility of falls or collisions. Store in a cool and dry place, away from heat sources and direct exposure to sunlight.
In case of accidents, emergency or fire	Immediately inform the customer. Follow company emergency instruction.