# AEB IMPROVEMENT THROUGH BIOTECHNOLOGY

#### SAFETY DATA SHEET

#### **IDROSAN**

Issued on 12/16/2021 - Rel. # 10 on 12/16/2021

#1/18

In conformity to Regulation (EU) 2020/878

## SECTION 1. Identification of the substance/mixture and of the company/enterprise

#### 1.1. Product identifier

Product name: IDROSAN

Product code: refer to sales department

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Chloroactive alkaline detergent

Sectors of use:

Industrial Manufacturing[SU3], Manufacture of food products[SU4], Public domain (administration, education, entertainment, services, craftsmen)[SU22]

Product category:

Washing and Cleaning Products (including solvent based products)

Process categories:

Use in batch and other process (syn-thesis) where opportunity for exposure arises[PROC4], Industrial spraying[PROC7], Transfer of substance or mixture (charging and discharging) at nondedicated facilities[PROC8A], Transfer of substance or mixture (charging and discharging) at dedicated facilities[PROC8B], Non industrial spraying[PROC11], Application with rollers or brushes [PROC10], Treatment of articles by dipping and pouring [PROC13]

Not recommended uses

Do not use for purposes other than those listed

#### 1.3. Details of the supplier of the safety data sheet

AEB SpA - Via Vittorio Arici 104 S.Polo - 25134 Brescia (BS) Italy

Tel. +39.030.2307.1 Fax +39.030.2307281

E-mail: info@aeb-group.com - Internet: www.aeb-group.com E-mail tecnico competente/technical dept.: sds@aeb-group.com

AEB USA 111 N Cluff Avenue Lodi CA 95240 (USA)

Tel: +1 2096258139 Fax: +1 2092248953

Email: info@aebusa.com - Internet: www.aeb-group.com

\_\_\_\_\_

AEB AFRICA (PTY) LTD 18 Track Crescent, Cor. Station Road Montague Gardens 7441 Cape Town (South Africa)

Tel.: +27 215512700 - Fax: +27 (0) 215511919

Email: info@aeb.co.za - Internet: www.aeb-group.com

AEB OCEANIA PTY LTD 178A Wakaden Street Griffith NSW 2680 T: 1300 704 971

Email: aeboceania@aeb-group.com - Internet: www.aeb-group.com

Produced by AEB SpA Via Vittorio Arici 104 S. Polo



#### **IDROSAN**

Issued on 12/16/2021 - Rel. # 10 on 12/16/2021

#2/18

In conformity to Regulation (EU) 2020/878

25134 Brescia

#### 1.4. Emergency telephone number

AEB SpA

Centralino/Switchboard: +39.030.2307.1 - (h 8.30-12.00 13.30-18.00 GMT +1; Lingua/Language: Italiano, English)

**AEB USA** 

Switchboard: +1 2096258139 (GMT -8; Language: English)

AEB AFRICA (PTY) LTD

Switchboard: +27 215512700 (GMT +1; Language: English, Afrikaans)

\_\_\_\_\_

AEB OCEANIA PTY LTD

Switchboard: +61 1300 704 971 (GMT +9; Language: English)

#### **SECTION 2. Hazards identification**

#### 2.1. Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) No 1272/2008:

Pictograms:

GHS05, GHS09

Hazard Class and Category Code(s):

Met. Corr. 1, Skin Corr. 1A, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 2

Hazard statement Code(s):

H290 - May be corrosive to metals.

H314 - Causes severe skin burns and eye damage.

H318 - Causes serious eye damage.

H400 - Very toxic to aquatic life. (Acute toxicity M-factor = 1)

H411 - Toxic to aquatic life with long lasting effects.

The product can be corrosive to metals

Corrosive product: causes severe skin burns and eye damage.

If brought into contact with eyes, the product causes serious damages to eyes, such as an opaque cornea or injury to iris.

The product is dangerous for the environment as it is very toxic to aquatic organisms

The product is dangerous to the environment as it is toxic to aquatic life with long lasting effects

#### 2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008:

Pictogram, Signal Word Code(s): GHS05, GHS09 - Danger



Hazard statement Code(s):

H290 - May be corrosive to metals.

H314 - Causes severe skin burns and eye damage.

H410 - Very toxic to aquatic life with long lasting effects.

# AEB IMPROVEMENT THROUGH BIOTECHNOLOGY

#### SAFETY DATA SHEET

#### **IDROSAN**

Issued on 12/16/2021 - Rel. # 10 on 12/16/2021

#3/18

In conformity to Regulation (EU) 2020/878

Supplemental Hazard statement Code(s):

EUH031 - Contact with acids liberates toxic gas (Cl2)

#### Precautionary statements:

Prevention

P260 - Do not breathe vapours/spray.

P280 - Wear protective gloves/clothing and eye/face protection.

Response

P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Disposal

P501 - Dispose of contents/container to local/regional/national/international regulations

#### Contains:

Sodium hypochlorite, Sodium hydroxide

Contains (Reg.EC 648/2004):

5% < 15% chlorine-based bleaching agents,< 5% polycarboxylates

#### 2.3. Other hazards

The substance / mixture does NOT contain substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

Do not ingest. Keep out of reach of children.

## SECTION 3. Composition/information on ingredients

#### 3.1 Substances

Irrilevant

#### 3.2 Mixtures

Refer to paragraph 16 for full text of hazard statements

Substance	Concentration[ w/w]	Classification	Index	CAS	EINECS	REACh
Sodium hydroxide	>= 5 < 10%	Met. Corr. 1, H290; Skin Corr. 1A, H314; Eye Dam. 1, H318 Limits: Skin Corr. 1A, H314 %C >=5; Skin Corr. 1B, H314 2<= %C <5; Eye Irrit. 2, H319 0,5<= %C <2; Eye Dam. 1, H318 %C >=2; Skin Irrit. 2, H315 %C >=0,5;	011-002-00-6	1310-73-2	215-185-5	01-2119457 892-27-XXX X
Sodium hypochlorite	>= 5 < 10%	EUH031; Met. Corr. 1, H290; Skin Corr. 1B,	017-011-00-1	7681-52-9	231-668-3	01-2119488 154-34-XX



#### **IDROSAN**

Issued on 12/16/2021 - Rel. # 10 on 12/16/2021

#4/18

#### In conformity to Regulation (EU) 2020/878

Substance	Concentration[ w/w]	Classification	Index	CAS	EINECS	REACh
Note B		H314; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Limits: , EUH031 %C >=5; Acute toxicity M-factor = 10 Chronic toxicity M-factor = 1				xx
Polycarboxylate substance for which there are Community workplace exposure limits	>= 0,1 < 1%					

## **SECTION 4. First aid measures**

## 4.1. Description of first aid measures

In case of skin contact: immediately take off all contaminated clothing and dispose of them safely. SEEK MEDICAL ADVICE IMMEDIATELY. In case of contact with skin, wash immediately with plenty of water and soap. In case of contact with the eyes: rinse them with water for an adequate amount of time and keeping the eyelids open, then immediately consult an ophthalmologist. Protect the uninjured eye.

In case of ingestion: DO NOT induce vomiting.

In case of inhalation: take the injured person to fresh air and keep him warm and at rest.

#### 4.2. Most important symptoms and effects, both acute and delayed

Inhalation can produce a burning sensation, cough, difficulty breathing and sore throat. Contact with the skin produces redness, burns and pain. Contact with eyes produces severe redness, pain and deep burns. Ingestion causes severe irritation or chemical burns in the mouth, throat, esophagus and stomach.

## 4.3. Indication of any immediate medical attention and special treatment needed

In the event of an accident or if you feel unwell, consult a doctor immediately (if possible show the instructions for use or the safety data sheet).

Treatment: The severity of injuries and the prognosis of intoxication are directly dependent on the concentration and duration of exposure. Symptomatic treatment

#### SECTION 5. Firefighting measures

## 5.1. Extinguishing media

The product is not flammable. In the event of a large fire, all extinguishing agents are permitted. Unsuitable extinguishing media: none in particular

# **AEB**

#### SAFETY DATA SHEET

#### **IDROSAN**

Issued on 12/16/2021 - Rel. # 10 on 12/16/2021

#5/18

In conformity to Regulation (EU) 2020/878

#### 5.2. Special hazards arising from the substance or mixture

Do not inhale the gases produced by the explosion and combustion

#### 5.3. Advice for firefighters

Use suitable respiratory equipment. Collect contaminated water used to extinguish the fire separately. Do not discharge it into the sewer system. If feasible from a safety perspective, move undamaged containers from the area of immediate danger

#### SECTION 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1 For non-emergency personnel:

Move away from the area surrounding the spill or release. Wear a mask, gloves and protective clothing.

#### 6.1.2 For emergency responders:

Eliminate all open flames and possible sources of ignition. Not smoking. Provide adequate ventilation. Evacuate the danger area and, if necessary, consult an expert.

#### 6.2. Environmental precautions

Contain spills with earth or sand.

If the product has entered a watercourse, sewers or has contaminated soil or vegetation, notify the authorities. Dispose of the waste material in compliance with the regulations

#### 6.3. Methods and material for containment and cleaning up

#### 6.3.1 Containment:

Rapidly recover the product, wear a mask and protective clothing (for specifications refer to section 8.2. SDS) Recover the product for reuse, if possible, or for removal. Possibly absorb it with inert materia or sucked it. Prevent it from entering the sewer system.

## 6.3.2 Cleaning up:

After wiping up, wash with water the area and materials involved

### 6.3.3 Other information:

Wash with plenty of water

#### 6.4. Reference to other sections

Refer to paragraphs 8 and 13 for more information

## **SECTION 7. Handling and storage**

#### 7.1. Precautions for safe handling

Avoid contact and inhalation of vapors Wear protective gloves/clothing and eye/face protection.



#### **IDROSAN**

Issued on 12/16/2021 - Rel. # 10 on 12/16/2021

#6/18

In conformity to Regulation (EU) 2020/878

Handle the product after consulting all other sections of this safety data sheet.

At work do not eat or drink.

See also paragraph 8 below.

### 7.2. Conditions for safe storage, including any incompatibilities

Keep in original container closed tightly. Do not store in open or unlabelled containers.

Keep containers upright and safe by avoiding the possibility of falls or collisions.

Store in a cool and dry place, away from heat sources and direct exposure to sunlight.

#### 7.3. Specific end use(s)

Industrial Manufacturing:

Handle with care. Store in a well-ventilated place away from heat sources (7-30  $^{\circ}$  C) and in the original, well-closed containers.

Follow the attached exposure scenarios

Manufacture of food products:

Handle with care. Store in a well-ventilated place and away from heat sources (7-30 ° C) and in the original well-closed containers.

Follow the attached exposure scenarios

Public domain (administration, education, entertainment, services, craftsmen):

Handle with care. Store in a well-ventilated place and away from heat sources (7-30 ° C) and in the original well-closed containers.

Follow the attached exposure scenarios

See the annex exposure scenario.

## SECTION 8. Exposure controls/personal protection

#### 8.1. Control parameters

==============

Related to contained substances:

Sodium hydroxide: Limit value – Eight hours

(ppm)/(mg/m3) Austria: x/2 inhalable aerosol

Belgium: x/2 (1) Denmark: x/2 France: x/2 Hungary: x/2

Japan (JSOH): x/2(1)

Latvia: x/0,5 Poland: x/0,5 Romania: x/1 Spain: x/2 Sweden: x/1 (1)

Switzerland: x/2 inhalable aerosol (MAK)

USA - OSHA: x/2

Limit Value - Short Term

(ppm)/(mg/m3) Austalia: x/2(1)

Austria: x/4 inhalable aerosol Canada - Ontario: x/2(1) Canada – Québec: x/2(1)

Denmark: x/2 Finland: x/2(1)



#### **IDROSAN**

Issued on 12/16/2021 - Rel. # 10 on 12/16/2021

#7/18

In conformity to Regulation (EU) 2020/878

Hungary: x/2 Ireland: x/2(1) New Zealand: x/2(1)

People's Republic of China: x/2(1)

Poland: x/1 Romaniax/3(1) Singapore: x/2 South Korea: x/2(1) Sweden: x/2(1)(2)

Switzerland: x/2 inhalable aerosol (MAK)

USA – NIOSH: x/2(1) United Kingdom: x/2

Remarks:

Australia: (1) Celling limit value

Canada – Ontario: (1) Celling limit value Canada – Québec: (1) Celling limit value

Finland: (1) Celling limit value

Ireland: (1) 15 minutes reference period

Japan: (1) Occupational exposure limit ceiling: Reference value to the maximal exposure concentration of the

substance during a working day New Zealand: (1) Celling limit value

People's Republic of China: (1) Celling limit value

South Korea: (1) Celling limit value Romania: (1) 15 minutes average value

Sweden: (1) Inhalable dust (2) Celling limit value USA – NIOSH: (1) Celling limit value (15 min)

Argentine: CMP-C: 2 mg mg/m3

Czech Republic: PEL 1 mg/m3/ NPK-P 2 mg/m3

Italy: OEL: ACGIH -STEL: C 2.0 mg/m3; Tipo OEL: ACGIH - STEL: C2 mg/m3 - Note: URT, eye, and skin irr Estonia: short-term esposure limit (maximum chemical substance average allowable concentration in inhaled air - 15 minutes) 2 mg/m3(Ceiling limit" means a maximum permissible continuous concentration of 15 minutes in the air for rapidly acting substances)

Norvay: ceiling value (a moment value that indicates the maximum concentration of a chemical in the breathing zone that should not be exceeded) 2 mg/m3

Lithuania: NRD 2 mg/m3 Slovakia: NPEL 2 mg/m3

South Africa: Short Term OEL-CL 2 mg/m3

Sodium hypochlorite:

Substance: Chlorine (CAS 7782-50-0)

Limit value - Eight hours

(ppm)/(mg/m³)

Austria: 0,5/1,5

Canada – Ontario: 0,5/-Canada - Québec: 0,5/1,5

Denmark: 0,5/1,5 Germany (AGS): 0,5/1,5 Germany (DFG): 0,5/1,5

Israel: 0,5/1,5 Japan: 0,5/x

Japan - JSOH: 0,5(1)/1,5(1)

Latvia: 0,3/1

New Zealand: 0,5/1,5

Poland: x/0,7 Singapore: 0,5/1,5 South Korea: 0,5/1,5

# AEB

#### SAFETY DATA SHEET

#### **IDROSAN**

Issued on 12/16/2021 - Rel. # 10 on 12/16/2021

#8/18

In conformity to Regulation (EU) 2020/878

Switzerland: 0,5/1,5

Limit value - Short term

 $(ppm)/(mg/m^3)$ 

Australia: 1(1)/3(1) Austria: 0,5/1,5 Belgium: 0,5/1,5 Canada – Ontario: 1/-Canada - Québec: 1/2,9

Denmark: 1/3

European Union: 0,5(1)/1,5(1)

Finland: 0,5(1)/1,5(1)

France: 0,5/1,5

Germany (AGS): 0,5(1)/1,5(1) Germany (DFG): 0,5/1,5

Hungary: x/1,5 Italy: 0,5/1,5 Latvia: 0,5(1)/1,5(1) New Zealand: 1/2,9

People's Republic of China: x/1(1)

Poland: x/1,5

Romania: 0,5(1)/1,5(1) Singapore: 1/2,9 South Korea: 1/3 Spain: 0,5/1,5

Sweden: 0,5(1)/1,5(1) Switzerland: 0,5/1,5 The Netherlands: x/1,5 Turkey: 0,5(1)/1,5(1) USA-NIOSH: 0,5(1)/1,42(1)

USA-OSHA: 1(1)/3(1) United Kingdom: 0,5/1,5

#### Remarks

Australia - People's Republic of China - USA-NIOSH: 1) Ceiling limit value

European Union: Bold-type: Indicative Occupational Exposure Limit Values and Limit Values for Occupational Exposure Binding Occupational Exposure Limit Value - BOELV ~ (1) 15 minutes average value (for references see bibliography)

Finland - Germany (AGS) - Latvia- Romania - Turkey: (1) 15 minutes average value

France: Bold type: Restrictive statutory limit values Germany (DFG): STV 15 minutes average value

Ireland: (1) 15 minutes reference period

Japan – JSOH: (1) Occupational exposure limit ceiling: Reference value to the maximal exposure concentration of the

substance during a working day Sweden: (1) Short-term limit value

#### Polycarboxylate:

TWA respirable dust fraction (DOW IHG): 0,5 mg/m3

- Substance: Sodium hydroxide

**DNEL** 

Systemic effects Short term Workers inhalation = 1 (mg/m3) Systemic effects Short term Consumers inhalation = 1 (mg/m3) Local effects Short term Workers inhalation = 1 (mg/m3) Local effects Short term Consumers inhalation = 1 (mg/m3)

- Substance: Sodium hypochlorite

# **AEB**

#### SAFETY DATA SHEET

#### **IDROSAN**

Issued on 12/16/2021 - Rel. # 10 on 12/16/2021

#9/18

In conformity to Regulation (EU) 2020/878

#### DNEL

Systemic effects Long term Workers inhalation = 1,55 (mg/m3) Systemic effects Long term Consumers inhalation = 1,55 (mg/m3) Systemic effects Short term Workers inhalation = 3,1 (mg/m3) Systemic effects Short term Consumers inhalation = 3,1 (mg/m3) Local effects Long term Workers inhalation = 1,55 (mg/m3) Local effects Long term Consumers inhalation = 1,55 (mg/m3) Local effects Short term Workers inhalation = 3,1 (mg/m3) Local effects Short term Consumers inhalation = 3,1 (mg/m3) PNEC Sweet water = 0,00021 (mg/l) Sea water = 0,000042 (mg/l)

#### 8.2. Exposure controls

intermittent emissions = 0,00026 (mg/l)

Appropriate engineering controls:

Industrial Manufacturing:

STP = 0.03 (mg/l)

No specific monitoring foreseen (act according to good practice and specific rules for the type of risk associated)

Manufacture of food products:

No specific monitoring foreseen (act according to good practice and specific rules for the type of risk associated)

Public domain (administration, education, entertainment, services, craftsmen):

No specific monitoring foreseen (act according to good practice and specific rules for the type of risk associated)

#### 8.2.2 Individual protection measures:

(a) Eye / face protection

Safety goggles with side protection for chemicals (EN166).

- (b) Skin protection
- (i) Hand protection

When handling the pure product use chemical resistant protective gloves (EN 374-1/EN374-2/EN374-3)

(ii) Other

When handling the pure product, wear full protective clothing (generic workwear / antacid, safety shoes S3-EN ISO 20345) or other protective equipment, according to the instructions of the employer

(c) Respiratory protection

Not needed for normal use. None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. During manual operations in case of insufficient ventilation, use mask with gas filters and inorganic vapors - Grey , Class 3 , B (EN 405) unless otherwise provided by the employer and / or assessments of environmental investigations hygienistic

(d) Thermal hazards No hazard to report

Environmental exposure controls:

Use according to good working practices and avoid to disperse the product into the environment.



## **IDROSAN**

Issued on 12/16/2021 - Rel. # 10 on 12/16/2021

# 10 / 18

In conformity to Regulation (EU) 2020/878

## **SECTION 9. Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Physical and chemical properties	Value	Determination method
Appearance	clear liquid	
Colour	yellow	
Odour	chlorine	
Odour threshold	not determined as it is considered not relevant for the characterization of the product	
рН	> 12 (20 ° C); > 12 (20 ° C, sol 5%)	
Melting point/freezing point	not determined as it is considered not relevant for the characterization of the product	
Initial boiling point and boiling range	not determined as it is considered not relevant for the characterization of the product	
Flash point	not determined as it is considered not relevant for the characterization of the product	ASTM D92
Evaporation rate	not determined as it is considered not relevant for the characterization of the product	
Flammability (solid, gas)	not determined as it is considered not relevant for the characterization of the product	
Upper/lower flammability or explosive limits	not determined as it is considered not relevant for the characterization of the product	
Vapour pressure	not determined as considered not relevant for the characterization of the product	
Vapour density	not determined as it is considered not relevant for the characterization of the product	
Relative density	1.20 ± 0.05 (20 ° C)	
Solubility	in water	
Water solubility	miscible in all proportions	
Partition coefficient: n-octanol/water	not determined as it is considered not relevant for the characterization of the product	
Auto-ignition temperature	not determined as it is considered not relevant for the characterization of the product	
Decomposition temperature	not determined as it is considered not relevant for the characterization of the product	
Viscosity	not determined as it is considered not relevant for the characterization of the product	
Explosive properties	not determined as it is considered not relevant for the characterization of the product	
Oxidising properties	not determined as it is considered not relevant for the characterization of the product	

## 9.2. Other information

No data available.

## **SECTION 10. Stability and reactivity**

# **AEB**

#### SAFETY DATA SHEET

#### **IDROSAN**

Issued on 12/16/2021 - Rel. # 10 on 12/16/2021

#11/18

In conformity to Regulation (EU) 2020/878

#### 10.1. Reactivity

Mixture containing sodium hypochlorite. It can be corrosive to metals. It is not pyrophoric.

#### 10.2. Chemical stability

Stable under the indicated conditions of use and storage

#### 10.3. Possibility of hazardous reactions

Very exothermic reaction with acids, amines

#### 10.4. Conditions to avoid

Light, heat.

#### 10.5. Incompatible materials

Acids Amines Metals Combustible materials

## 10.6. Hazardous decomposition products

Toxic gas (chlorine)

## SECTION 11. Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

(a) acute toxicity: Sodium hydroxide: Ingestion - LD50 rat (mg / kg / 24h bw): nd

Skin contact - LC50 rabbit (mg / kg / 24h bw): 1350

Inhalation - LD50 rat (mg / I / 4h): nd

Sodium hypochlorite: Ingestion - LD50 rat (mg / kg / 24h bw):> 5000

Skin contact - LC50 rat / rabbit (mg / kg / 24h bw):> 20000

Inhalation - LD50 rat (mg / I / 4h):> 10, 5

Polycarboxylate: Ingestion - LD50 rat (mg / kg / 24h bw):> 5000

Contact with skin - LD50 rabbit (mg / kg / 24h bw):> 5000

Inhalation - LC50 rat (mg / I / 4h): nd

(b) skincorrosion/irritation: Corrosive product: causes severe skin burns and eye damage.



#### **IDROSAN**

Issued on 12/16/2021 - Rel. # 10 on 12/16/2021

# 12 / 18

In conformity to Regulation (EU) 2020/878

Sodium hydroxide: Corrosive Sodium hypochlorite: Corrosive Polycarboxylate: Non-corrosive Sodium hydroxide: Irritating Sodium hypochlorite: Irritating Polycarboxylate: Slightly irritating

(c) serious eye damage/irritation: Corrosive product: causes severe skin burns and eye damage. - If brought into contact with eyes, the product causes serious damages to eyes, such as an opaque cornea or injury to iris.

Sodium hydroxide: Corrosive Sodium hypochlorite: Corrosive Polycarboxylate: Non-corrosive Sodium hydroxide: Irritating Sodium hypochlorite: Irritating Polycarboxylate: Slightly irritating

(d) respiratoryorskinsensitisation: Sodium hydroxide: Not sensitizing

Sodium hypochlorite: Not sensitizing Polycarboxylate: Non-sensitizing

(e) germ cell mutagenicity: Sodium hydroxide: NaOH did not induce mutagenicity in in vitro and in vivo studies (EU

RAR, 2007; section 4.1.2.7, page 73). Sodium hypochlorite: Not mutagenic Polycarboxylate: Non-mutagenic

(f) carcinogenicity: Sodium hydroxide: Systemic carcinogenicity is not expected to occur as NaOH is not expected to be systemically available in the body under normal conditions of handling and use. Finally, adequate studies are not available to assess the risk on local carcinogenic effects.

Sodium hypochlorite: Not carcinogenic Polycarboxylate: Non-carcinogenic

(g) eproductivetoxicity: Sodium hydroxide: NaOH is not expected to be systemically available in the body under normal conditions of handling and use and for this reason it can be said that the substance will neither reach the fetus nor reach the male and female reproductive organs (EU RAR Sodium Hydroxide (2007), section 4.1.2.8, page 73). It can be concluded that a specific study is not required to determine reproductive toxicity.

Sodium hypochlorite: Non-toxic for reproduction

Polycarboxylate: Not available

(h) specific target organ toxicity (STOT) single exposure: Sodium hydroxide: The substance can be absorbed into the body by inhalation of its aerosol, by ingestion and by contact with the skin causing corrosion

Sodium hypochlorite: It can be irritating to the respiratory tract

Polycarboxylate: Not available

(i) specific target organ toxicity (STOT) repeated exposureSodium hydroxide: The introductory sections of Annexes VII-X indicate a specific adaptation to standard information requirements as in vivo testing should be avoided with corrosive substances at concentration / dose levels causing corrosivity. However, NaOH is not expected to be systemically available in the body under normal conditions of handling and use and therefore no systemic effects of NaOH are expected after repeated exposure (EU RAR sodium hydroxide (2007); section 4.1.3.1.4, page 76 ).

Sodium hypochlorite: Not classified Polycarboxylate: Not available

(j) aspiration hazard: Sodium hydroxide: Not available

Sodium hypochlorite: Not available Polycarboxylate: Not available

### 11.2. Information on other hazards

No data available.

## **SECTION 12. Ecological information**

#### 12.1. Toxicity

Related to contained substances:

# **AEB**

#### SAFETY DATA SHEET

#### **IDROSAN**

Issued on 12/16/2021 - Rel. # 10 on 12/16/2021

# 13 / 18

In conformity to Regulation (EU) 2020/878

Sodium hydroxide:

Acute toxicity - fish LC50 (mg / I / 96h): 45

Acute toxicity - crustaceans EC50 (mg / I / 48h): 40

Acute toxicity to algae ErC50 (mg / I / 72-96h): n.d

Chronic toxicity - fish NOEC (mg / I): n.d

Chronic toxicity - crustaceans NOEC (mg / I): n.d

Chronic toxicity to algae NOEC (mg / I): n.d

Available data indicate that NaOH concentrations of approximately 20 to 40 mg / L may be acutely toxic to fish and invertebrates (single species test). There is a lack of data on the increase in pH due to the addition of these quantities of NaOH in the test waters used. In waters with relatively low buffering capacity, NaOH concentrations of 20-40 mg / L may lead to an increase in pH with one or more pH units (EU RAR, 2007; section 3.2.1.1.3, page 30).

The OECD SIDS (2002) assigned a low reliability code ("invalid" or "not assignable") to all available tests, since in general the tests were not conducted according to current guidelines (EU RAR, 2007; section 3.2. 1.1.4, page 30). Furthermore, in many test reports there were no data on pH, buffer capacity and / or composition of the test medium, although this is essential information for NaOH toxicity testing. This is the most important reason why most of the tests were considered "invalid". Despite this lack of valid data, it is not necessary to perform further aquatic toxicity tests with NaOH, as all available tests have resulted in a rather small range of toxicity values (acute toxicity test: 20 to 450 mg / L; test chronic toxicity:> or = 25 mg / L) and there are sufficient data on the pH ranges tolerated by the main taxonomic groups.

Furthermore, a generic PNEC cannot be derived from the single species toxicity data for NaOH, as the pH of natural waters and the buffering capacity of natural waters show considerable differences and aquatic organisms / ecosystems are adapted to these specific natural conditions, with resulting in different pH optima and tolerated pH ranges (EU RAR, 2007; section 3.2.1.1.4, page 30). According to the OECD SIDS (2002), a lot of information is available on the relationship between pH and ecosystem structure, and natural changes in the pH of aquatic ecosystems have also been quantified and widely reported in ecological publications and manuals. C(E)L50 (mg/l) = 45

#### Sodium hypochlorite:

cute toxicity - LC50 freshwater fish (mg / I / 96h): 0.060 Acute toxicity - LC50 seawater fish (mg / I / 96h): 0.032

Acute toxicity - Daphnie EC50 (mg / I / 48h): 0.048

Acute toxicity - Daphnia Magna, fresh water EC50 (mg / I / 48h): 0.141 Acute toxicity - Ceriodaphnia dubia, fresh water EC50 (mg / I / 48h): 0.035 Acute toxicity - Cassostrea Virginica, sea water EC50 (mg / I / 48h): 0.026

Acute toxicity ErC50 algae (mg / I / 72-96h): 0.0183

Acute toxicity - Pseudokirchnerella subcapitata EC50 (mg / I / 96h): 0.04 Acute toxicity - Myriophyllum spicatum, fresh water EC50 (mg / I / 96h): 0.1

Chronic toxicity - fish, sea water NOEC 28 die (mg / I): 0.04

Chronic toxicity - crustaceans NOEC 7 die (mg / I): 0,007 (oyster)

Chronic toxicity Pseudokirchnerella subcapitata ErC10 (mg / I): 0.03

Chronic toxicity Pseudokirchnerella subcapitata NOEC (mg / I): 0.017

Chronic toxicity Periphyton algae, fresh water, NOEC 7 die (mg / l): 0.0021

Toxicity, sediment compartment: not classified

Toxicity of the terrestrial compartment: not calssified

C(E)L50 (mg/I) = 0.06 Acute toxicity M-factor = 10

### Polycarboxylate:

LC50, Oncorhynchus mykiss (Rainbow trout), 96 h, 700 mg / I

EC50, Daphnia magna (Water flea), 48 h,> 1 000 mg / I

EC50, Marine algae (Skeletonema costatum), 72 h, Speed of growth, 480 mg / I

# **AEB**

#### SAFETY DATA SHEET

#### **IDROSAN**

Issued on 12/16/2021 - Rel. # 10 on 12/16/2021

# 14 / 18

In conformity to Regulation (EU) 2020/878

For similar material (s)

(NOEC), Daphnia magna (Large water flea), Continuous flow test, 21 d, number of offspring, 12 mg / I For similar material (s)

MATC (Maximum Acceptable Toxicant Level), Daphnia magna (Large water flea), Continuous flow test, 21 d, number of descendants, 17 mg / I

Information on a similar product: CL50, Eisenia fetida (earthworms), 14 days,> 1 000 mg / kg

The product is dangerous for the environment as it is very toxic to aquatic organisms following acute exposure. The product is dangerous for the environment as it is toxic to aquatic organisms following acute exposure.

Use according to good working practices and avoid to disperse the product into the environment.

#### 12.2. Persistence and degradability

Related to contained substances:

Sodium hydroxide:

according to REACH regulation, it is not necessary to conduct the study if the substance is inorganic (Annex VII, adaptation column 2).

Sodium hypochlorite:

Not applicable. It is a strong oxidant. Reacts with organic substances of soil and sediment degrading rapidly.

Polycarboxylate:

The material is expected to biodegrade very slowly (in the environment). It does not pass the OECD / EEC tests for rapid biodegradability.

## 12.3. Bioaccumulative potential

Related to contained substances:

Sodium hydroxide:

According to REACH, it is not necessary to conduct the study if the substance has a low bioaccumulation potential (Annex IX, adaptation column 2). Considering its high water solubility, NaOH should not bioconcentrate in organisms. Log Pow is not applicable for an inorganic compound that dissociates (EU RAR 2007, section 3.1.1 page 19 and section 3.1.3.4, page 26). Furthermore, sodium is an element present in nature prevalent in the environment and to which organisms are regularly exposed, for which they have a certain ability to regulate the concentration of the organism.

Sodium hypochlorite:

Non-bioaccumulative

LogP (calculated) = -3.42

Polycarboxylate:

Not available

#### 12.4. Mobility in soil

Related to contained substances:

Sodium hydroxide:

According to the REACH regulation, it is not necessary to conduct an adsorption / desorption study if, based on the physicochemical properties, the substance can be expected to have a low adsorption potential (Annex VIII, adaptation column 2).

Considering its high water solubility, NaOH should not bioconcentrate in organisms. The high water solubility and low



#### **IDROSAN**

Issued on 12/16/2021 - Rel. # 10 on 12/16/2021

# 15 / 18

In conformity to Regulation (EU) 2020/878

vapor pressure indicate that NaOH will be found primarily in the aquatic environment.

The 73% aqueous NaOH solution at room temperature is a highly viscous gelatinous material and without additional dilution (precipitation), it is not expected to infiltrate the soil to any significant extent. The 50% aqueous NaOH solution is liquid and is expected to infiltrate the soil to a measurable extent. As a dilution of NaOH

increases, increases its speed of movement through the ground. During movement through the ground, some ion exchange will occur.

Also, part of the hydroxide can remain in the aqueous phase and will move down through the soil in the direction of groundwater flow (EU RAR 2007, section 3.1.3, page 24).

Sodium hypochlorite:

Mobile in soil and sediments

Polycarboxylate: Not available

## 12.5. Results of PBT and vPvB assessment

No PBT/vPvB ingredient is present

#### 12.6. Endocrine disrupting properties

No data available.

#### 12.7. Other adverse effects

No adverse effects

Regulation (EC) No 2006/907 - 2004/648

The (I) surfactant (s) content (s) in this preparation complies (comply) with (i) the biodegradability criteria as laid down in Regulation CE/648/2004 on detergents. All data are held at the disposal of the competent authorities of Member States and will be provided, at their direct request or at the request of a detergent manufacturer, to those authorities.

### **SECTION 13. Disposal considerations**

#### 13.1. Waste treatment methods

Do not reuse empty containers. Dispose of them in accordance with the regulations in force. Any remaining product should be disposed of according to applicable regulations by addressing to authorized companies.

Recover if possible. Send to authorized discharge plants or for incineration under controlled conditions. Operate according to local and National rules in force

## **SECTION 14. Transport information**

#### 14.1. UN number or ID number

ADR/RID/IMDG/ICAO-IATA: 3266





If subject to the following characteristics is ADR exempt: Combination packagings: per inner packaging 1 L per package 30 Kg

Inner packaging placed in skrink-wrapped or stretch-wrapped trays: per inner packaging 1 L per package 20 Kg

#### 14.2. UN proper shipping name

ADR/RID/IMDG: LIQUIDO INORGANICO CORROSIVO, BASICO, N.A.S. (Sodio ipoclorito e sodio idrossido in miscela) ADR/RID/IMDG: CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Sodium hypochlorite and Sodium hydroxide in mixture)

ICAO-IATA: CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Sodium hypochlorite and Sodium hydroxide in

# **AEB**

#### SAFETY DATA SHEET

#### **IDROSAN**

Issued on 12/16/2021 - Rel. # 10 on 12/16/2021

# 16 / 18

In conformity to Regulation (EU) 2020/878

mixture)

#### 14.3. Transport hazard class(es)

ADR/RID/IMDG/ICAO-IATA: Class: 8

ADR/RID/IMDG/ICAO-IATA: Label: 8+ ENVIRONMENTALLY HAZARDOUS

ADR: Tunnel restriction code: E

ADR/RID/IMDG/ICAO-IATA: Limited quantities : 1 L

IMDG - EmS: F-A, S-B

#### 14.4. Packing group

ADR/RID/IMDG/ICAO-IATA: II

#### 14.5. Environmental hazards

ADR/RID/ICAO-IATA: Product is environmentally hazardous

IMDG: Marine polluting agent: Yes

## 14.6. Special precautions for user

The transport must be carried out by authorized vehicles for the transport of dangerous goods in accordance with the requirements of the applicable Edition of the agreement A.D.R. and national provisions. The transport must be carried out in the original packaging and in packages that are made from materials resistant to content and not likely to generate with this dangerous reactions. The process of loading and unloading of dangerous goods have received adequate training on the risks presented by prepared and on possible procedures to be taken in the event of emergency situations

## 14.7. Maritime transport in bulk according to IMO instruments

Transport in bulk is not foreseen

### SECTION 15. Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions relating to the product or contained substances (All. XVII Reg. EC 1907/2006): not applicable Substances in Candidate List (art. 59 Reg. EC 1907/2006): the product does not contain SVHC in a proportion  $\geq$  0.1%. Substances subject to authorisation (Ann. XIV Reg. CEC 1907/2006): the product does not contain SVHC in a proportion  $\geq$  0.1%.

Reg. EC 648/04: see 2.2

Reg. (EU) n. 1169/2011: see 2.2 Reg (UE) 528/2012: see.to 2.2

Seveso category:

E1 - ENVIRONMENTAL HAZARDS

REGULATION (EU) No 1357/2014 - waste:

HP8 - Corrosive HP14 - Ecotoxic



#### **IDROSAN**

Issued on 12/16/2021 - Rel. # 10 on 12/16/2021

# 17 / 18

In conformity to Regulation (EU) 2020/878

#### 15.2. Chemical safety assessment

No chemical safety assessment was carried out by the supplier

## **SECTION 16. Other information**

#### 16.1. Other information

Points modified compared to previous release: 2.1. Classification of the substance or mixture, 3.2 Information on ingredients 4.3. Indication of any immediate medical attention and special treatment needed 7.3. Specific end use(s), 8.1. Control parameters, 8.2. Exposure controls, 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008, 12.1. Toxicity, 12.2. Persistence and degradability, 12.3. Bioaccumulative potential, 12.4. Mobility in soil, 12.6. Endocrine disrupting properties 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Description of hazard statements set out in paragraph 3

H290 = May be corrosive to metals.

H314 = Causes severe skin burns and eye damage.

H318 = Causes serious eye damage.

H400 = Very toxic to aquatic life.

H410 = Very toxic to aquatic life with long lasting effects.

Classification based on data of all mixture components

Main normative references:

Reg. (CE) n. 1907 del 18/12/06 REACH (Registration, Evaluation and Authorisation of CHemicals) et seg.

Reg. (CE) 1272/2008 CLP (Classification Labelling and Packaging) et seq.

Regulation (EC) n. 648 of 31/03/04 (on detergents) et seg.

Regulation (UE) n. 1169/2011 (on the provision of food information to consumers)

Directive 2012/18/EU (on the control of major-accident hazards involving dangerous substances) et seq.

Regulation (UE) 528/2012 (Biocides) et seq.

Procedure used to classify under CLP mixture (Reg . EC 1272/2008):

Physical hazards: On the basis of experimental data

H314 Skin. Corr. 1A: On the basis of experimental data / Calculation Method

Other hazards: Calculation Method

Training required: This document must be submitted to the employer to determine the possible need for appropriate training for workers to ensure protection of human health and the environment.

n.a.: not applicable n.d.: not available

ADR: Accord europèen relative au transport International des merchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

ATE: Acute Toxicity Estimat

BFC: BioconCentration Factor

BOD: Biochemical Oxigen Demand

CAS: Chemical Abstract Service number

CAP: Centre AntiPoison

CE/EC number EINECS (European Inventory of existing Commercial Substances) e ELINCS (European List of notified

Chemical Substances)

CL50/LC50: Lethal Concentration 50

DL50/LD50: Lethal Dose 50 COD: Chemical Oxygen Demand DNEL: Derived No Effect Level



#### **IDROSAN**

Issued on 12/16/2021 - Rel. # 10 on 12/16/2021

# 18 / 18

In conformity to Regulation (EU) 2020/878

EC50: half maximal Effective Concentration

**ERC:** Enviroment Release Classes

EU/UE: European Union

IATA: International Air Transport Association ICAO: International Civil Aviation Organization

IMDG: International Maritime Dangerous Goods code

Kow: Octanol water partition coefficient NOEC: No Observed Effect Concentration OEL: Occupational Exposure Limit

PBT: Persistent Bioaccumulative and Toxic

PC: Product Categories

PNEC: Predicted No Effect Concentration

PROC: Process Categories

RID: Règlement concernent le transport International ferroviaire des merchandises dangereuses (Regulations

concerning International rail transport of dangerous goods)

STOT: Target Organ Systemic Toxicity STOT (RE): Repeated Exposure STOT (SE): Single Exposure STP: Sewage Treatment Plants

SU: Sector of Use

SVCH: Substance of Very High Concern

TLV: Threshold Limit Value

vPvB: Very Persistent Very Bioaccumulative

#### References and Sources:

- ECHA Registered Substances:
- https://echa.europa.eu/web/guest/information-on-chemicals/registered-substances
- SDS supplier
- GESTIS DNEL Database: http://www.dguv.de/ifa/gestis/gestis-dnel-datenbank/index-2.jsp
- GESTIS International Limit Value: http://limitvalue.ifa.dguv.de

This msds was made in good faith by AEB technical Office on the basis of the information available at the date of the last revision. The person in charge must regularly inform the employees about the specific risks they encounter when using this substance/product. The information contained here relate only to the substance/the preparation indicated and may not apply if the product is used improperly or in combination with others. Nothing contained herein shall be construed as a guarantee, either express or implied. It is the responsibility of the user to ensure the opportunities and completeness of the information contained herein for their own particular use.

\*\*\* this tab annuls and replaces any previous edition. (IIXX)

Changes to the previous edition: issued in according with Reg. (EU) 878/20

## **SUMI**

#### **Safe Use of Mixtures Information**





# AISE\_SUMI\_IS\_4\_2

Version 1.1, August 2018

## Industrial uses; Automated task; Semi-automated task; Dedicated equipment

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

#### General description of the process covered

The SUMI applies to industrial uses where products are used in closed process where opportunity for exposure arises. This Safe Use Information is based on the AISE\_SWED\_IS\_4\_2.

## **Operational Conditions**

Maximum duration	480 minutes per day.
Range of application /	Indoor Use.
Process conditions	Process carried out at room temperature.
	In case of dilution, tap water at a maximum temperature of 45°C is used.
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per
	hour). No LEV required.

Measures related to	Wear suitable gloves.
personal protective equipment (PPE), hygiene and health evaluation	See section 8 of the SDS of this product for specifications.
	Training of workers in relation to proper use and maintenance of PPEs must be ensured.
Environmental	Prevent that undiluted product reaches surface waters.
measures	If appropriate AISE SPERC 8a.1.a.v2 may apply: wide dispersive use
	resulting in release to municipal sewage treatment plant.

### Additional good practice advice

Don't eat or drink. Don't smoke. Don't use in proximity of open flame.	
Wash hands after use. Avoid contact with damaged skin. Do not mix with other products.	
Spillage instructions	Dilute with fresh water and mop up.
Hygiene practices	Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS.

#### Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

#### **Disclaimer**

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling.

If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself.

Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product.

This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk.

## **SUMI**

## **Safe Use of Mixtures Information**





# AISE\_SUMI\_IS\_7\_4\_G

Version 1.1, August 2018

## Industrial spraying; Automated task; Open system; Long term

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

## General description of the process covered

The SUMI applies to industrial spraying products. This Safe Use Information is based on the AISE\_SWED\_IS\_7\_4.

## **Operational Conditions**

Maximum duration	480 minutes per day.
Range of application /	Indoor Use.
<b>Process conditions</b>	Process carried out at room temperature.
	In case of dilution, tap water at a maximum temperature of 45°C is used.
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per
	hour). No LEV required.

Measures related to	Wear suitable gloves and eye protection.
personal protective	See section 8 of the SDS of this product for specifications.
equipment (PPE),	
hygiene and health	
evaluation	
	Training of workers in relation to proper use and maintenance of PPEs
	must be ensured.
Environmental	Prevent that undiluted product reaches surface waters.
measures	If appropriate AISE SPERC 8a.1.a.v2 may apply: wide dispersive use
	resulting in release to municipal sewage treatment plant.

#### Additional good practice advice

Don't eat or drink. Don't smoke. Don't use in proximity of open flame.	
Wash hands after use. Avoid contact with damaged skin. Do not mix with other products.	
Spillage instructions	Dilute with fresh water and mop up.
Hygiene practices	Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS.

#### Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

#### **Disclaimer**

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling.

If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself.

Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product.

This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk.

## **SUMI**

#### **Safe Use of Mixtures Information**





## AISE\_SUMI\_IS\_8b\_1

Version 1.1, August 2018

## Transfer and dilution of concentrated product by using dedicated dosing system

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

## General description of the process covered

This SUMI applies to industrial uses where products are transferred to or diluted in a dedicated dosing system. This Safe Use Information is based on the AISE\_SWED\_IS\_8b\_1\_L and AISE\_SWED\_IS\_8b\_1\_S

## **Operational Conditions**

Maximum duration	60 minutes per day.
Range of application /	Indoor Use.
Process conditions	Process carried out at room temperature.
	In case of dilution, tap water at a maximum temperature of 45°C is used.
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per
	hour). No LEV required.

Measures related to	Wear suitable gloves.
personal protective equipment (PPE), hygiene and health	See section 8 of the SDS of this product for specifications.
evaluation	Training of workers in valeties to preser use and maintenance of DDFs
	Training of workers in relation to proper use and maintenance of PPEs must be ensured.
Environmental	Prevent that undiluted product reaches surface waters.
measures	If appropriate AISE SPERC 8a.1.a.v2 may apply: wide dispersive use
	resulting in release to municipal sewage treatment plant.

#### Additional good practice advice

Don't eat or drink. Don't smoke. Don't use in proximity of open flame.	
Wash hands after use. Avoid contact with damaged skin. Do not mix with other products.	
Spillage instructions	Dilute with fresh water and mop up.
Hygiene practices	Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS.

#### Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

#### **Disclaimer**

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling.

If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself.

Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product.

This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk.

## **SUMI**

## **Safe Use of Mixtures Information**





## AISE\_SUMI\_IS\_10\_1\_G

Version 1.1, August 2018

## **Brushing**; Automated task

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

## General description of the process covered

This SUMI applies to industrial uses where the product is used in an automated brushing task. This Safe Use Information is based on the **AISE\_SWED\_IS\_10\_1**.

## **Operational Conditions**

Maximum duration	480 minutes per day.	
Range of application /	Indoor Use.	
<b>Process conditions</b>	Process carried out at room temperature.	
	In case of dilution, tap water at a maximum temperature of 45°C is used.	
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per	
	hour). No LEV required.	

Measures related to	Wear suitable gloves and eye protection.
personal protective equipment (PPE), hygiene and health	See section 8 of the SDS of this product for specifications.
evaluation	
	Training of workers in relation to proper use and maintenance of PPEs
	must be ensured.
Environmental	Prevent that undiluted product reaches surface waters.
measures	If appropriate AISE SPERC 8a.1.a.v2 may apply: wide dispersive use
	resulting in release to municipal sewage treatment plant.

#### Additional good practice advice

Don't eat or drink. Don't smoke. Don't use in proximity of open flame.	
Wash hands after use. Avoid contact with damaged skin. Do not mix with other products.	
Spillage instructions	Dilute with fresh water and mop up.
Hygiene practices	Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS.

## Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

#### **Disclaimer**

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling.

If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself.

Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product.

This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk.

## **SUMI**

#### **Safe Use of Mixtures Information**





# AISE\_SUMI\_IS\_13\_3\_G

Version 1.1, August 2018

## Industrial uses; Treatment of articles by dipping or pouring

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

## General description of the process covered

This SUMI applies to industrial uses where articles are treated by dipping or pouring. This Safe Use Information is based on the AISE\_SWED\_IS\_13\_3.

## **Operational Conditions**

Maximum duration	480 minutes per day.	
Range of application /	Indoor Use.	
<b>Process conditions</b>	Process carried out at room temperature.	
	In case of dilution, tap water at a maximum temperature of 45°C is used.	
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per	
	hour). No LEV required.	

Measures related to personal protective equipment (PPE), hygiene and health evaluation	Wear suitable gloves and eye protection. See section 8 of the SDS of this product for specifications.	
	Training of workers in relation to proper use and maintenance of PPEs must be ensured.	
Environmental	Prevent that undiluted product reaches surface waters.	
measures	<b>If appropriate AISE SPERC 8a.1.a.v2 may apply</b> : wide dispersive use resulting in release to municipal sewage treatment plant.	

#### Additional good practice advice

Don't eat or drink. Don't smoke. Don't use in proximity of open flame.	
Wash hands after use. Avoid contact with damaged skin. Do not mix with other products.	
Spillage instructions	Dilute with fresh water and mop up.
Hygiene practices	Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS.

## Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

#### **Disclaimer**

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling.

If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself.

Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product.

This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk.

## **SUMI**

#### **Safe Use of Mixtures Information**





## AISE\_SUMI\_PW\_4\_1

Version 1.1, August 2018

## Professional uses; Semi-closed system

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

## General description of the process covered

The SUMI applies to professional uses where products are used in closed process where opportunity for exposure arises. This Safe Use Information is based on the AISE\_SWED\_PW\_4\_1.

## **Operational Conditions**

Maximum duration	480 minutes per day.	
Range of application /	Indoor Use.	
<b>Process conditions</b>	Process carried out at room temperature.	
	In case of dilution, tap water at a maximum temperature of 45°C is used.	
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per	
	hour). No LEV required.	

Measures related to	See section 8 of the SDS of this product for specifications.
personal protective	
equipment (PPE),	Training of workers in relation to proper use and maintenance of PPEs
hygiene and health	must be ensured.
evaluation	
Environmental	Prevent that undiluted product reaches surface waters.
measures	If appropriate AISE SPERC 8a.1.a.v2 may apply: wide dispersive use
	resulting in release to municipal sewage treatment plant.

#### Additional good practice advice

Don't eat or drink. Don't smoke. Don't use in proximity of open flame.	
Wash hands after use. Avoid contact with damaged skin. Do not mix with other products.	
Spillage instructions	Dilute with fresh water and mop up.
Hygiene practices	Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS.

## Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

#### **Disclaimer**

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling.

If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself.

Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product.

This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk.

## **SUMI**

#### **Safe Use of Mixtures Information**





## AISE\_SUMI\_PW\_8a\_1\_G

Version 1.1, August 2018

## Transfer of product to a container (bottle/bucket/machine)

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

## General description of the process covered

This SUMI applies to professional uses where the product is transferred to or diluted in a container, such as a dispenser, bottle or bucket. Safe Use Information is based on the AISE\_SWED\_PW\_8a\_1\_L and AISE\_SWED\_PW\_8a\_1\_S.

## **Operational Conditions**

Maximum duration	60 minutes per day.	
Range of application /	Indoor Use.	
Process conditions	Process carried out at room temperature.	
	In case of dilution, tap water at a maximum temperature of 45°C is used.	
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per	
	hour). No LEV required.	

Measures related to personal protective equipment (PPE), hygiene and health	Wear suitable gloves and eye protection. See section 8 of the SDS of this product for specifications.
evaluation	
	Training of workers in relation to proper use and maintenance of PPEs must be ensured.
Environmental	Prevent that undiluted product reaches surface waters.
measures	If appropriate AISE SPERC 8a.1.a.v2 may apply: wide dispersive use
	resulting in release to municipal sewage treatment plant.

#### Additional good practice advice

Don't eat or drink. Don't smoke. Don't use in proximity of open flame.	
Wash hands after use. Avoid contact with damaged skin. Do not mix with other products.	
Spillage instructions	Dilute with fresh water and mop up.
Hygiene practices	Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS.

#### Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

#### **Disclaimer**

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling.

If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself.

Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product.

This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk.

## **SUMI**

#### **Safe Use of Mixtures Information**





## AISE\_SUMI\_PW\_10\_2\_G

Version 1.1, August 2018

## Professional uses; Brushing after trigger spraying or brushing with tools

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

## General description of the process covered

This SUMI applies to professional uses where the product is brushed on a surface, with limited exposure to the hands, either after trigger spraying or through the use of tools such as a mop. This Safe Use Information is based on the AISE\_SWED\_PW\_10\_2.

## **Operational Conditions**

Maximum duration	480 minutes per day.	
Range of application /	Indoor Use.	
Process conditions	Process carried out at room temperature.	
	In case of dilution, tap water at a maximum temperature of 45°C is used.	
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per	
	hour). No LEV required.	

Measures related to personal protective equipment (PPE), hygiene and health	Wear suitable gloves and eye protection. See section 8 of the SDS of this product for specifications.
evaluation	Training of workers in relation to proper use and maintenance of PPEs
	must be ensured.
Environmental	Prevent that undiluted product reaches surface waters.
measures	If appropriate AISE SPERC 8a.1.a.v2 may apply: wide dispersive use
	resulting in release to municipal sewage treatment plant.

#### Additional good practice advice

Don't eat or drink. Don't smoke. Don't use in proximity of open flame.	
Wash hands after use. Avoid contact with damaged skin. Do not mix with other products.	
Spillage instructions	Dilute with fresh water and mop up.
Hygiene practices	Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS.

#### Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

#### **Disclaimer**

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling.

If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself.

Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product.

This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk.

## **SUMI**

Informazioni sull'Uso Sicuro delle Miscele





# AISE\_SUMI\_PW\_11\_2\_G

Versione 1.1, agosto 2018

## Usi professionali; Applicazione a spruzzo (trigger)

Questo documento ha lo scopo di comunicare le condizioni per l'uso sicuro del prodotto e deve sempre essere considerato complementare alla Scheda Dati di Sicurezza e all'etichetta.

## Descrizione generale del processo

Questo SUMI si applica agli usi professionali con applicazione a spruzzo meccanico. Il SUMI si basa sull' AISE\_SWED\_PW\_11\_2.

## **Condizioni operative**

Durata massima	60 minuti/giorno
Tipo di applicazione /	Al chiuso (indoor)
Condizioni di processo	Processo svolto a temperatura ambiente
	Se il prodotto deve essere diluito, usare acqua corrente alla Temperatura massima di 45°C.
Ricambi d'aria	Nessun LEV richiesto; prevedere ventilazione generale standard base (1-3
	ricambi d'aria/ora).

## Misure di gestione del rischio

Condizioni e misure relative ai Dispositivi di Protezione Individuale (DPI), all'igiene e alla valutazione della salute.	Indossare guanti adatti. Proteggere gli occhi Vedere sezione 8 della SDS del prodotto per le specifiche.	
	Deve essere assicurato l'addestramento del personale per il corretto uso e la manutenzione dei DPI.	
Misure di protezione ambientale	Evitare che sversamenti di prodotto non diluito raggiungano le acque superficiali.	
	<b>Nel caso si applichi l'AISE SPERC 8a.1.a.v2</b> : uso ampiamente dispersivo che può portare al rilascio all'impianto di trattamento municipalizzato.	

### Ulteriori accorgimenti di buona pratica

Non bere o mangiare Non fumare. Non usare in prossimità di fiamme libere.	
Lavare le mani dopo l'uso Evitare il contatto con pelle lesa. Non miscelare con altri prodotti.	
In caso di sversamento	Sciacquare diluendo con acqua e assorbire con panni, spugne o simili.
Consigli di igiene	Seguire le istruzioni riportate in etichetta o nella scheda tecnica ed usare buone pratiche di igiene occupazionale come specificato nella sez.7 della SDS del prodotto.

#### Informazioni addizionali dipendenti dalla composizione del prodotto

L'etichetta e (quando richiesta) la Scheda Dati di Sicurezza contengono informazioni cruciali, addizionali e specifiche per l'utilizzo sicuro delle miscele.

Far riferimento all'etichetta e alla Scheda Dati di Sicurezza del prodotto, particolarmente per le informazioni riguardanti: classificazione di pericolo del prodotto, fragranze potenzialmente allergeniche, ingredienti significativi e valori limite di esposizione (quando disponibili).

#### **Avvertenza**

Questo è un documento per comunicare le condizioni generiche di uso sicuro per un prodotto. È responsabilità del formulatore allegare questo SUMI alla SDS del prodotto specifico che sta immettendo sul mercato.

Se nella SDS viene menzionato il codice di un SUMI (o dello SWED associato) il formulatore del prodotto dichiara che tutte le sostanze contenute nella miscela sono presenti in concentrazione tale per cui l'uso del prodotto è sicuro. Quando disponibile, l'uso sicuro del prodotto è garantito dalla valutazione dei risultati del CSA "Chemical Safety Assessment" effettuato da parte del fornitore delle materie prime. Nel caso in cui non sia stato effettuato un CSA da parte del fornitore, il formulatore ha effettuato esso stesso la valutazione di sicurezza degli ingredienti che contribuiscono alla pericolosità.

In accordo alla legislazione sulla salute del Lavoro, il datore di lavoro che utilizza prodotti valutati sicuri seguendo le condizioni del SUMI, rimane responsabile di comunicare agli impiegati le rilevanti informazioni di utilizzo. Quando si sviluppano le istruzioni per i lavoratori, i SUMI dovrebbero essere sempre considerati in combinazione con le SDS e le etichette dei prodotti.

Questo documento è stato reso disponibile da A.I.S.E. e tradotto da Assocasa Federchimica con solo scopo informativo. Il formulatore utilizza il contenuto del documento a suo rischio.

Assocasa Federchimica declina ogni responsabilità verso qualsiasi persona o entità per qualsiasi perdita, danno, indipendentemente dal tipo (effettivo, consequenziale, punitivo o altro), lesione, rivendicazione, responsabilità o altra causa di qualsiasi tipo o carattere basato su o risultante dall'uso (anche parziale) del contenuto di questo documento.

## **SUMI**

#### **Safe Use of Mixtures Information**





## AISE\_SUMI\_PW\_11\_3\_G

Version 1.1, August 2018

## Professional uses; Spraying

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

## General description of the process covered

This SUMI applies to professional uses of products in a spraying application. This Safe Use Information is based on the AISE\_SWED\_PW\_11\_3.

## **Operational Conditions**

Maximum duration	480 minutes per day.	
Range of application /	Indoor Use.	
<b>Process conditions</b>	Process carried out at room temperature.	
	In case of dilution, tap water at a maximum temperature of 45°C is used.	
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per	
	hour). No LEV required.	

Measures related to	Wear suitable gloves and eye protection.
personal protective	See section 8 of the SDS of this product for specifications.
equipment (PPE),	
hygiene and health evaluation	
	Training of workers in relation to proper use and maintenance of PPEs
	must be ensured.
Environmental	Prevent that undiluted product reaches surface waters.
measures	If appropriate AISE SPERC 8a.1.a.v2 may apply: wide dispersive use
	resulting in release to municipal sewage treatment plant.

#### Additional good practice advice

Don't eat or drink. Don't smoke. Don't use in proximity of open flame.	
Wash hands after use. Avoid contact with damaged skin. Do not mix with other products.	
Spillage instructions	Dilute with fresh water and mop up.
Hygiene practices	Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS.

## Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

#### **Disclaimer**

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling.

If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself.

Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product.

This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk.

## **SUMI**

#### **Safe Use of Mixtures Information**





## AISE\_SUMI\_PW\_13\_1\_G

Version 1.1, August 2018

## Professional uses - Treatment of articles by dipping, soaking or pouring

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

## General description of the process covered

This SUMI applies to professional uses where articles are treated by dipping or pouring. This Safe Use Information is based on the AISE\_SWED\_PW\_13\_1.

## **Operational Conditions**

Maximum duration	60 minutes per day.	
Range of application /	Indoor Use.	
<b>Process conditions</b>	Process carried out at room temperature.	
	In case of dilution, tap water at a maximum temperature of 45°C is used.	
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per	
	hour). No LEV required.	

Measures related to	Wear suitable gloves and eye protection.
personal protective	See section 8 of the SDS of this product for specifications.
equipment (PPE), hygiene and health evaluation	
	Training of workers in relation to proper use and maintenance of PPEs
	must be ensured.
Environmental	Prevent that undiluted product reaches surface waters.
measures	If appropriate AISE SPERC 8a.1.a.v2 may apply: wide dispersive use
	resulting in release to municipal sewage treatment plant.

### Additional good practice advice

Don't eat or drink. Don't smoke. Don't use in proximity of open flame.	
Wash hands after use. Avoid contact with damaged skin. Do not mix with other products.	
Spillage instructions	Dilute with fresh water and mop up.
Hygiene practices	Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS.

#### Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

#### **Disclaimer**

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling.

If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself.

Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product.

This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk.

# **WORKING ISTRUCTION TABLE**



This tab provides instructions for appropriate and safe use of products and proper management of emergency situations for cleaning staff/users.

## Attached to MSDS rel#9 del 12/16/21

Use description	Use in batch and other process (syn- thesis) where opportunity for exposure arises [PROC4], Industrialspraying [PROC7], Transfer of substance or mixture (charging and discharging) at dedicated facilities [PROC8B], Transfer of substance or mixture (charging and discharging) at nondedicated facilities [PROC8A], Application with rollers or brushes [PROC10], Non industrial spraying[PROC11], Treatment of articles by dipping and pouring [PROC13]
Product name	IDROSAN
Classification of the product (100%)	H290 - May be corrosive to metals. H314 - Causes severe skin burns and eye damage. H318 - Causes serious eye damage. H400 - Very toxic to aquatic life H411 - Toxic to aquatic life with long lasting effects. EUH031 - Contact with acids liberates toxic gas (Cl2)
Classification of the diluted product (maximum use	At maximux concentration of use (5% tq) the product is classified:
· concentration)	H314 - Causes severe skin burns and eye damage. H318 - Causes serious eye damage. H412 -Harmful to aquatic life with long lasting effects.
Handling of the product (100%)	Avoid contact and inhalation of vapors
	Wear protective gloves/clothing and eye/face protection. At work do not eat or drink.
Handling of the diluted product	Avoid contact and inhalation of vapors Wear protective gloves/clothing and eye/face protection. At work do not eat or drink.
DPI required concentrated product (racking, concentrated use, spillage)	Chemical resistant protective gloves (EN 374-1/EN374-2/EN374-3), safety glasses (EN 166).
Diluited product	Chemical resistant protective gloves (EN 374-1/EN374-2/EN374-3), safety glasses (EN 166).

In case of emergency (accidents involving exposure to the product)	Immediately inform the customer. Immediately inform the employer. Contact Poisons Centres tel. number in 1.4 section of the MSDS
Accidental release large quantities measures: concentrated product	Wear gloves, mask and protective clothing (for specifications refer to section 8.2. SDS) Possibly absorb it with inert materia or sucked it.  After wiping up, wash with water the area and materials involved
Diluited product	Wear gloves and protective clothing (for specifications refer to section 8.2. SDS). Wash with water the area and materials involved
Storage of the product	Keep in original container closed tightly. Do not store in open or unlabelled containers. Keep containers upright and safe by avoiding the possibility of falls or collisions. Store in a cool and dry place, away from heat sources and direct exposure to sunlight.
In case of accidents, emergency or fire	Immediately inform the customer. Follow company emergency instruction.