



STERIFOAM

.....

Neutral foam detergent with a hygienizing action

.....

→ DESCRIPTION

Sterifoam is a neutral foam detergent with a hygienizing activity not based on oxidants, to be used for the daily cleaning of surfaces present in general in food industries and in the zoo-technical field.

Sterifoam is able to effectively remove different types of organic contaminations, carrying out at the same time a low environmental impact towards surfaces and operators. The excellent gripping power on vertical surfaces and a quick rinseability facilitate its utilization.

Sterifoam can be applied with a wide range of dispensing equipments (EasyFoam P, Combifoam, Foam lance, centralized equipments, etc.).

→ TECHNICAL CHARACTERISTICS

Physical appearance: brown clear liquid

pH as it is: $7,5 \pm 0,5$

Relative density at 20°C: $1,00 \pm 0,05$

Active components: cationic compounds

The above indicated chemical-physical data represent the typical product's characteristics drawn from the analysis carried out on the product. These values are not a specification.

→ INSTRUCTIONS FOR USE*

Pre-wash with water, then directly apply **Sterifoam** foam on the surfaces to be treated, at a concentration between 2 and 6%, according to the kind of dirt and the contamination degree. After a contact time of 10-15 min. carry out a careful final rinsing with drinking water in order to remove any possible trace of washing solution. Anyway avoid prolonged contact times with surfaces (> 1 hour).

→ FIELDS OF APPLICATION

Sterifoam can be applied for the cleaning of walls, floors, external side of equipments and lines, tables and conveyor belts. For the washing and hygienization of trucks.





STERIFOAM

→ COMPATIBILITY OF THE FORMULATION

Sterifoam is compatible with most material normally present in food industries, if used according to the producer's indications. It can be used with care even on aluminium. In case of doubt, carry out a test on the single material before using the product.

→ PRECAUTIONS FOR HANDLING AND STORAGE

Store in the original containers and avoid extreme temperatures. Consult the Material Safety Data Sheet.

→ TITRATION METHOD

Available on demand.

→ PACKAGING

25 kg net drums.
1000 kg net IBC.

*The indications have been established for general use conditions. For conditions differing from the norm, for example depending on the particular water hardness, the working method or cleaning problems, please consult us; our technical service will be pleased to advise you and to cooperate with you.

