SANIFOAM P

Alkaline foam detergent with high chlorine content

-> DESCRIPTION

SANIFOAM P is an alkaline foaming detergent with a high content in chlorine and potash characterized by high rinsability. It is conceived for the daily cleaning of surfaces present in the food industry and the zoo-technical sector.

SANIFOAM P has intermediate characteristics between a traditional foaming agent and a gel: excellent clinging on vertical surfaces with duration along time and a better cleaning with a quick rinsing. **SANIFOAM P** can be applied with a wide range of supply equipments (Easyfoam P, Combifoam, Foamlance, centralized systems, etc.).

TECHNICAL CHARACTERISTICS

Physical appearance: clear yellow liquid pH (100% solution at 20°C >12 Relative density at 20°C: $1,15 \pm 0,05$ Active chlorine (1% solution): 500 ppm

The above indicated chemical-physical data represent the typical product's characteristics drawn from the analysis carried out on the product. These values are not a specification.

→ INSTRUCTIONS FOR USE*

Pre-wash with water (from 35 to 60°C), followed by the foam application of **SANIFOAM P** directly on the surfaces to be treated, in concentration between 3 and 6%, according to the kind of soil and the contamination level. Use at room temperature and on not warm surfaces. After 10-15' of contact carry out a careful final rinsing with drinking-water to remove any possible trace of washing solution. Anyway avoid prolonged contact times with surfaces (> 1 hour).

→ FIELDS OF APPLICATION

SANIFOAM P can be applied for the cleaning of walls, floors, external side of equipments and lines, tables and conveyor belts. The rinsing speed makes it the ideal product for COP systems such as those installed in bottling lines.



AEB OCEANIA PTY • LTD 178A Wakaden Street, Griffith, NSW 2680 (AU) Tel: +61 1300 704 971 • aeboceania@aeb-group.com • www.aeb-group.com



SANIFOAM P

→ COMPATIBILITY OF THE FORMULATION

SANIFOAM P is compatible with most material normally present in food industries, if used according to the producer's indications. Do not use on light metals such as aluminium and zinc-plated iron. In case of doubt, carry out a test on the single material before using the product.

→ PRECAUTIONS FOR HANDLING AND STORAGE

Store in the original containers and avoid extreme temperatures. Frost sensitive: keep at temperatures above 7°C. Consult the Material Safety Data Sheet.

→ TITRATION METHOD

Sample: 50 mL of washing solution Indicator: phenolphthalein + some drops of tiosulphate Titrating agent: hydrochloric acid (HCl) 1N

% (v/v) **SANIFOAM P** = mL titrating agent x 0,89 % (w/w) **SANIFOAM P** = mL titrating agent x 1,02

→ PACKAGING

20 kg net drums. 1100 kg net IBC.

*The indications have been established for general use conditions. For conditions differing from the norm, for example depending on the particular water hardness, the working method or cleaning problems, please consult us; our technical service will be pleased to advise you and to cooperate with you.



AEB OCEANIA PTY • LTD 178A Wakaden Street, Griffith, NSW 2680 (AU) Tel: +61 1300 704 971 • aeboceania@aeb-group.com • www.aeb-group.com