

SECTION 1. Identification of the substance/mixture and of the company/enterprise

1.1. Product identifier

Product name : ACID JD
Product code: refer to sales department

1.2. Relevant identified uses of the substance or mixture and uses advised against

Descaling acidic detergent

Sectors of use:

Industrial Manufacturing[SU3]

Product category:

Washing and Cleaning Products (including solvent based products)

Process categories:

Use in batch and other process (syn- thesis) where opportunity for exposure arises[PROC4], Transfer of substance or mixture (charging and discharging) at dedicated facilities[PROC8B], Treatment of articles by dipping and pouring[PROC13]

Not recommended uses

Do not use for purposes other than those listed

1.3. Details of the supplier of the safety data sheet

AEB SpA - Via Vittorio Arici 104 S.Polo - 25134 Brescia (BS) Italy
Tel. +39.030.2307.1 Fax +39.030.2307281
E-mail: info@aeb-group.com - Internet: www.aeb-group.com
E-mail tecnico competente/technical dept.: sds@aeb-group.com

AEB USA
111 N Cluff Avenue
Lodi CA 95240 (USA)
Tel: +1 2096258139 Fax: +1 2092248953
Email: info@aebusa.com - Internet: www.aeb-group.com

AEB AFRICA (PTY) LTD
18 Track Crescent, Cor. Station Road
Montague Gardens 7441
Cape Town (South Africa)
Tel.: +27 215512700 - Fax: +27 (0) 215511919
Email: info@aeb.co.za - Internet: www.aeb-group.com

AEB OCEANIA PTY LTD
178A Wakaden Street
Griffith NSW 2680
T: 1300 704 971
Email: aeboceania@aeb-group.com - Internet: www.aeb-group.com

Produced by
AEB SpA
Via Vittorio Arici 104 S. Polo
25134 Brescia

1.4. Emergency telephone number

AEB SpA
Centralino/Switchboard: +39.030.2307.1 - (h 8.30-12.00 13.30-18.00 GMT +1; Lingua/Language: Italiano, English)

AEB USA
Switchboard: +1 2096258139 (GMT -8; Language: English)

AEB AFRICA (PTY) LTD
Switchboard: +27 215512700 (GMT +1; Language: English, Afrikaans)

AEB OCEANIA PTY LTD
Switchboard: +61 1300 704 971 (GMT +9; Language: English)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) No 1272/2008:

Pictograms:
GHS05, GHS06

Hazard Class and Category Code(s):
Met. Corr. 1, Skin Corr. 1, Eye Dam. 1, Acute Tox. 3

Hazard statement Code(s):
H290 - May be corrosive to metals.
H314 - Causes severe skin burns and eye damage.
H318 - Causes serious eye damage.
H331 - Toxic if inhaled.

The product can be corrosive to metals
Toxic product: do not inhale
Corrosive product: causes severe skin burns and eye damage.
If brought into contact with eyes, the product causes serious damages to eyes, such as an opaque cornea or injury to iris.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008:

Pictogram, Signal Word Code(s):
GHS05, GHS06 - Danger

Hazard statement Code(s):
H290 - May be corrosive to metals.
H314 - Causes severe skin burns and eye damage.
H331 - Toxic if inhaled.

Supplemental Hazard statement Code(s):
EUH071 - Corrosive to the respiratory tract.



Precautionary statements:

Prevention

P260 - Do not vapours/spray.

P280 - Wear protective gloves/clothing and eye/face protection.

Response

P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Contains: Nitric acid

Contains (Reg.EC 648/2004):/

2.3. Other hazards

The substance / mixture does NOT contain substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

The use of this chemical agent involves the obligation of "risk assessment" by the employer in accordance with the provisions of Dlgs n. 81. April 9, 2008. Workers exposed to this chemical agent should not be subject to health surveillance if the results of the risk assessment show that, depending on the type and quantity of dangerous chemical agent and method and frequency of exposure to the agent, there is only a "moderate Risk" for the health and safety of workers and that the measures laid down in the Decree are sufficient to reduce the risk.

Do not ingest. Keep out of reach of children.

For professional use only

SECTION 3. Composition/information on ingredients

3.1 Substances

Irrilevant

3.2 Mixtures

Refer to paragraph 16 for full text of hazard statements

Substance	Concentration[w/w]	Classification	Index	CAS	EINECS	REACH
Nitric acid (B)	>= 50 < 70%	EUH071; Ox. Liq. 2, H272; Met. Corr. 1, H290; Skin Corr. 1A, H314; Acute Tox. 3, H331	007-004-00-1	7697-37-2	231-714-2	01-2119487 297-23-XXX X
Urea substance for which there are Community workplace exposure limits	>= 0,1 < 1%			57-13-6	200-315-5	01-2119463 277-33-XXX X

SECTION 4. First aid measures

4.1. Description of first aid measures

Inhalation:

Ventilate the area. Move immediately the contaminated patient from the area and keep him at rest in a well ventilated room. CALL A PHYSICIAN.

If breathing has stopped, give artificial respiration.

Direct contact with skin (of the pure product):

Take off immediately contaminated clothing.

In case of contact with skin, wash immediately with water.

Immediately consult a physician.

Direct contact with eyes (of the pure product):

Wash immediately and thoroughly with running water, keeping eyelids open for at least 10 minutes, then protect your eyes with a dry sterile gauze. Seek medical advice immediately

Do not use eye drops or ointments of any kind before the examination or advice from an oculist.

Ingestion:

Give medicine paraffine oil; do not give milk or animal / vegetal fats in general.

Drink water with egg white; do not give bicarbonate.

Absolutely do not induce vomiting or emesis. Seek medical advice immediately.

4.2. Most important symptoms and effects, both acute and delayed

Ingestion may cause chemical burns in the mouth and throat. In contact with skin it may cause burns. Contact with eyes causes very severe irritation, including redness and tear. Inhalation may cause asthma respiratory failure; irritation of the mucous membranes and the respiratory tract may cause nausea and difficulty in breathing.

4.3. Indication of any immediate medical attention and special treatment needed

Immediately call a POISON CENTER or a doctor.

Call a POISON CENTER or a doctor.

SECTION 5. Firefighting measures

5.1. Extinguishing media

Suggested extinguishing media:

Water spray, CO₂, foam, dry chemical, depending on the materials involved in the fire.

Extinguishing media to avoid:

Water jets. Use water jets only to cool the surfaces of the containers exposed to fire.

5.2. Special hazards arising from the substance or mixture

No data available.

5.3. Advice for firefighters

Use protection for the breathing apparatus

Safety helmet and full protective clothing.

The water spray can be used to protect the people involved in the extinction.

You may also use self-contained breathing apparatus, especially when working in confined and poorly ventilated areas

and if you use halogenated extinguishers (Halon 1211 fluobrene, Solkan 123, NAF, etc...)
Keep containers cool with water spray

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel:

Leave the area surrounding the spill or release. Do not smoke
Wear mask, gloves and protective clothing.

6.1.2 For emergency responders:

Eliminate all unguarded flames and possible sources of ignition. No smoking.
Provide a sufficient ventilation.
Evacuate the danger area and, in case, consult an expert.

6.2. Environmental precautions

Contain spills with earth or sand.
If the product has entered a watercourse, sewers or has contaminated soil or vegetation, notify the authorities.
Dispose of the waste material in compliance with the regulations

6.3. Methods and material for containment and cleaning up

6.3.1 Containment:

Rapidly recover the product, wear a mask and protective clothing (for specifications refer to section 8.2. SDS)
Recover the product for reuse, if possible, or for removal. Possibly absorb it with inert material or suck it.
Prevent it from entering the sewer system.

6.3.2 Cleaning up:

After wiping up, wash with water the area and materials involved

6.3.3 Other information:

None in particular.

6.4. Reference to other sections

Refer to paragraphs 8 and 13 for more information

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid contact and inhalation of vapors
Wear protective gloves/clothing and eye/face protection.
In residential areas do not use on large surfaces.
At work do not eat or drink.
See also paragraph 8 below.

7.2. Conditions for safe storage, including any incompatibilities

Keep in original container closed tightly. Do not store in open or unlabelled containers.
Keep containers upright and safe by avoiding the possibility of falls or collisions.
Store in a cool and dry place, away from heat sources and direct exposure to sunlight.

7.3. Specific end use(s)

Industrial Manufacturing:
Handle with extreme caution.
Store in a well ventilated place away from heat sources.(7-30°C)

See the annex exposure scenario.

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

=====
Related to contained substances:

Nitric acid:
Limit value - Eight hours
(ppm)/(mg/m³)

- Australia: 2/5.2
- Austria: x/x
- Belgio: x/x
- Canada – Ontario: 2/x
- Canada - Québec: 2/5.2
- Denmark: 2/5
- European Union: x/x
- Finland: 0.5/1.3
- France: x/x
- Germany (AGS): x/x
- Hungary: x/x
- Ireland: x/x
- Italy: x/x
- Japan – JSOH: 2/5.2
- Latvia: 0.78/2
- New Zealand: 2/5.2
- Poland: x/1.4
- Singapore: 2/5.2
- South Korea: 2/5
- Spain: x/x
- Sweden: 0.5/1.3
- Switzerland: 2/5
- The Netherlands: x/x
- Turkey: x/x
- USA - NIOSH: 2/5
- USA – OSHA: 2/5
- United Kingdom: x/x

Limit value - Short term
(ppm)/(mg/m³)

- Australia: 4/10
- Austria: 1/2.6
- Belgio: 1/2.6
- Canada – Ontario: 4/x
- Canada - Québec: 4/10
- Denmark: 4/10
- European Union: 1/2.6
- Finland: 1 (1)/2.6 (1)
- France: 1/2.6

Germany (AGS):1 (1)/2.6 (1)
Hungary: x/2.6
Ireland: 1 (1)/2.6 (1)
Italy: 1/2.6
Japan – JSOH: x/x
Latvia: 1 (1)/2.6 (1)
New Zealand: 4/10
Poland: x/2.6
Singapore: 4/10
South Korea: 4/10
Spain: 1/2.6
Sweden: 1 (1)/2.6 (1)
Switzerland: 2/5
The Netherlands: x/1.3
Turkey: 1 (1)/2.6 (1)
USA - NIOSH: 4 (1)/10 (1)
USA – OSHA: x/x
United Kingdom: 1/2.6

Remarks

European Union: Bold-type: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] ~ (for references see bibliography)

Finland: (1) 15 minutes average values

France: *Italic type*: Indicative statutory limit values

Germany (AGS): (1) 15 minutes average values

Ireland: (1) 15 minutes average period

Latvia: (1) 15 minutes average values

Poland: nitric acid (V)

Sweden: (1) 15 minutes average values

Turkey: (1) 15 minutes average values

USA - NIOSH: (1) 15 minutes average values

Tipo OEL: UE - STEL: 2.6 mg/m³, 1 ppm

Tipo OEL: ACGIH - TWA(8h): 2 ppm - STEL: 4 ppm - Note: URT and eye irr, dental erosion

Urea:

Limit value - Eight hours
(ppm)/(mg/m³)

Latvia: -/10

People's Republic of China: -/5

OEL: ACGIH - TWA -/10

Limit value - Short term
(ppm)/(mg/m³)

People's Republic of China: -/10(1)

Remarks:

People's Republic of China:(1) 15 minutes average value

- Substance: Nitric acid

DNEL

Local effects Long term Workers inhalation = 1,3

Local effects Long term Consumers inhalation = 0,65 (mg/m³)

Local effects Short term Workers inhalation = 2,6 (mg/m³)

Local effects Short term Consumers inhalation = 1,3 (mg/m³)

- Substance: Urea

DNEL

Systemic effects Long term Workers inhalation = 292 (mg/m³)
 Systemic effects Long term Workers dermal = 580 (mg/kg bw/day)
 Systemic effects Long term Consumers inhalation = 125 (mg/m³)
 Systemic effects Long term Consumers dermal = 580 (mg/kg bw/day)
 Systemic effects Long term Consumers oral = 42 (mg/kg bw/day)
 Systemic effects Short term Workers inhalation = 292 (mg/m³)
 Systemic effects Short term Workers dermal = 580 (mg/kg bw/day)
 Systemic effects Short term Consumers inhalation = 125 (mg/m³)
 Systemic effects Short term Consumers dermal = 580 (mg/kg bw/day)
 Systemic effects Short term Consumers oral = 42 (mg/kg bw/day)

PNEC

Sweet water = 0,047 (mg/l)

8.2. Exposure controls

Appropriate engineering controls:

Industrial Manufacturing:

No specific monitoring foreseen (act according to good practice and specific rules for the type of risk associated)

8.2.2 Individual protection measures:

(a) Eye / face protection

Wear protective goggles (EN 166).

(b) Skin protection

(i) Hand protection

When handling the pure product use chemical resistant protective gloves (EN 374-1/EN374-2/EN374-3)

(ii) Other

During working operation wear protective clothing (generic workwear / antacid, safety shoes or other protective equipment) according to the instructions of the employer

(c) Respiratory protection

Not needed for normal use

In case of insufficient ventilation or emergency, use mask with gas filters and and inorganic vapors - Grey , Class 3 , B (EN 405) unless otherwise provided by the employer and / or assessments of environmental investigations hygienistic

(d) Thermal hazards

No hazard to report

Environmental exposure controls:

Use according to good working practices and avoid to disperse the product into the environment.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical and chemical properties	Value	Determination method
Appearance	Clear colorless liquid	

Physical and chemical properties	Value	Determination method
Odour	not determined as considered not relevant for the characterization of the product	
Odour threshold	not determined as considered not relevant for the characterization of the product	
pH	< 2 (20°C; sol. 3%); < 2 (20°C; sol. 100%)	
Melting point/freezing point	not determined as considered not relevant for the characterization of the product	
Initial boiling point and boiling range	not determined as considered not relevant for the characterization of the product	
Flash point	not determined as considered not relevant for the characterization of the product	
Evaporation rate	not determined as considered not relevant for the characterization of the product	
Flammability (solid, gas)	not determined as considered not relevant for the characterization of the product	
Upper/lower flammability or explosive limits	not determined as considered not relevant for the characterization of the product	
Vapour pressure	not determined as considered not relevant for the characterization of the product	
Vapour density	not determined as considered not relevant for the characterization of the product	
Relative density	1,30 ± 0,05 (20°C)	
Solubility	in water	
Water solubility	miscible in all proportions	
Partition coefficient: n-octanol/water	not determined as considered not relevant for the characterization of the product	
Auto-ignition temperature	not determined as considered not relevant for the characterization of the product	
Decomposition temperature	not determined as considered not relevant for the characterization of the product	
Viscosity	not determined as considered not relevant for the characterization of the product	
Explosive properties	not determined as considered not relevant for the characterization of the product	
Oxidising properties	not determined as considered not relevant for the characterization of the product	

9.2. Other information

No data available.

SECTION 10. Stability and reactivity

10.1. Reactivity

Acid

10.2. Chemical stability

Stable at room temperature and under normal conditions of use Corrosive to cement. Non-corrosive to stainless steel, antacid grease, glass.

10.3. Possibility of hazardous reactions

Reacts exothermically with water. Reacts energetically with reducing agents, strong bases, organic materials and chlorides. The reaction with the most common metals can release oxygen.

10.4. Conditions to avoid

Direct heat sources and what is expected in 10.3

10.5. Incompatible materials

Organic substances, it reacts with most chemicals. In contact with reducing substances (paper, rags, sawdust) may cause ignition. In contact with some metals form NO_x oxides. The concentrated product should not be mixed with organic substances (milk, wine, beer, rubber, paper, etc.) as it may develop toxic gas.

10.6. Hazardous decomposition products

Do not decompose if used for intended uses

SECTION 11. Toxicological information

11.1. Information on toxicological effects

ATE(mix) oral = ∞
ATE(mix) dermal = ∞
ATE(mix) inhal = 5,3 mg/l/4 h

(a) acute toxicity: Toxic product: do not inhale

Nitric acid: Ingestion - LD50 rat (mg / kg / 24h bw): nd

Skin contact - LC50 rat / rabbit (mg / kg / 24h bw): nd

Inhalation - LD50 rat (mg / l / 4h): > 2.65

Urea: Inhalation - LD50 rat (mg / kg / 24h bw): 8471

Skin contact - LC50 rat / rabbit (mg / kg / 24h bw): na

Inhalation - LD50 rat (mg / l / 4h): n..d.

(b) skin corrosion/irritation Corrosive product: causes severe skin burns and eye damage.

Nitric acid: Corrosive

Urea: Not corrosive

Nitric acid: Irritating

Urea: Irritating to the skin - Species: Rabbit No - Source: Study report (2003) - Notes: In vivo test, OECD Guideline 404,

(c) serious eye damage/irritation: Corrosive product: causes severe skin burns and eye damage. - If brought into contact with eyes, the product causes serious damages to eyes, such as an opaque cornea or injury to iris.

Nitric acid: Corrosive

Urea: Not corrosive

Nitric acid: irritating

Urea: Test: Irritating to eyes - Species: Rabbit No - Source: Study report ((1988) - Notes: In vivo test, OECD Guideline 405

(d) respiratory or skin sensitization: Nitric acid: Not available

Urea: Not sensitizing

(e) germ cell mutagenicity: Nitric acid: Not mutagenic

Urea: Not mutagenic

(f) carcinogenicity: Nitric acid: Non-conclusive data

Urea: Not carcinogenic

(g) reproductive toxicity: Nitric acid: Non-toxic for reproduction

Urea: Not toxic

(h) specific target organ toxicity (STOT) single exposure: Nitric acid: Not available

Urea: Not toxic

(i) specific target organ toxicity (STOT) repeated exposure: Nitric acid: Not available

Urea: Not toxic

(j) aspiration hazard: Nitric acid: Not available

Urea: Not available

=====

Related to contained substances:

Nitric acid:

CL50 Inhalation (rat) vapour/dust/mist/fume (mg/l/4h) or gas (ppmV/4h) > 2,65

Urea:

LD50 (rat) Oral (mg/kg body weight) = 8471

SECTION 12. Ecological information

12.1. Toxicity

=====

Related to contained substances:

Nitric acid:

Acute toxicity - LC50 fish (mg / l / 96h): 4650

Acute toxicity - EC50 crustaceans (mg / l / 48h): Median lethal pH (48h) 4.4-4.7 for Ceriodaphnia dubia (US EPA guideline). This study shows that the pH rather than the anion (nitrate) is causing the toxic effects in daphnids. This is confirmed by two additional studies with sodium nitrate (24h EC50 8609 mg / L for Daphnia magna, similar to OECD TG 202) and potassium nitrate (48h EC50 490 mg / L for Daphnia magna, no guideline followed). The read-across rationale can be found in the category approach document in Section 13 of IUCLID and is fully incorporated in the CSR.

Acute toxicity ErC50 algae (mg / l / 72-96h): nd

C(E)L50 (mg/l) = 4650

Urea:

Acute toxicity - LC50 (mg / l / 96h): > 6810

Acute toxicity - EC50 crust (mg / l / 48h): 20608

Acute algae ErC50 (mg / l / 72-96h): nd

Chronic toxicity - NOEC fish (mg / l): 200 (1wk)

Chronic toxicity - NOEC crustaceans (mg / l): na

Chronic NOE toxicity (mg / l): nd

Use according to good working practices and avoid to disperse the product into the environment.

12.2. Persistence and degradability

=====

Related to contained substances:

Nitric acid:
Not available

Urea:
It is not easily biodegradable

12.3. Bioaccumulative potential

=====
Related to contained substances:
Nitric acid:
Not bioaccumilable

Urea:
Not bioaccumulable

12.4. Mobility in soil

=====
Related to contained substances:
Nitric acid:
Not available

Urea:
Not available

12.5. Results of PBT and vPvB assessment

No PBT/vPvB ingredient is present

12.6. Other adverse effects

No adverse effects

Regulation (EC) No 2006/907 - 2004/648

The (l) surfactant (s) content (s) in this preparation complies (comply) with (i) the biodegradability criteria as laid down in Regulation CE/648/2004 on detergents. All data are held at the disposal of the competent authorities of Member States and will be provided, at their direct request or at the request of a detergent manufacturer, to those authorities.

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Do not reuse empty containers. Dispose of them in accordance with the regulations in force. Any remaining product should be disposed of according to applicable regulations by addressing to authorized companies.
Recover if possible. Operate according to local or national regulations

SECTION 14. Transport information

14.1. UN number

ADR/RID/IMDG/ICAO-IATA: 3264

If subject to the following characteristics is ADR exempt:



Combination packagings: per inner packaging 1 L per package 30 Kg
Inner packaging placed in skrink-wrapped or stretch-wrapped trays: per inner packaging 1 L per package 20 Kg

14.2. UN proper shipping name

ADR/RID/IMDG: LIQUIDO INORGANICO CORROSIVO, ACIDO, N.A.S. (Acido nitrico in miscela)
ADR/RID/IMDG: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric acid in mixture)
ICAO-IATA: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric acid in mixture)

14.3. Transport hazard class(es)

ADR/RID/IMDG/ICAO-IATA: Class : 8
ADR/RID/IMDG/ICAO-IATA: Label : 8
ADR: Tunnel restriction code : E
ADR/RID/IMDG/ICAO-IATA: Limited quantities : 1 L
IMDG - EmS : F-A, S-B

14.4. Packing group

ADR/RID/IMDG/ICAO-IATA: II

14.5. Environmental hazards

ADR/RID/ICAO-IATA: Product is not environmentally hazardous
IMDG: Marine polluting agent : No

14.6. Special precautions for user

The transport must be carried out by authorized vehicles for the transport of dangerous goods in accordance with the requirements of the applicable Edition of the agreement A.D.R. and national provisions. The transport must be carried out in the original packaging and in packages that are made from materials resistant to content and not likely to generate with this dangerous reactions. The process of loading and unloading of dangerous goods have received adequate training on the risks presented by prepared and on possible procedures to be taken in the event of emergency situations

14.7. Transport in bulk according to Annex II of MARPOL73/78 and IBC Code

Transport in bulk is not foreseen

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions relating to the product or contained substances (All. XVII Reg. EC 1907/2006): not applicable
Substances in Candidate List (art. 59 Reg. EC 1907/2006): the product does not contain SVHC
Substances subject to authorisation (Ann. XIV Reg. CEC 1907/2006): the product does not contain SVHC
Reg. EC 648/04: see 2.2
Reg. (EU) n. 1169/2011: see 2.2

Seveso category:
H2 - ACUTE TOXIC

REGULATION (EU) No 1357/2014 - waste:
HP8 - Corrosive

15.2. Chemical safety assessment

No chemical safety assessment was carried out by the supplier

SECTION 16. Other information

16.1. Other information

Points modified compared to previous release: 2.2. Label elements

Description of hazard statements set out in paragraph 3

H272 = May intensify fire; oxidiser.
H290 = May be corrosive to metals.
H314 = Causes severe skin burns and eye damage.
H331 = Toxic if inhaled.

Classification based on data of all mixture components

Main normative references:

Reg. (CE) n. 1907 del 18/12/06 REACH (Registration, Evaluation and Authorisation of CHemicals) et seq.
Reg. (CE) 1272/2008 CLP (Classification Labelling and Packaging) et seq.
Regulation (EC) n. 648 of 31/03/04 (on detergents) et seq.
Regulation (UE) n. 1169/2011 (on the provision of food information to consumers)
Directive 2012/18/EU (on the control of major-accident hazards involving dangerous substances) et seq.

Procedure used to classify under CLP mixture (Reg . EC 1272/2008):

Physical hazards: On the basis of experimental data

H314 Skin. Corr. 1A: On the basis of experimental data / Calculation Method

Other hazards: Calculation Method

Training required: This document must be submitted to the employer to determine the possible need for appropriate training for workers to ensure protection of human health and the environment.

n.a.: not applicable

n.d.: not available

ADR: Accord européen relative au transport International des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

ATE: Acute Toxicity Estimat

BFC: BioconCentration Factor

BOD: Biochemical Oxigen Demand

CAS: Chemical Abstract Service number

CAP: Centre AntiPoison

CE/EC number EINECS (European Inventory of existing Commercial Substances) e ELINCS (European List of notified Chemical Substances)

CL50/LC50: Lethal Concentration 50

DL50/LD50: Lethal Dose 50

COD: Chemical Oxygen Demand

DNEL: Derived No Effect Level
EC50: half maximal Effective Concentration
ERC: Environment Release Classes
EU/UE: European Union
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization
IMDG: International Maritime Dangerous Goods code
Kow: Octanol water partition coefficient
NOEC: No Observed Effect Concentration
OEL: Occupational Exposure Limit
PBT: Persistent Bioaccumulative and Toxic
PC: Product Categories
PNEC: Predicted No Effect Concentration
PROC: Process Categories
RID: Règlement concernant le transport International ferroviaire des marchandises dangereuses (Regulations concerning International rail transport of dangerous goods)
STOT: Target Organ Systemic Toxicity
STOT (RE): Repeated Exposure
STOT (SE): Single Exposure
STP: Sewage Treatment Plants
SU: Sector of Use
SVCH: Substance of Very High Concern
TLV: Threshold Limit Value
vPvB: Very Persistent Very Bioaccumulative

References and Sources:

- ECHA Registered Substances:
<https://echa.europa.eu/web/guest/information-on-chemicals/registered-substances>
- SDS supplier
- GESTIS DNEL Database: <http://www.dguv.de/ifa/gestis/gestis-dnel-datenbank/index-2.jsp>
- GESTIS International Limit Value: <http://limitvalue.ifa.dguv.de>

This msds was made in good faith by AEB technical Office on the basis of the information available at the date of the last revision. The person in charge must regularly inform the employees about the specific risks they encounter when using this substance/product. The information contained here relate only to the substance/the preparation indicated and may not apply if the product is used improperly or in combination with others. Nothing contained herein shall be construed as a guarantee, either express or implied. It is the responsibility of the user to ensure the opportunities and completeness of the information contained herein for their own particular use.

*** this tab annuls and replaces any previous edition. (IIXX)

Changes to the previous edition: label variation, SE updating, working istruction sheet attached

SUMI**Safe Use of Mixtures Information****AISE_SUMI_IS_4_2***Version 1.1, August 2018****Industrial uses; Automated task; Semi-automated task; Dedicated equipment***

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

The SUMI applies to industrial uses where products are used in closed process where opportunity for exposure arises. This Safe Use Information is based on the **AISE_SWED_IS_4_2**.

Operational Conditions

Maximum duration	480 minutes per day.
Range of application / Process conditions	Indoor Use. Process carried out at room temperature. In case of dilution, tap water at a maximum temperature of 45°C is used.
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per hour). No LEV required.

Risk Management Measures

Measures related to personal protective equipment (PPE), hygiene and health evaluation	Wear suitable gloves. See section 8 of the SDS of this product for specifications. 
	Training of workers in relation to proper use and maintenance of PPEs must be ensured.
Environmental measures	Prevent that undiluted product reaches surface waters. If appropriate AISE SPERC 8a.1.a.v2 may apply: wide dispersive use resulting in release to municipal sewage treatment plant.

Additional good practice advice

<p>Don't eat or drink.</p> <p>Don't smoke.</p> <p>Don't use in proximity of open flame.</p>	
<p>Wash hands after use.</p> <p>Avoid contact with damaged skin.</p> <p>Do not mix with other products.</p>	
Spillage instructions	Dilute with fresh water and mop up.
Hygiene practices	Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS.

Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

Disclaimer

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling.

If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself.

Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product.

This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk.

A.I.S.E. disclaims any liability to any person or entity for any loss, damage no matter of what kind (actual, consequential, punitive or otherwise), injury, claim, liability or other cause of any kind or character based upon or resulting from the use (even partly) of the content of this document.

SUMI**Safe Use of Mixtures Information****AISE_SUMI_IS_8b_1***Version 1.1, August 2018****Transfer and dilution of concentrated product by using dedicated dosing system***

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

This SUMI applies to industrial uses where products are transferred to or diluted in a dedicated dosing system. This Safe Use Information is based on the **AISE_SWED_IS_8b_1_L** and **AISE_SWED_IS_8b_1_S**

Operational Conditions

Maximum duration	60 minutes per day.
Range of application / Process conditions	Indoor Use.
	Process carried out at room temperature.
	In case of dilution, tap water at a maximum temperature of 45°C is used.
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per hour). No LEV required.

Risk Management Measures

Measures related to personal protective equipment (PPE), hygiene and health evaluation	Wear suitable gloves. See section 8 of the SDS of this product for specifications.
	 Training of workers in relation to proper use and maintenance of PPEs must be ensured.
Environmental measures	Prevent that undiluted product reaches surface waters.
	If appropriate AISE SPERC 8a.1.a.v2 may apply: wide dispersive use resulting in release to municipal sewage treatment plant.

Additional good practice advice

<p>Don't eat or drink. Don't smoke. Don't use in proximity of open flame.</p>	
<p>Wash hands after use. Avoid contact with damaged skin. Do not mix with other products.</p>	
<p>Spillage instructions</p>	<p>Dilute with fresh water and mop up.</p>
<p>Hygiene practices</p>	<p>Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS.</p>

Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

Disclaimer

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling.

If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself.

Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product.

This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk.

A.I.S.E. disclaims any liability to any person or entity for any loss, damage no matter of what kind (actual, consequential, punitive or otherwise), injury, claim, liability or other cause of any kind or character based upon or resulting from the use (even partly) of the content of this document.

SUMI**Safe Use of Mixtures Information****AISE_SUMI_IS_13_3_G***Version 1.1, August 2018****Industrial uses; Treatment of articles by dipping or pouring***

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

This SUMI applies to industrial uses where articles are treated by dipping or pouring. This Safe Use Information is based on the **AISE_SWED_IS_13_3**.

Operational Conditions

Maximum duration	480 minutes per day.
Range of application / Process conditions	Indoor Use. Process carried out at room temperature. In case of dilution, tap water at a maximum temperature of 45°C is used.
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per hour). No LEV required.

Risk Management Measures

Measures related to personal protective equipment (PPE), hygiene and health evaluation	Wear suitable gloves and eye protection. See section 8 of the SDS of this product for specifications. 
	Training of workers in relation to proper use and maintenance of PPEs must be ensured.
Environmental measures	Prevent that undiluted product reaches surface waters.
	If appropriate AISE SPERC 8a.1.a.v2 may apply: wide dispersive use resulting in release to municipal sewage treatment plant.

Additional good practice advice

<p>Don't eat or drink. Don't smoke. Don't use in proximity of open flame.</p>	
<p>Wash hands after use. Avoid contact with damaged skin. Do not mix with other products.</p>	
<p>Spillage instructions</p>	<p>Dilute with fresh water and mop up.</p>
<p>Hygiene practices</p>	<p>Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS.</p>

Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

Disclaimer

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling.

If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself.

Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product.

This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk.

A.I.S.E. disclaims any liability to any person or entity for any loss, damage no matter of what kind (actual, consequential, punitive or otherwise), injury, claim, liability or other cause of any kind or character based upon or resulting from the use (even partly) of the content of this document.

WORKING ISTRUCTION TABLE



This tab provides instructions for appropriate and safe use of products and proper management of emergency situations for cleaning staff/users.

Attached to MSDS rel#6 del 02/17/20

Use description	Use in batch and other process (synthesis) where opportunity for exposure arises [PROC4]; Transfer of substance or mixture (charging and discharging) at dedicated facilities [PROC8b]; Treatment of articles by dipping and pouring [PROC13]
Product name	ACID JD
Classification of the product (100%)	H290 - May be corrosive to metals. H314 - Causes severe skin burns and eye damage. H318 - Causes serious eye damage. H331 - Toxic if inhaled. EUH071 - Corrosive to the respiratory tract.
Classification of the diluted product (maximum use concentration)	At maximux concentration of use (3%) the product is classified: H314 - Causes severe skin burns and eye damage. H318 - Causes serious eye damage. EUH071 - Corrosive to the respiratory tract.
Handling of the product (100%)	Avoid contact and inhalation of vapors Wear protective gloves/protective clothing/eye protection/face protection. At work do not eat or drink.
Handling of the diluted product	Avoid contact and inhalation of vapors Wear protective gloves/protective clothing/eye protection/face protection. At work do not eat or drink.
DPI required concentrated product (racking, concentrated use, spillage...)	Chemical resistant protective gloves (EN 374-1/EN374-2/EN374-3), safety glasses (EN 166).
Diluted product	Chemical resistant protective gloves (EN 374-1/EN374-2/EN374-3), safety glasses (EN 166).

<p>In case of emergency (accidents involving exposure to the product)</p>	<p>Immediately inform the customer. Immediately inform the employer. Contact Poisons Centres tel. number in 1.4 section of the MSDS</p>
<p>Accidental release large quantities measures: concentrated product</p>	<p>Wear gloves,mask, glasses and protective clothing (for specifications refer to section 8.2 . SDS). Possibly absorb it with inert materia or sucked it. After wiping up, wash with water the area and materials involved</p>
<p>Diluted product</p>	<p>Wear gloves,mask, glasses and protective clothing (for specifications refer to section 8.2 . SDS). Possibly absorb it with inert materia or sucked it. After wiping up, wash with water the area and materials involved</p>
<p>Storage of the product</p>	<p>Keep in original container closed tightly. Do not store in open or unlabelled containers. Keep containers upright and safe by avoiding the possibility of falls or collisions. Store in a cool and dry place, away from heat sources and direct exposure to sunlight.</p>
<p>In case of accidents, emergency or fire</p>	<p>Immediately inform the customer. Follow company emergency instruction.</p>