

SECTION 1. Identification of the substance/mixture and of the company/enterprise

1.1. Product identifier

Product name : ADIX Liquid
Product code: refer to sales department

1.2. Relevant identified uses of the substance or mixture and uses advised against

Additive for alkaline detergents

Sectors of use:

Industrial Manufacturing[SU3], Manufacture of food products[SU4]

Product category:

Washing and Cleaning Products (including solvent based products)

Process categories:

Use in batch and other process (syn- thesis) where opportunity for exposure arises[PROC4], Transfer of substance or mixture (charging and discharging) at dedicated facilities[PROC8B], Treatment of articles by dipping and pouring [PROC13]

Not recommended uses

Do not use for purposes other than those listed

1.3. Details of the supplier of the safety data sheet

AEB SpA - Via Vittorio Arici 104 S.Polo - 25134 Brescia (BS) Italy
Tel. +39.030.2307.1 Fax +39.030.2307281
E-mail: info@aeb-group.com - Internet: www.aeb-group.com
E-mail tecnico competente/technical dept.: sds@aeb-group.com

AEB USA
111 N Cluff Avenue
Lodi CA 95240 (USA)
Tel: +1 2096258139 Fax: +1 2092248953
Email: info@aebusa.com - Internet: www.aeb-group.com

AEB AFRICA (PTY) LTD
18 Track Crescent, Cor. Station Road
Montague Gardens 7441
Cape Town (South Africa)
Tel.: +27 215512700 - Fax: +27 (0) 215511919
Email: info@aeb.co.za - Internet: www.aeb-group.com

AEB OCEANIA PTY LTD
178A Wakaden Street
Griffith NSW 2680
T: 1300 704 971
Email: aebocania@aeb-group.com - Internet: www.aeb-group.com

Produced by
AEB SpA
Via Vittorio Arici 104 S. Polo
25134 Brescia

1.4. Emergency telephone number

AEB SpA

Centralino/Switchboard: +39.030.2307.1 - (h 8.30-12.00 13.30-18.00 GMT +1; Lingua/Language: Italiano, English)

AEB USA

Switchboard: +1 2096258139 (GMT -8; Language: English)

AEB AFRICA (PTY) LTD

Switchboard: +27 215512700 (GMT +1; Language: English, Afrikaans)

AEB OCEANIA PTY LTD

Switchboard: +61 1300 704 971 (GMT +9; Language: English)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) No 1272/2008:

Pictograms:

GHS05, GHS07, GHS09

Hazard Class and Category Code(s):

Skin Irrit. 2, Eye Dam. 1, Aquatic Acute 1, Aquatic Chronic 3

Hazard statement Code(s):

H315 - Causes skin irritation.

H318 - Causes serious eye damage.

H400 - Very toxic to aquatic life. (Acute toxicity M-factor = 1)

H412 - Harmful to aquatic life with long lasting effects.

If brought into contact with the skin, the product causes significant inflammation with erythema, scabs, or edema.

If brought into contact with eyes, the product causes serious damages to eyes, such as an opaque cornea or injury to iris.

The product is dangerous for the environment as it is very toxic to aquatic organisms

The product is dangerous to the environment as it is harmful to aquatic life with long lasting effects

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008:

Pictogram, Signal Word Code(s):

GHS05, GHS09 - Danger

Hazard statement Code(s):

H315 - Causes skin irritation.

H318 - Causes serious eye damage.

H410 - Very toxic to aquatic life with long lasting effects.

Supplemental Hazard statement Code(s):

not applicable



Precautionary statements:

Prevention

P280 - Wear protective gloves and eye/face protection.

Response

P302+P352 - IF ON SKIN: Wash with plenty of water.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

Disposal

P501 - Dispose of contents/container to local/regional/national/international regulations

Contains:

Phosphonic polymer, Trimethyl-3-[(1-oxo-10-undecenyl)amino]propylammonium methyl sulphate, Alkyl polyglucoside C8 - 10.

Contains (Reg.EC 648/2004):

15% < 30% non-ionic surfactants, < 5% cationic surfactants, phosphonates

2.3. Other hazards

The substance / mixture does NOT contain substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

Do not ingest. Keep out of reach of children.

SECTION 3. Composition/information on ingredients

3.1 Substances

Irrilevant

3.2 Mixtures

Refer to paragraph 16 for full text of hazard statements

Substance	Concentration[w/w]	Classification	Index	CAS	EINECS	REACH
Amine Alkoxylate (polymer)	>= 10 < 25%	Skin Irrit. 2, H315				Polymer
Trimethyl-3-[(1-oxo-10-undecenyl)amino]propylammonium methyl sulphate	>= 2,5 < 3%	Skin Irrit. 2, H315; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 2, H411 Acute toxicity M-factor = 10		94313-91-4	304-990-8	01-2120736 263-59-XXX X
Phosphonic polymer	>= 1 < 2,5%	Met. Corr. 1, H290; Skin Corr. 1C, H314; Eye Dam. 1, H318				Polymer
Alkyl polyglucoside C8 - 10	>= 1 < 2,5%	Eye Dam. 1, H318		68515-73-1	500-220-1	01-2119488 530-36-XXX X

SECTION 4. First aid measures

4.1. Description of first aid measures

Inhalation:

Ventilate the area. Move immediately the contaminated patient from the area and keep him at rest in a well ventilated area. If you feel unwell seek medical advice.

Direct contact with skin (of the pure product):

Take off immediately contaminated clothing.
Wash immediately with plenty of running water and possibly with soap, the areas of the body that have, or are only suspected to have, come in contact with the product.
In case of contact with skin, wash immediately with water.

Direct contact with eyes (of the pure product):

Wash immediately and thoroughly with running water, keeping eyelids open for at least 10 minutes, then protect your eyes with a dry sterile gauze. Seek medical advice immediately
Do not use eye drops or ointments of any kind before the examination or advice from an oculist.

Ingestion:

Not hazardous. It's possible to give activated charcoal in water or medicinal mineral vaseline oil.

4.2. Most important symptoms and effects, both acute and delayed

Contact with eyes may cause intense irritation, including redness and tearing.
Contact with skin causes irritation and redness

4.3. Indication of any immediate medical attention and special treatment needed

If skin irritation occurs: Get medical advice/attention.
Immediately call a POISON CENTER or a doctor.

SECTION 5. Firefighting measures

5.1. Extinguishing media

Suggested extinguishing media:

Water spray, CO₂, foam, dry chemical, depending on the materials involved in the fire.

Extinguishing media to avoid:

Water jets. Use water jets only to cool the surfaces of the containers exposed to fire.

5.2. Special hazards arising from the substance or mixture

No data available.

5.3. Advice for firefighters

Use protection for the breathing apparatus
Safety helmet and full protective clothing.
The water spray can be used to protect the people involved in the extinction.
You may also use self-contained breathing apparatus, especially when working in confined and poorly ventilated areas.
Keep containers cool with water spray

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel:

Leave the area surrounding the spill or release. Do not smoke

Wear mask, gloves and protective clothing.

6.1.2 For emergency responders:

Eliminate all unguarded flames and possible sources of ignition. No smoking.

Provide a sufficient ventilation.

Evacuate the danger area and, in case, consult an expert.

6.2. Environmental precautions

Contain spills with earth or sand.

If the product has entered a watercourse, sewers or has contaminated soil or vegetation, notify the authorities.

Dispose of the waste material in compliance with the regulations

6.3. Methods and material for containment and cleaning up

6.3.1 Containment:

Rapidly recover the product, wear a mask and protective clothing (for specifications refer to section 8.2. SDS)

Recover the product for reuse, if possible, or for removal. Possibly absorb it with inert material or suck it.

Prevent it from entering the sewer system.

6.3.2 Cleaning up:

After wiping up, wash with water the area and materials involved

6.3.3 Other information:

None in particular.

6.4. Reference to other sections

Refer to paragraphs 8 and 13 for more information

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid contact and inhalation of vapors

Wear protective gloves and eye/face protection.

At work do not eat or drink.

See also paragraph 8 below.

7.2. Conditions for safe storage, including any incompatibilities

Keep in original container closed tightly. Do not store in open or unlabelled containers.

Keep containers upright and safe by avoiding the possibility of falls or collisions.

Store in a cool and dry place, away from heat sources and direct exposure to sunlight.

7.3. Specific end use(s)

Industrial Manufacturing:

Handle with extreme caution.

Store in a well ventilated place away from heat sources. (7-30°C)

Manufacture of food products:

Handle with care.

Store in a clean, dry, ventilated area away from heat and direct sunlight.

Keep container tightly closed. (7-30°C)

See the annex exposure scenario.

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

- Substance: Trimethyl-3-[(1-oxo-10-undecenyl)amino]propylammonium methyl sulphate

DNEL

Systemic effects Long term Workers inhalation = 10,1 (mg/m³)

Systemic effects Long term Workers dermal = 2,9 (mg/kg bw/day)

Systemic effects Long term Consumers inhalation = 2,5 (mg/m³)

Systemic effects Long term Consumers dermal = 1,4 (mg/kg bw/day)

Systemic effects Long term Consumers oral = 1,43 (mg/kg bw/day)

PNEC

Sweet water = 0,00032 (mg/l)

Sea water = 0,00032 (mg/l)

STP = 3,2 (mg/l)

- Substance: Alkyl polyglucoside C8 - 10

DNEL

Systemic effects Long term Workers inhalation = 420 (mg/m³)

Systemic effects Long term Workers dermal = 595000 (mg/kg bw/day)

Systemic effects Long term Consumers inhalation = 124 (mg/m³)

Systemic effects Long term Consumers dermal = 357000 (mg/kg bw/day)

Systemic effects Long term Consumers oral = 35,7 (mg/kg bw/day)

PNEC

Sweet water = 0,176 (mg/l)

sediment Sweet water = 1516 (mg/kg/sediment)

Sea water = 0,0176 (mg/l)

sediment Sea water = 0,152 (mg/kg/sediment)

intermittent emissions = 0,27 (mg/l)

STP = 560 (mg/l)

8.2. Exposure controls

Appropriate engineering controls:

Industrial Manufacturing:

No specific monitoring foreseen (act according to good practice and specific rules for the type of risk associated)

Manufacture of food products:

No specific monitoring foreseen (act according to good practice and specific rules for the type of risk associated)

8.2.2 Individual protection measures:

(a) Eye / face protection

Wear protective goggles (EN 166).

(b) Skin protection

(i) Hand protection

When handling the pure product use chemical resistant protective gloves (EN 374-1/EN374-2/EN374-3).

(ii) Other

During working operation wear protective clothing (generic workwear / antacid, safety shoes or other protective equipment) according to the instructions of the employer

(c) Respiratory protection

Not needed for normal use

In case of insufficient ventilation or emergency, use mask with gas filters type ABECK (EN 405) unless otherwise provided by the employer and / or assessments of environmental investigations hygienistic.

None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information.

Use certified respiratory protection equipment meeting EU requirements (89/656/EEC, 245/2016 UE), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

(d) Thermal hazards

No hazard to report

Environmental exposure controls:

Use according to good working practices and avoid to disperse the product into the environment.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical and chemical properties	Value	Determination method
Appearance	clear liquid	
Colour	amber	
Odour	not determined as considered not relevant for the characterization of the product	
Odour threshold	not determined as considered not relevant for the characterization of the product	
pH	5,0 ± 0,5 (100%, 20 °C); 6,5 ± 0,5 (sol.6%, 20 °C)	
Melting point/freezing point	not determined as considered not relevant for the characterization of the product	
Initial boiling point and boiling range	not determined as considered not relevant for the characterization of the product	
Flash point	not determined as considered not relevant for the characterization of the product	
Evaporation rate	not determined as considered not relevant for the characterization of the product	
Flammability (solid, gas)	not determined as considered not relevant for the characterization of the product	
Upper/lower flammability or explosive limits	not determined as considered not relevant for the characterization of the product	
Vapour pressure	not determined as considered not relevant for the characterization of the product	
Vapour density	not determined as considered not relevant for the characterization of the product	
Relative density	1,05 ± 0,05 (20 °C)	
Solubility	in water	
Water solubility	miscible in all proportions	

Physical and chemical properties	Value	Determination method
Partition coefficient: n-octanol/water	not determined as considered not relevant for the characterization of the product	
Auto-ignition temperature	not determined as considered not relevant for the characterization of the product	
Decomposition temperature	not determined as considered not relevant for the characterization of the product	
Viscosity	not determined as considered not relevant for the characterization of the product	
Explosive properties	not determined as considered not relevant for the characterization of the product	
Oxidising properties	not determined as considered not relevant for the characterization of the product	

9.2. Other information

No data available.

SECTION 10. Stability and reactivity

10.1. Reactivity

No reactivity hazards

10.2. Chemical stability

No hazardous reaction when handled and stored according to provisions.

10.3. Possibility of hazardous reactions

There are no hazardous reactions

10.4. Conditions to avoid

Heat or direct sunlight

10.5. Incompatible materials

Can generate flammable gases on contact with metals Inorganic Sulfides, nitrides, elementary, strong reducing agents.
Can generate toxic gases in contact with inorganic sulfides, strong reducing agents.

10.6. Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11. Toxicological information

11.1. Information on toxicological effects

ATE(mix) oral = ∞

ATE(mix) dermal = ∞

ATE(mix) inhal = ∞

(a) acute toxicity: Amine Alkoxylate (polymer): Practically non-toxic to a single ingestion.

Experimental/calculated data:

LD50 rat (oral): > 5,000 mg/kg

Rat LD50 (dermal): not determined

Trimethyl-3-[(1-oxo-10-undecenyl)amino]propylammonium methyl sulphate: Ingestion - LD50 rat (mg / kg / 24h bw):> 5000

Skin contact - LC50 rat / rabbit (mg / kg / 24h bw):> 2000

Inhalation - LD50 rat (mg / l / 4h): nd

Phosphonic polymer: Ingestion - LD50 rat (mg / kg / 24h bw):> 2000

Skin contact - LC50 rat / rabbit (mg / kg / 24h bw):> 2000.

Inhalation - LD50 rat (mg / l / 4h): na

Alkyl polyglucoside C8 - 10: Practically non-toxic to individual skin contact and/or single ingestion

Oral rat LD50 value: > 2000 mg/kg

Dermal LC50 rat/rabbit value: > 2000

(b) skin corrosion/irritation: If brought into contact with the skin, the product causes significant inflammation with erythema, scabs, or edema.

Amine Alkoxylate (polymer): Non-corrosive

Trimethyl-3-[(1-oxo-10-undecenyl)amino]propylammonium methyl sulphate: Non-corrosive

Phosphonic polymer: Causes serious skin and eye damage (Rabbit OECD 404)

Alkyl polyglucoside C8 - 10: Not corrosive

Amine Alkoxylate (polymer): Irritating

Trimethyl-3-[(1-oxo-10-undecenyl)amino]propylammonium methyl sulphate: Irritating

Phosphonic polymer: Causes serious skin and eye damage (Rabbit OECD 404)

Alkyl polyglucoside C8 - 10: Not irritating

(c) serious eye damage/irritation: If brought into contact with eyes, the product causes serious damages to eyes, such as an opaque cornea or injury to iris.

Amine Alkoxylate (polymer): Non-corrosive

Trimethyl-3-[(1-oxo-10-undecenyl)amino]propylammonium methyl sulphate: Corrosive

Phosphonic polymer: Causes serious eye damage (rabbit OECD 405)

Alkyl polyglucoside C8 - 10: Corrosive

Amine Alkoxylate (polymer): Non-irritating

Trimethyl-3-[(1-oxo-10-undecenyl)amino]propylammonium methyl sulphate: Irritating

Phosphonic polymer: Causes serious eye damage (rabbit OECD 405)

Alkyl polyglucoside C8 - 10: Irritating

(d) respiratory or skin sensitization: Amine Alkoxylate (polymer): Not available

Trimethyl-3-[(1-oxo-10-undecenyl)amino]propylammonium methyl sulphate: Non-sensitizing

Phosphonic polymer: Sensitization (Guinea pig OECD 406): Based on available data, the classification criteria are not met.

Alkyl polyglucoside C8 - 10: Not sensitizing

(e) germ cell mutagenicity: Amine Alkoxylate (polymer): Non-mutagenic

Trimethyl-3-[(1-oxo-10-undecenyl)amino]propylammonium methyl sulphate: Non-mutagenic

Phosphonic polymer: Based on the available data, the classification criteria are not met.

Alkyl polyglucoside C8 - 10: Not mutagenic

(f) carcinogenicity: Amine Alkoxylate (polymer): Non-carcinogenic

Trimethyl-3-[(1-oxo-10-undecenyl)amino]propylammonium methyl sulphate: Non-carcinogenic

Phosphonic polymer: Based on the available data, the classification criteria are not met.

Alkyl polyglucoside C8 - 10: Not carcinogenic

(g) reproductive toxicity: Amine Alkoxylate (polymer): Non-toxic for reproduction
Trimethyl-3-[(1-oxo-10-undecenyl)amino]propylammonium methyl sulphate: Not available
Phosphonic polymer: Based on the available data, the classification criteria are not met.
Alkyl polyglucoside C8 - 10: Non-toxic for reproduction
(h) specific target organ toxicity (STOT) single exposure: Amine Alkoxylate (polymer): Not available
Trimethyl-3-[(1-oxo-10-undecenyl)amino]propylammonium methyl sulphate: Not available
Phosphonic polymer: Based on the available data, the classification criteria are not met.
Alkyl polyglucoside C8 - 10: Unavailable
(i) specific target organ toxicity (STOT) repeated exposure: Amine Alkoxylate (polymer): Not available
Trimethyl-3-[(1-oxo-10-undecenyl)amino]propylammonium methyl sulphate: Not available
Phosphonic polymer: Based on the available data, the classification criteria are not met.
Alkyl polyglucoside C8 - 10: Unavailable
(j) aspiration hazard: Amine Alkoxylate (polymer): Not available
Trimethyl-3-[(1-oxo-10-undecenyl)amino]propylammonium methyl sulphate: Not available
Phosphonic polymer: Based on the available data, the classification criteria are not met.
Alkyl polyglucoside C8 - 10: Unavailable

11.2. Information on other hazards

No data available.

SECTION 12. Ecological information

12.1. Toxicity

=====

Related to contained substances:

Amine Alkoxylate (polymer):

Ittiotossicità:

CL0 (48 h) 2,000 mg/l, *Leuciscus idus*

Aquatic invertebrates:

LC50 (48 h), *Daphnia*

not determined

Aquatic plants:

EC50 (72 h), algae

not determined

Microorganisms/effects on activated sludge:

CE10 > 5,000 mg/l, activated sludge (DEV-L2)

Trimethyl-3-[(1-oxo-10-undecenyl)amino]propylammonium methyl sulphate:

Acute toxicity - LC50 fish (mg / l / 96h): > 251.3 (*Brachydanio rerio*)

Acute toxicity - crustaceans EC50 (mg / l / 48h): 136 mg / l (*Daphnia magna*)

Acute toxicity algae ErC50 (mg / l / 72-96h): 0.097 mg / l (Algae *Pseud subcapit.*)

Chronic toxicity - NOEC fish (mg / l): nd

Chronic toxicity - crustaceans NOEC (mg / l): n.d.

Chronic toxicity NOEC algal (mg / l): nd

C(E)L50 (mg/l) = 136 Acute toxicity M-factor = 10

Phosphonic polymer:

Acute toxicity - LC50 fish (mg / l / 96h): n.d

Acute toxicity - crustaceans EC50 (mg / l / 48h): >100 (*Daphnia*)

Acute toxicity algae ErC50 (mg / l / 72-96h): nd

Chronic toxicity - NOEC fish (mg / l): nd

Chronic toxicity - crustaceans NOEC (mg / l): n.d.

Chronic toxicity NOEC algal (mg / l): nd

Alkyl polyglucoside C8 - 10:
Fish
LC50 > 100 mg/l (DIN EN ISO 7346-2)
Aquatic invertebrates:
EC50 > 100 mg/l (OECD-guideline 202, part 1)
Aquatic plants:
EC50 > 10-100 mg/l (Directive 88/302/EEC, part C, p 89)
Microorganisms/effects on activated sludge:
Ce0 > 100 mg/l (OECD-guideline 209)
Ce0 > 100 mg/l (DIN 38412 part 8)
Chronic toxicity on fish:
NOEC > 1-10 mg/l (OECD Guideline 204)
Chronic toxicity to aquatic invertebrates:
NOEC > 1-10 mg/l (OECD-guideline 202, part 2)

The product is dangerous for the environment as it is very toxic to aquatic organisms following acute exposure.
The product is dangerous for the environment as it is toxic for aquatic organisms following acute exposure.

Use according to good working practices and avoid to disperse the product into the environment.

12.2. Persistence and degradability

=====

Related to contained substances:

Amine Alkoxylate (polymer):

Readily biodegradable

Trimethyl-3-[(1-oxo-10-undecenyl)amino]propylammonium methyl sulphate:

Readily biodegradable > 60% (OECD 301B)

Phosphonic polymer:

50% (OECD 302 B) COD (Std. Method 5220 D): 480 mg / g

Alkyl polyglucoside C8 - 10:

Evaluation of biodegradability and delete (H2O):

Readily biodegradable (according to OECD criteria).

Disposal considerations:

(Annex III, part A) The surfactant (s) contained in this formulation is (are) subject (s) to the biodegradability criteria as laid down in Regulation (EC) No 648/2004 on detergents. All the supporting data shall be kept available to the competent authorities of the Member States and will be provided to the authorities at their request or at the request of a manufacturer of the formula.

12.3. Bioaccumulative potential

=====

Related to contained substances:

Amine Alkoxylate (polymer):

Not bioaccumulative

Trimethyl-3-[(1-oxo-10-undecenyl)amino]propylammonium methyl sulphate:

Not available

Phosphonic polymer:

Not available

Alkyl polyglucoside C8 - 10:

Assessment of bioaccumulation potential: No accumulation in organisms should be expected.

12.4. Mobility in soil

=====

Related to contained substances:

Amine Alkoxylate (polymer):

Evaluation transport between environmental compartments:

Volatility: the substance does not evaporate into the atmosphere from the surface of the water.

Adsorption in soil: A soil absorption to the solid phase is possible

Trimethyl-3-[(1-oxo-10-undecenyl)amino]propylammonium methyl sulphate:

Not available

Phosphonic polymer:

Not available

Alkyl polyglucoside C8 - 10:

Evaluation of transport between environmental departments: The substance does not evaporate into the atmosphere from the surface of the water. An absorption to the solid phase of the soil is possible.

12.5. Results of PBT and vPvB assessment

No PBT/vPvB ingredient is present

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No adverse effects

Regulation (EC) No 2006/907 - 2004/648

The (I) surfactant (s) content (s) in this preparation complies (comply) with (i) the biodegradability criteria as laid down in Regulation CE/648/2004 on detergents. All data are held at the disposal of the competent authorities of Member States and will be provided, at their direct request or at the request of a detergent manufacturer, to those authorities.

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Do not reuse empty containers. Dispose of them in accordance with the regulations in force. Any remaining product should be disposed of according to applicable regulations by addressing to authorized companies.

Recover if possible. Send to authorized discharge plants or for incineration under controlled conditions. Operate according to local and National rules in force

SECTION 14. Transport information

14.1. UN number

ADR/RID/IMDG/ICAO-IATA: 3082

If subject to the following characteristics is ADR exempt:

Combination packagings: per inner packaging 5 L per package 30 Kg



Inner packaging placed in shrink-wrapped or stretch-wrapped trays: per inner packaging 5 L per package 20 Kg

14.2. UN proper shipping name

ADR/RID/IMDG: MATERIA PERICOLOSA PER L'AMBIENTE, LIQUIDA, N.A.S.
(Trimethyl-3-[(1-oxo-10-undecenyl)amino] propylammonium methyl sulphate)
ADR/RID/IMDG: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Trimethyl-3-[(1-oxo-10-undecenyl)amino] propylammonium methyl sulphate)
ICAO-IATA: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Trimethyl-3-[(1-oxo-10-undecenyl)amino] propylammonium methyl sulphate)

14.3. Transport hazard class(es)

ADR/RID/IMDG/ICAO-IATA: Class : 9
ADR/RID/IMDG/ICAO-IATA: Label : 9+Environment
ADR: Tunnel restriction code : --
ADR/RID/IMDG/ICAO-IATA: Limited quantities : 5 L
IMDG - EmS : F-A, S-F

14.4. Packing group

ADR/RID/IMDG/ICAO-IATA: III

14.5. Environmental hazards

ADR/RID/ICAO-IATA: Product is environmentally hazardous
IMDG: Marine polluting agent : Yes

14.6. Special precautions for user

The transport must be carried out by authorized vehicles for the transport of dangerous goods in accordance with the requirements of the applicable Edition of the agreement A.D.R. and national provisions. The transport must be carried out in the original packaging and in packages that are made from materials resistant to content and not likely to generate with this dangerous reactions. The process of loading and unloading of dangerous goods have received adequate training on the risks presented by prepared and on possible procedures to be taken in the event of emergency situations

14.7. Transport in bulk according to Annex II of MARPOL73/78 and IBC Code

Transport in bulk is not foreseen

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions relating to the product or contained substances (All. XVII Reg. EC 1907/2006): not applicable
Substances in Candidate List (art. 59 Reg. EC 1907/2006): the product does not contain SVHC
Substances subject to authorisation (Ann. XIV Reg. CEC 1907/2006): the product does not contain SVHC

Reg. EC 648/04: see 2.2
Reg. (EU) n. 1169/2011: see 2.2
Reg (UE) 528/2012: see to 2.2

Seveso category:

E1 - ENVIRONMENTAL HAZARDS

REGULATION (EU) No 1357/2014 - waste:

HP4 - Irritant — skin irritation and eye damage

HP14 - Ecotoxic

15.2. Chemical safety assessment

No chemical safety assessment was carried out by the supplier

SECTION 16. Other information

16.1. Other information

Points modified compared to previous release: 2.1. Classification of the substance or mixture, 2.2. Label elements, 4.0 Transport information

Description of hazard statements set out in paragraph 3

H315 = Causes skin irritation.

H318 = Causes serious eye damage.

H400 = Very toxic to aquatic life.

H411 = Toxic to aquatic life with long lasting effects.

H290 = May be corrosive to metals.

H314 = Causes severe skin burns and eye damage.

Classification based on data of all mixture components

Main normative references:

Reg. (CE) n. 1907 del 18/12/06 REACH (Registration, Evaluation and Authorisation of CHemicals) et seq.

Reg. (CE) 1272/2008 CLP (Classification Labelling and Packaging) et seq.

Regulation (EC) n. 648 of 31/03/04 (on detergents) et seq.

Regulation (UE) n. 1169/2011 (on the provision of food information to consumers)

Directive 2012/18/EU (on the control of major-accident hazards involving dangerous substances) et seq.

Regulation (UE) 528/2012 (Biocides) et seq.

Procedure used to classify under CLP mixture (Reg . EC 1272/2008):

Physical hazards: On the basis of experimental data

Other hazards: Calculation Method

Training required: This document must be submitted to the employer to determine the possible need for appropriate training for workers to ensure protection of human health and the environment.

n.a.: not applicable

n.d.: not available

ADR: Accord européen relative au transport International des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

ATE: Acute Toxicity Estimati

BFC: BioconCentration Factor

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstract Service number

CAP: Centre AntiPoison

CE/EC number EINECS (European Inventory of existing Commercial Substances) e ELINCS (European List of notified Chemical Substances)
CL50/LC50: Lethal Concentration 50
DL50/LD50: Lethal Dose 50
COD: Chemical Oxygen Demand
DNEL: Derived No Effect Level
EC50: half maximal Effective Concentration
ERC: Environment Release Classes
EU/UE: European Union
IATA: International Air Transport Association
ICAO: International Civil Aviation Organization
IMDG: International Maritime Dangerous Goods code
Kow: Octanol water partition coefficient
NOEC: No Observed Effect Concentration
OEL: Occupational Exposure Limit
PBT: Persistent Bioaccumulative and Toxic
PC: Product Categories
PNEC: Predicted No Effect Concentration
PROC: Process Categories
RID: Règlement concernant le transport International ferroviaire des marchandises dangereuses (Regulations concerning International rail transport of dangerous goods)
STOT: Target Organ Systemic Toxicity
STOT (RE): Repeated Exposure
STOT (SE): Single Exposure
STP: Sewage Treatment Plants
SU: Sector of Use
SVCH: Substance of Very High Concern
TLV: Threshold Limit Value
vPvB: Very Persistent Very Bioaccumulative

References and Sources:

- ECHA Registered Substances:
• <https://echa.europa.eu/web/guest/information-on-chemicals/registered-substances>
- SDS supplier
- GESTIS DNEL Database: <http://www.dguv.de/ifa/gestis/gestis-dnel-datenbank/index-2.jsp>
- GESTIS International Limit Value: <http://limitvalue.ifa.dguv.de>

This msds was made in good faith by AEB technical Office on the basis of the information available at the date of the last revision. The person in charge must regularly inform the employees about the specific risks they encounter when using this substance/product. The information contained here relate only to the substance/the preparation indicated and may not apply if the product is used improperly or in combination with others. Nothing contained herein shall be construed as a guarantee, either express or implied. It is the responsibility of the user to ensure the opportunities and completeness of the information contained herein for their own particular use.

*** this tab annuls and replaces any previous edition. (IIXX)

Changes to the previous edition: Classification variation, ADR classification variation, exposure scenario updating, attached working instruction table

SUMI**Safe Use of Mixtures Information****AISE_SUMI_IS_4_1***Version 1.1, August 2018****Industrial uses; Automated task; Semi-automated task; Dedicated equipment***

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

The SUMI applies to industrial uses where products are used in closed process where opportunity for exposure arises. This Safe Use Information is based on the **AISE_SWED_IS_4_1**.

Operational Conditions

Maximum duration	480 minutes per day.
Range of application / Process conditions	Indoor Use.
	Process carried out at room temperature.
	In case of dilution, tap water at a maximum temperature of 45°C is used.
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per hour). No LEV required.

Risk Management Measures

Measures related to personal protective equipment (PPE), hygiene and health evaluation	See section 8 of the SDS of this product for specifications.
	Training of workers in relation to proper use and maintenance of PPEs must be ensured.
Environmental measures	Prevent that undiluted product reaches surface waters.
	If appropriate AISE SPERC 8a.1.a.v2 may apply: wide dispersive use resulting in release to municipal sewage treatment plant.

Additional good practice advice

Don't eat or drink. Don't smoke. Don't use in proximity of open flame.	
Wash hands after use. Avoid contact with damaged skin. Do not mix with other products.	
Spillage instructions	Dilute with fresh water and mop up.
Hygiene practices	Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS.

Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

Disclaimer

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling.

If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself.

Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product.

This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk.

A.I.S.E. disclaims any liability to any person or entity for any loss, damage no matter of what kind (actual, consequential, punitive or otherwise), injury, claim, liability or other cause of any kind or character based upon or resulting from the use (even partly) of the content of this document.

SUMI**Safe Use of Mixtures Information****AISE_SUMI_IS_8b_1***Version 1.1, August 2018****Transfer and dilution of concentrated product by using dedicated dosing system***

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

This SUMI applies to industrial uses where products are transferred to or diluted in a dedicated dosing system. This Safe Use Information is based on the **AISE_SWED_IS_8b_1_L** and **AISE_SWED_IS_8b_1_S**

Operational Conditions

Maximum duration	60 minutes per day.
Range of application / Process conditions	Indoor Use.
	Process carried out at room temperature.
	In case of dilution, tap water at a maximum temperature of 45°C is used.
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per hour). No LEV required.

Risk Management Measures

Measures related to personal protective equipment (PPE), hygiene and health evaluation	Wear suitable gloves. See section 8 of the SDS of this product for specifications. 
	Training of workers in relation to proper use and maintenance of PPEs must be ensured.
Environmental measures	Prevent that undiluted product reaches surface waters.
	If appropriate AISE SPERC 8a.1.a.v2 may apply: wide dispersive use resulting in release to municipal sewage treatment plant.

Additional good practice advice

Don't eat or drink. Don't smoke. Don't use in proximity of open flame.	
Wash hands after use. Avoid contact with damaged skin. Do not mix with other products.	
Spillage instructions	Dilute with fresh water and mop up.
Hygiene practices	Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS.

Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

Disclaimer

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling.

If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself.

Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product.

This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk.

A.I.S.E. disclaims any liability to any person or entity for any loss, damage no matter of what kind (actual, consequential, punitive or otherwise), injury, claim, liability or other cause of any kind or character based upon or resulting from the use (even partly) of the content of this document.

SUMI**Safe Use of Mixtures Information****AISE_SUMI_IS_13_4***Version 1.1, August 2018****Industrial uses; Treatment of articles by dipping or pouring***

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

This SUMI applies to industrial uses where articles are treated by dipping or pouring. This Safe Use Information is based on the **AISE_SWED_IS_13_4**.

Operational Conditions

Maximum duration	480 minutes per day.
Range of application / Process conditions	Indoor Use.
	Process carried out at room temperature.
	In case of dilution, tap water at a maximum temperature of 45°C is used.
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per hour). No LEV required.

Risk Management Measures

Measures related to personal protective equipment (PPE), hygiene and health evaluation	See section 8 of the SDS of this product for specifications.
	Training of workers in relation to proper use and maintenance of PPEs must be ensured.
Environmental measures	Prevent that undiluted product reaches surface waters.
	If appropriate AISE SPERC 8a.1.a.v2 may apply: wide dispersive use resulting in release to municipal sewage treatment plant.

Additional good practice advice

Don't eat or drink. Don't smoke. Don't use in proximity of open flame.	
Wash hands after use. Avoid contact with damaged skin. Do not mix with other products.	
Spillage instructions	Dilute with fresh water and mop up.
Hygiene practices	Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS.

Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

Disclaimer

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling.

If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself.

Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product.

This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk.

A.I.S.E. disclaims any liability to any person or entity for any loss, damage no matter of what kind (actual, consequential, punitive or otherwise), injury, claim, liability or other cause of any kind or character based upon or resulting from the use (even partly) of the content of this document.

WORKING ISTRUCTION TABLE



This tab provides instructions for appropriate and safe use of products and proper management of emergency situations for cleaning staff/users.

Attached to MSDS rel#8 del 02/04/2021

Use description	Transfer of substance or mixture (charging and discharging) at dedicated facilities [PROC8b]; Application with rollers or brushes [PROC10]; Use in batch and other process (syn- thesis) where opportunity for exposure arises [PROC4]; Non industrial spraying [PROC11]
Product name	ADIX Liquid
Classification of the product (100%)	H315 - Causes skin irritation. H318 - Causes serious eye damage. H411 - Very toxic to aquatic life with long lasting effects.
Classification of the diluted product (maximum use concentration)	At maximux concentration of use (6%) the product is classified: Not dangerous according to Regulation (EC) No 1272/2008
Handling of the product (100%)	Avoid contact and inhalation of vapors Wear protective gloves and eye/face protection. t work do not eat or drink.
Handling of the diluted product	At work do not eat or drink.
DPI required concentrated product (racking, concentrated use, spillage...)	Chemical resistant protective gloves (EN 374-1/EN374-2/EN374-3), safety glasses (EN 166).
Diluted product	No DPI required for intende uses

In case of emergency (accidents involving exposure to the product)	Immediately inform the customer. Immediately inform the employer. Contact Poisons Centres tel. number in 1.4 section of the MSDS
Accidental release large quantities measures: concentrated product	Wear mask, gloves, glasses and protective clothing (for specifications refer to section 8.2. SDS) Possibly absorb it with inert material or suck it. After wiping up, wash with water the area and materials involved
Diluted product	Wear gloves, glasses and protective clothing (for specifications refer to section 8.2. SDS). Wash with water the area and materials involved
Storage of the product	Keep in original container closed tightly. Do not store in open or unlabelled containers. Keep containers upright and safe by avoiding the possibility of falls or collisions. Store in a cool and dry place, away from heat sources and direct exposure to sunlight.
In case of accidents, emergency or fire	Immediately inform the customer. Follow company emergency instruction.