

# EASYFOAM

Compressed air delivery system of foam detergents with great performances in small space



**Easyfoam** is a compact, high performance foam delivery system. It produces a very consistent, highly adhesive foam that makes it ideal for cleaning ceilings and vertical surfaces.

**Easyfoam** does not produce vapors, making it perfectly suited for safely applying highly alkaline foam detergents.

There are four models:

- **Easyfoam P 15 MT**
- **Easyfoam P 20 MT**
- **Easyfoam Mix 15 MT**
- **Easyfoam Mix 20 MT**

All Easyfoam models are available:

- with stain-resistant connection pipe with a length of 15 or 20 metres;
- with wheels.

## TECHNICAL CHARACTERISTICS

- 1** The equipment is produced with **stainless steel components** and plastic materials.
- 2** Safe supply of the solution with pressure lower than 1 Bar and no spray effect.
- 3** Utilization of plant water with min. pressure from 2 to 2,5 Bar. If using higher pressure, it is necessary to install a reducer (not included with the standard equipment).
- 4** Air: min. 3 Bar, max. 6 Bar (the foam becomes more consistent as the air pressure increases).
- 5** **Double one-way valve** on the air and water inlet.
- 6** **Stainless steel spray gun** 400 mm in length, with rubber handle.
- 7** Plastic hose reel.
- 8** Surface treatable in 1 minute: about 25 m<sup>2</sup>.

**Easyfoam P** and **Easyfoam Mix** do not require any special precautions concerning the installation of the water and pneumatic supply lines (at the customer's cost). It is, however, necessary to comply with all current regulations in order to ensure the safest conditions for operating the equipment.



## EASYFOAM MIX15 MT EASYFOAM MIX 20 MT

System for the combined supply of alkaline foam detergents and additive with booster effect and sanitizing action.

- Stain-resistant connection pipe, resistant to maximum pressure of 25 Bar, available in two measures: 15 and 20 m.
- When using foam detergents and additive it is advisable to utilize water at room temperature.
- Aimed percentage of foam-detergents: 3-10% (depending on the viscosity of the product used).
- Aimed percentage of additive: fixed.
- Dimensions: width 50 cm, height 110 cm, depth 5 cm.



- 1 - Double one-way valve, on the air and water inlet.
- 2 - Stainless steel spray gun.
- 3 - Double suction system, for foam detergent and additive



- 1 - Double one-way valve, on the air and water inlet.
- 2 - Stainless steel spray gun.
- 3 - Suction system, for foam detergent and additive.

## EASYFOAM P 15 MT EASYFOAM P 20 MT

System for the delivery of foam detergents by compressed air.

- Stain-resistant connection pipe, resistant to the max. pressure of 25 Bar, available in two measures: 15 and 20 m.
- When using foam detergents and additive it is advisable to utilize water at room temperature. It is however possible to use water up to 50°C.
- Aimed percentage of foam-detergents: 3-10% (depending on the viscosity of the product used).
- Dimensions: width 19 cm, height 24 cm, depth 5 cm.