



# LUBISAN Super Vet

.....  
 Lubricant with a synthetic basis for conveyor belts  
 .....

## → DESCRIPTION

**Lubisan Super Vet** is a very high performance, synthetic, liquid lubricant for the lubrication of conveyor belts of containers for liquid products in the food, cosmetic and pharmaceutical sectors.

**Lubisan Super Vet** is used for the transportation of glass, PET, aluminium and tinned plate containers.

**Lubisan Super Vet** is substantially insensitive to the dilution water hardness. Its function is to reduce frictions, to clean the belts and it has also a bacteriostatic action.

**Lubisan Super Vet** is non foaming if it is used at the optimal concentration.

## → TECHNICAL CHARACTERISTICS

Physical appearance: light yellow clear liquid

pH (0,8% solution):  $8,5 \pm 0,5$

pH:  $5,0 \pm 0,5$

Relative density at 20°C:  $1,00 \pm 0,05$

Phosphor content (P): absent

The above indicated chemical-physical data represent the typical product's characteristics drawn from the analysis carried out on the product. These values are not a specification.

## → INSTRUCTIONS FOR USE\*

The supply of **Lubisan Super Vet** should be carried out with the help of high precision centralized equipments, such as Lubimatic, by dividing the equipment into different areas in the case or particularly long or complex lines and by using nozzles with a fan spraying. The usage concentration is between 0,3 and 0,8%, according to the running speed of the lines and the spraying frequency. The compatibility with the packaging materials should be tested before the formulation is applied.

## → FIELDS OF APPLICATION

For the lubrication of steel belts.

## → COMPATIBILITY OF THE FORMULATION

**Lubisan Super Vet** is compatible with most material normally present in food, cosmetic and pharmaceutical industries, if used according to the producer's indications. In case of doubt, carry out a test on the single material before using the product.





## LUBISAN Super Vet

### → PRECAUTIONS FOR HANDLING AND STORAGE

Store in the original containers and avoid extreme temperatures. Consult the Material Safety Data Sheet.

### → TITRATION METHOD

Available on demand.

### → PACKAGING

25 kg net drums.  
200 kg net drums.  
500 kg net IBC.  
1000 kg net IBC.

\*The indications have been established for general use conditions. For conditions differing from the norm, for example depending on the particular water hardness, the working method or cleaning problems, please consult us; our technical service will be pleased to advise you and to cooperate with you.

