## **TECHNICAL DATASHEET**



# MEMBRAN UF

Medium alkalinity detergent for organic and inorganic membranes

### → DESCRIPTION

**Membran UF** is a medium alkalinity and high sequestering liquid detergent, to be used for the cleaning of UF and MF Membranes present in all sectors of food industries, beverage bottling and pharmaceutical sector.

**Membran UF** is able to easily remove organic and inorganic residues from Membranes, restoring the normal flow levels. Suitable also for hard waters.

**Membran UF** can also be used to remove organic contaminations from other sectors of the food industry, such as the dairy field.

### -> TECHNICAL CHARACTERISTICS

Physical appearance: light yellow clear liquid

pH (1% solution at 20°C):  $12.0 \pm 0.5$ Relative density at 20°C:  $1.25 \pm 0.05$ Conductivity 1% sol. at 25°C: 6.9 mS/cm.

The above indicated chemical-physical data represent the typical product's characteristics drawn from the analysis carried out on the product. These values are not a specification.

### -> INSTRUCTIONS FOR USE

Use **Membran UF** at variable concentrations from 0,5 to 1%. We suggest temperatures between 40 and 60°C with recycling times of at least 40′ in the case of UF and MF Membranes. Before the application of the product, it is necessary to verify the indications of tolerance to pH value and temperature of the Membranes, indicated by the producer on the MSDS. Carry out a careful final rinsing with drinking-water in order to remove any possible trace of product.

### -> FIELDS OF APPLICATION

For the alkaline cleaning of UF and MF Membranes and tangential filtration equipments.

# MEMBRAN UF

### --> COMPATIBILITY OF THE FORMULATION

The compatibility of **Membran UF** with the materials to be washed must be evaluated on the basis of the production specifications indicated by plant manufacturers. In case of doubt, carry out a test on the single material before using the product.

### -> PRECAUTIONS FOR HANDLING AND STORAGE

Store in the original containers and avoid extreme temperatures. Consult the Material Safety Data Sheet.

### → TITRATION METHOD

Sample: 50 mL of washing solution.

Indicator: phenolphthalein.

Titrating agent: hydrochloric acid (HCl) 1N.

pleased to advise you and to cooperate with you.

% (v/v) **Membran UF** = mL titrating agent x 0,367. % (w/w) **Membran UF** = mL titrating agent x 0,482.

### --> PACKAGING

30 kg drums. 1200 kg flowbins.

The indications have been established for general use conditions. For conditions differing from the norm, for example depending on the particular water hardness, the working method or cleaning problems, please consult us; our technical service will be

