

REMOVIL VAC

Issued on 09/04/2020 - Rel. # 5 on 09/04/2020

#1/16

In conformity to Regulation (EU) 2015/830

SECTION 1. Identification of the substance/mixture and of the company/enterprise

1.1. Product identifier

Product name : REMOVIL VAC Product code: refer to sales department

1.2. Relevant identified uses of the substance or mixture and uses advised against

medium alkaline detergent Sectors of use: Industrial Manufacturing[SU3], Manufacture of food products[SU4] Product category: Washing and Cleaning Products (including solvent based products) Process categories: Use in batch and other process (syn- thesis) where opportunity for exposure arises[PROC4], Transfer of substance or mixture (charging and discharging) at dedicated facilities[PROC8B], Treatment of articles by dipping and pouring[PROC13]

Not recommended uses Do not use for purposes other than those listed

1.3. Details of the supplier of the safety data sheet

AEB SpA - Via Vittorio Arici 104 S.Polo - 25134 Brescia (BS) Italy Tel. +39.030.2307.1 Fax +39.030.2307281 E-mail: info@aeb-group.com - Internet: www.aeb-group.com E-mail tecnico competente/technical dept.: sds@aeb-group.com

AEB USA 111 N Cluff Avenue Lodi CA 95240 (USA) Tel: +1 2096258139 Fax: +1 2092248953 Email: info@aebusa.com - Internet: www.aeb-group.com

AEB AFRICA (PTY) LTD 18 Track Crescent, Cor. Station Road Montague Gardens 7441 Cape Town (South Africa) Tel.: +27 215512700 - Fax: +27 (0) 215511919 Email: info@aeb.co.za - Internet: www.aeb-group.com

AEB OCEANIA PTY LTD 178A Wakaden Street Griffith NSW 2680 T: 1300 704 971 Email: aeboceania@aeb-group.com - Internet: www.aeb-group.com

Produced by AEB SpA Via Vittorio Arici 104 S. Polo



REMOVIL VAC

Issued on 09/04/2020 - Rel. # 5 on 09/04/2020

In conformity to Regulation (EU) 2015/830

25134 Brescia

1.4. Emergency telephone number

AEB SpA

Centralino/Switchboard: +39.030.2307.1 - (h 8.30-12.00 13.30-18.00 GMT +1; Lingua/Language: Italiano, English)

AEB USA

Switchboard: +1 2096258139 (GMT -8; Language: English)

AEB AFRICA (PTY) LTD Switchboard: +27 215512700 (GMT +1; Language: English, Afrikaans)

AEB OCEANIA PTY LTD

Switchboard: +61 1300 704 971 (GMT +9; Language: English)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

2.1.1 Classification according to Regulation (EC) No 1272/2008:

Pictograms: GHS05, GHS08

Hazard Class and Category Code(s): Met. Corr. 1, Skin Corr. 1, Eye Dam. 1, STOT RE 2

Hazard statement Code(s):

H290 - May be corrosive to metals.

H314 - Causes severe skin burns and eye damage.

H318 - Causes serious eye damage.

H373 - May cause damage to organs through prolonged or repeated exposure (by inhalation).

The product can be corrosive to metals

Corrosive product: causes severe skin burns and eye damage.

If brought into contact with eyes, the product causes serious damages to eyes, such as an opaque cornea or injury to iris.

Warning: This product can cause serious irreversible damages to man's health through prolonged or repeated exposure

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008:

Pictogram, Signal Word Code(s): GHS05, GHS08 - Danger

Hazard statement Code(s): H290 - May be corrosive to metals. H314 - Causes severe skin burns and eye damage.





REMOVIL VAC

Issued on 09/04/2020 - Rel. # 5 on 09/04/2020

In conformity to Regulation (EU) 2015/830

H373 - May cause damage to organs through prolonged or repeated exposure (by inhalation).

Supplemental Hazard statement Code(s): not applicable

Precautionary statements:

Prevention

P260 - Do not breathe vapours/spray.

P280 - Wear protective gloves/clothing and eye/face protection.

Response

P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Contains:

tetrasodium ethylene diamine tetraacetate, sodium hydroxide

Contains (Reg.EC 648/2004):

5% < 15% EDTA and salts thereof, < 5% anionic surfactants, amphoteric surfactants

2.3. Other hazards

The substance / mixture does NOT contain substances PBT/vPvB according to Regulation (EC) No 1907/2006, Annex XIII

The use of this chemical agent involves the obligation of "risk assessment" by the employer in accordance with the provisions of Dlgs n. 81. April 9, 2008. Workers exposed to this chemical agent should not be subject to health surveillance if the results of the risk assessment show that, depending on the type and quantity of dangerous chemical agent and method and frequency of exposure to the agent, there is only a "moderate Risk" for the health and safety of workers and that the measures laid down in the Decree are sufficient to reduce the risk.

Do not ingest. Keep out of reach of children.

SECTION 3. Composition/information on ingredients

3.1 Substances

Irrilevant

3.2 Mixtures

Refer to paragraph 16 for full text of hazard statements

Substance	Concentration[w/w]	Classification	Index	CAS	EINECS	REACh
Sodium hydroxide	>= 10 < 20%	Met. Corr. 1, H290; Skin Corr. 1A, H314; Eye Dam. 1, H318	011-002-00-6	1310-73-2	215-185-5	01-2119457 892-27-XXX X
Tetrasodium ethylene diamine	>= 10 < 20%	Acute Tox. 4, H302;	607-428-00-2	64-02-8	200-573-9	01-211948



REMOVIL VAC

Issued on 09/04/2020 - Rel. # 5 on 09/04/2020

#4/16

In conformity to Regulation (EU) 2015/830

Substance	Concentration[w/w]	Classification	Index	CAS	EINECS	REACh
tetraacetate		Eye Dam. 1, H318; Acute Tox. 4, H332; STOT RE 2, H373				6762-27-XX XX

SECTION 4. First aid measures

4.1. Description of first aid measures

Inhalation:

Ventilate the area. Move immediately the contaminated patient from the area and keep him at rest in a well ventilated area. If you feel unwell seek medical advice.

Direct contact with skin (of the pure product) .:

Take off immediately contaminated clothing.

In case of contact with skin, wash immediately with watrer.

Immediately consult a physician.

Direct contact with eyes (of the pure product).:

Wash immediately and thoroughly with running water, keeping eyelids open for at least 10 minutes, then protect your eyes with a dry sterile gauze. Seek medical advice immediately

Do not use eye drops or ointments of any kind before the examination or advice from an oculist.

Ingestion:

Drink water with egg white; do not give bicarbonate.

Absolutely do not induce vomiting or emesis. Seek medical advice immediately.

4.2. Most important symptoms and effects, both acute and delayed

Swallowing may cause chemical burns in the mouth and throat. In contact with skin it may cause burns. Contact with eyes causes very severe irritation, including redness and tear. Inhalation may cause asthma respiratory failure; Irritation of the mucous membranes and the respiratory tract may cause nausea and difficulty in breathing. Repeated inhalation may result in respiratory tract damage.

4.3. Indication of any immediate medical attention and special treatment needed

Get medical advice/attention if you feel unwell. Immediately call a POISON CENTER or a doctor.

SECTION 5. Firefighting measures

5.1. Extinguishing media

Suggested extinguishing media:

Water spray, CO2, foam, dry chemical, depending on the materials involved in the fire.

Extinguishing media to avoid:

Water jets. Use water jets only to cool the surfaces of the containers exposed to fire.



REMOVIL VAC

Issued on 09/04/2020 - Rel. # 5 on 09/04/2020

#5/16

In conformity to Regulation (EU) 2015/830

5.2. Special hazards arising from the substance or mixture

No data available.

5.3. Advice for firefighters

Use protection for the breathing apparatus

Safety helmet and full protective clothing.

The water spray can be used to protect the people involved in the extinction.

You may also use self-contained breathing apparatus, especially when working in confined and poorly ventilated areas. Keep containers cool with water spray

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel: Leave the area surrounding the spill or release. Do not smoke Wear mask, gloves and protective clothing.

6.1.2 For emergency responders:Eliminate all unguarded flames and possible sources of ignition. No smoking.Privide a sufficient ventilation.Evacuate the danger area and, in case, consult an expert.

6.2. Environmental precautions

Contain spills with earth or sand.

If the product has entered a watercourse, sewers or has contaminated soil or vegetation, notify the authorities. Dispose of the waste material in compliance with the regulations

6.3. Methods and material for containment and cleaning up

6.3.1 Containment:

Rapidly recover the product, wear a mask and protective clothing (for specifications refer to section 8.2. SDS) Recover the product for reuse, if possible, or for removal. Possibly absorb it with inert materia or sucked it. Prevent it from entering the sewer system.

6.3.2 Cleaning up: After wiping up, wash with water the area and materials involved

6.3.3 Other information: None in particular.

6.4. Reference to other sections

Refer to paragraphs 8 and 13 for more information



REMOVIL VAC

Issued on 09/04/2020 - Rel. # 5 on 09/04/2020

#6/16

In conformity to Regulation (EU) 2015/830

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Avoid contact and inhalation of vapors Wear protective gloves/clothing and eye/face protection. In residential areas do not use on large surfaces. At work do not eat or drink. See also paragraph 8 below.

7.2. Conditions for safe storage, including any incompatibilities

Keep in original container closed tightly. Do not store in open or unlabelled containers. Keep containers upright and safe by avoiding the possibility of falls or collisions. Store in a cool and dry place, away from heat sources and direct exposure to sunlight.

7.3. Specific end use(s)

Industrial Manufacturing: Handle with extreme caution. Store in a well ventilated place away from heat sources. (7-30°C)

Manufacture of food products: Handle with care. Store in a clean, dry, ventilated area away from heat and direct sunlight. Keep container tightly closed.(7-30°C)

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

------Related to contained substances: Sodium hydroxide: Limit value - Eight hours (ppm)/(mg/m3) Austria: x/2 inhalable aerosol Belgium: x/2(1)Denmark: x/2 France: x/2 Hungary: x/2 Japan (JSOH): x/2(1) Latvia: x/0,5 Poland: x/0.5 Romania: x/1 Spain: x/2 Sweden: x/1 (1) Switzerland: x/2 inhalable aerosol (MAK) USA – OSHA: x/2

Limit Value – Short Term



REMOVIL VAC

Issued on 09/04/2020 - Rel. # 5 on 09/04/2020

#7/16

In conformity to Regulation (EU) 2015/830

(ppm)/(mg/m3)Austalia: x/2(1) Austria: x/4 inhalable aerosol Canada - Ontario: x/2(1) Canada – Québec: x/2(1) Denmark: x/2 Finland: x/2(1) Hungary: x/2 Ireland: x/2(1) New Zealand: x/2(1) People's Republic of China: x/2(1) Poland: x/1 Romaniax/3(1) Singapore: x/2 South Korea: x/2(1) Sweden: x/2(1)(2)Switzerland: x/2 inhalable aerosol (MAK) USA – NIOSH: x/2(1)United Kingdom: x/2 Remarks: Australia: (1) Celling limit value Canada - Ontario: (1) Celling limit value Canada - Québec: (1) Celling limit value Finland: (1) Celling limit value Ireland: (1) 15 minutes reference period Japan: (1) Occupational exposure limit ceiling: Reference value to the maximal exposure concentration of the substance during a working day New Zealand: (1) Celling limit value People's Republic of China: (1) Celling limit value South Korea: (1) Celling limit value Romania: (1) 15 minutes average value Sweden: (1) Inhalable dust (2) Celling limit value USA – NIOSH: (1) Celling limit value (15 min) Argentine: CMP-C: 2 mg mg/m3 Czech Republic: PEL 1 mg/m3/ NPK-P 2 mg/m3 Italy: OEL: ACGIH -STEL: C 2.0 mg/m3; Tipo OEL: ACGIH - STEL: C2 mg/m3 - Note: URT, eye, and skin irr Estonia: short-term esposure limit (maximum chemical substance average allowable concentration in inhaled air - 15 minutes) 2 mg/m3(Ceiling limit" means a maximum permissible continuous concentration of 15 minutes in the air for rapidly acting substances) Norvay: ceiling value (a moment value that indicates the maximum concentration of a chemical in the breathing zone that should not be exceeded) 2 mg/m3 Lithuania: NRD 2 mg/m3 Slovakia: NPEL 2 mg/m3 South Africa: Short Term OEL-CL 2 mg/m³ - Substance: Sodium hydroxide DNEL Systemic effects Short term Workers inhalation = 1 (mg/m3) Systemic effects Short term Consumers inhalation = 1 (mg/m3) Local effects Short term Workers inhalation = 1 (mg/m3) Local effects Short term Consumers inhalation = 1 (mg/m3) - Substance: Tetrasodium ethylene diamine tetraacetate DNEL Systemic effects Long term Consumers oral = 25 (mg/kg bw/day) Local effects Long term Workers inhalation = 1,5 Local effects Long term Consumers inhalation = 0,6 (mg/m3) Local effects Short term Workers inhalation = 3 (mg/m3)



REMOVIL VAC

Issued on 09/04/2020 - Rel. # 5 on 09/04/2020

In conformity to Regulation (EU) 2015/830

Local effects Short term Consumers inhalation = 1,2 (mg/m3) PNEC Sweet water = 2,2 (mg/l) Sea water = 0,22 (mg/l) intermittent emissions = 1,56 (mg/l) STP = 43 (mg/l) ground = 0,72 (mg/kg ground)

8.2. Exposure controls

Appropriate engineering controls: Industrial Manufacturing: No specific monitoring foreseen (act according to good practice and specific rules for the type of risk associated)

Manufacture of food products: No specific monitoring foreseen (act according to good practice and specific rules for the type of risk associated)

8.2.2 Individual protection measures:

(a) Eye / face protection Wear protective goggles (EN 166).

(b) Skin protection

(i) Hand protection When handling the pure product use chemical resistant protective gloves (EN 374-1/EN374-2/EN374-3).

(ii) Other

During working operation wear protective clothing (generic workwear / antacid, safety shoes or other protective equipment) according to the instructions of the employer.

(c) Respiratory protection

In case of insufficient ventilation or emergency, use mask with Universal ABECK filters (EN 405) unless otherwise provided by the employer and / or assessments of environmental investigations hygienistic. None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements (89/656/EEC, 245/2016 UE), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by

(d) Thermal hazards No hazard to report

Environmental exposure controls:

Use according to good working practices and avoid to disperse the product into the environment.

SECTION 9. Physical and chemical properties

measures, methods or procedures of work organization.

9.1. Information on basic physical and chemical properties

8 / 16



REMOVIL VAC

Issued on 09/04/2020 - Rel. # 5 on 09/04/2020

#9/16

In conformity to Regulation (EU) 2015/830

Physical and chemical properties	Value	Determination method
Appearance	Clear, colorless or slightly straw-colored liquid	
Odour	not determined as considered not relevant for the characterization of the product	
Odour threshold	not determined as deemed not relevant to the characterization of the product	
рН	>12,0 (20° C ; sol 5 %); >12,0 (20° C ; 100%)	
Melting point/freezing point	not determined as deemed not relevant to the characterization of the product	
Initial boiling point and boiling range	not determined as deemed not relevant to the characterization of the product	
Flash point	not determined as deemed not relevant to the characterization of the product	
Evaporation rate	not determined as deemed not relevant to the characterization of the product	
Flammability (solid, gas)	not determined as deemed not relevant to the characterization of the product	
Upper/lower flammability or explosive limits	not determined as deemed not relevant to the characterization of the product	
Vapour pressure	not determined as deemed not relevant to the characterization of the product	
Vapour density	not determined as deemed not relevant to the characterization of the product	
Relative density	1,25 ± 0,05 (20° C)	
Solubility	in water	
Water solubility	miscible in all proportions	
Partition coefficient: n-octanol/water	not determined as deemed not relevant to the characterization of the product	
Auto-ignition temperature	not determined as deemed not relevant to the characterization of the product	
Decomposition temperature	not determined as deemed not relevant to the characterization of the product	
Viscosity	not determined as deemed not relevant to the characterization of the product	
Explosive properties	not determined as deemed not relevant to the characterization of the product	
Oxidising properties	not determined as deemed not relevant to the characterization of the product	

9.2. Other information

No data available.

SECTION 10. Stability and reactivity

10.1. Reactivity

Base



REMOVIL VAC

Issued on 09/04/2020 - Rel. # 5 on 09/04/2020

In conformity to Regulation (EU) 2015/830

10.2. Chemical stability

Stable under recommended storage and handling conditions

10.3. Possibility of hazardous reactions

Avoid direct contact of the undiluted product with aluminum, tin, nickel, copper, zinc and their alloys. Very exothermic reaction with strong acids.

10.4. Conditions to avoid

Avoid prolonged contact with air, storage at temp. below 7 ° C and the provisions of 10.3

10.5. Incompatible materials

It can generate flammable gases in contact with halogenated organic substances, elementary metals.

10.6. Hazardous decomposition products

It does not decompose when used for its intended uses.

SECTION 11. Toxicological information

11.1. Information on toxicological effects

ATE(mix) oral = 13.830,6 mg/kg ATE(mix) dermal = ∞ ATE(mix) inhal = 85,5 mg/l/4 h

(a) acute toxicity: Sodium hydroxide: Ingestion - LD50 rat (mg / kg / 24h bw): nd
Skin contact - LC50 rabbit (mg / kg / 24h bw): 1350
Inhalation - LD50 rat (mg / I / 4h): nd
Tetrasodium ethylene diamine tetraacetate: Ingestion - LD50 rat (mg / kg / 24h bw): 1 780 - 2 000
Skin contact - LC50 rat / rabbit (mg / kg / 24h bw): nd
Inhalation - LD50 rat (mg / I / 4h):> 1 - 5 (dust-fog)
(b) skin corrosion/irritationCorrosive product: causes severe skin burns and eye damage.



REMOVIL VAC

Issued on 09/04/2020 - Rel. # 5 on 09/04/2020

11 / 16

In conformity to Regulation (EU) 2015/830

Sodium hydroxide: Corrosive

Tetrasodium ethylene diamine tetraacetate: Not corrosive

Sodium hydroxide: Irritating

Tetrasodium ethylene diamine tetraacetate: Treatment of intact rabbit skin with an aqueous 80% Na4 EDTA preparation caused mild or absent irritation. These data show that it is not necessary to classify and label the substance for skin irritant properties based on EU or GHS regulations.

(c) serious eye damage/irritation: Corrosive product: causes severe skin burns and eye damage. - If brought into contact with eyes, the product causes serious damages to eyes, such as an opaque cornea or injury to iris. Sodium hydroxide: Corrosive

Tetrasodium ethylene diamine tetraacetate: The opacity caused by the instillation of the undiluted substance in the eye of the rabbits is irreversible. These data demonstrate that it is necessary to classify and label the substance for irritant and corrosive properties according to EU or GHS regulations.

Sodium hydroxide: Irritating

Tetrasodium ethylene diamine tetraacetate: The opacity caused by the instillation of the undiluted substance in the eye of the rabbits is irreversible. These data demonstrate that it is necessary to classify and label the substance for irritant and corrosive properties according to EU or GHS regulations.

(d) respiratory or skin sensitization: Sodium hydroxide: Not sensitizing

Tetrasodium ethylene diamine tetraacetate: Not sensitizing

(e) germ cell mutagenicity: Sodium hydroxide: Not mutagenic

Tetrasodium ethylene diamine tetraacetate: As for Na4EDTA, no genotoxicity studies are available, therefore data from other sodium EDTA and free acid EDTA salts have been considered. (For the read-across justification, see also section 13). The Na EDTA salts were negative in numerous ames tests. The Na salts of EDTA were negative in numerous tests on mouse lymphoma. Numerous other tests were performed in vitro and in general the EDTA was not genotoxic in vitro. In vivo, somatic cells in mice (bone marrow cells) showed negative results compared to micronuclei endpoints, aneuploidy and sibling chromatid exchanges. In germ cells, negative results have been obtained for the induction of structural chromosomal aberrations in spermatogonia, for the induction of aneuploidy in primary and secondary spermatocytes and also for the induction of dominant lethals. A positive result was obtained in a micronuc test

(f) carcinogenicity: Sodium hydroxide: Not carcinogenic

Tetrasodium ethylene diamine tetraacetate: There are no epidemiological studies available to evaluate the carcinogenic potential of Na4EDTA. No carcinogenicity studies of Na4EDTA are available. Therefore, carcinogenicity studies with Na3EDTA were used for evaluation. A biological assay of Na3EDTA for possible carcinogenicity was conducted by administering test material in the diet to Fischer rats 344 and B6C3F1 mice. The studies did not report specific data on renal toxicity in either species even though histology was performed. Although a variety of tumors occurred between the test and control animals of both species, no tumor was related to treatment. Summing up the negative results of the carcinogenicity study and of the SHE cell transformation tests, as well as the general non-mutagenicity after oral doses, it can be concluded that there are no concerns about a carcinogenic potential of EDTA.

(g) reproductive toxicity: Sodium hydroxide: Non-toxic for reproduction

Tetrasodium ethylene diamine tetraacetate: Numerous in vitro tests are available on the teratogenic effects of EDTA or Na salts of EDTA. However, they gave inconsistent results and were generally not well reported. Therefore they were not considered for risk assessment. There are 2 cases of pregnant women treated with CaNa2EDTA due to lead intoxication. However, as these treatments were performed late in pregnancy, these data were not considered for risk assessment. Endpoint conclusion: no observed adverse effects (negative)

(h) specific target organ toxicity (STOT) single exposure: Sodium hydroxide: The substance can be absorbed into the body by inhalation of its aerosols and by ingestion.

Tetrasodium ethylene diamine tetraacetate: Non-toxic

(i) specific target organ toxicity (STOT) repeated exposureWarning: This product can cause serious irreversible damages to man's health through prolonged or repeated exposure

Sodium hydroxide: The substance can be absorbed into the body by inhalation of its aerosols and by ingestion. The symptoms of pulmonary edema often do not manifest themselves before a few hours and are exacerbated by physical exertion. Rest and medical observation are therefore essential

Tetrasodium ethylene diamine tetraacetate: Based on the results obtained in the toxicity studies and taking into account the provisions established in the CLP Regulation, a classification as STOT RE Cat 2 (H373)

NOAEL oral (rat): 500 mg / kg bw / day

NOAEL oral (mouse) is justified : 938 mg / kg bw / day

NOAEC inhalation (rat): 3 - 15 mg / m³ air

LOAEC inhalation (rat): 15 - 30 mg / m³ air

(j) aspiration hazard: Sodium hydroxide: Not available



REMOVIL VAC

Issued on 09/04/2020 - Rel. # 5 on 09/04/2020

In conformity to Regulation (EU) 2015/830

Tetrasodium ethylene diamine tetraacetate: Not classified

SECTION 12. Ecological information

12.1. Toxicity

Related to contained substances: Sodium hydroxide: Acute toxicity - LC50 fish (mg / I / 96h): 45 Acute toxicity - crustaceans EC50 (mg / I / 48h): 40 Acute toxicity algae ErC50 (mg / I / 72-96h): nd Chronic toxicity - NOEC fish (mg / I): nd Chronic toxicity - crustaceans NOEC (mg / I): nd Chronic toxicity NOEC algal (mg / I): nd C(E)L50 (mg/I) = 45

Tetrasodium ethylene diamine tetraacetate: Acute toxicity - fish LC50 (mg / I / 96h): 41 - 1 592 (frequent value> 100) Acute toxicity - fish LC100 (mg / I / 96h) 75 - 1 846 Acute toxicity - crustaceans EC50 (mg / I / 48h): 140 Acute toxicity - crustaceans EC50 (mg / I / 24h): 610 - 625 (frequent value> 500) Acute toxicity - crustaceans EC0 (mg / I / 48h): 100 Acute toxicity - crustaceans EC0 (mg / I / 24h): 310 Acute toxicity - crustaceans E100 (mg / I / 48h): 180 Acute algae toxicity ErC50 (mg / I / 72h): 2.77 - 1 000 (frequent data> 100) Acute algae toxicity EC10 (µg / I / 72h): 700 - 307 630 Acute algae toxicity EC90 (mg / I / 72h): 100 Chronic toxicity - NOEC fish (mg / I 35 g) 25.7 Chronic toxicity - crustaceans NOEC (mg / I 21g): 25 Chronic toxicity - crustaceans LOEC (mg / I 21g): 50 Chronic toxicity - NOEC algae (µg / I 72h): 390 - 100 000 Chronic toxicity - LOEC algae (µg / I 21g): 780 - 1 000 000

Microorganism toxicity - EC10 (30 min) 500 mg / L Terrestrial macroorganism toxicity except anthropod EC50 (14 g) 156.46 mg / kg soil C(E)L50 (mg/l) = 100 NOEC (mg/l) = 25

Use according to good working practices and avoid to disperse the product into the environment.

12.2. Persistence and degradability

Related to contained substances: Sodium hydroxide: Not applicable

Tetrasodium ethylene diamine tetraacetate:

The EDTA (acid form) and its salts are not readily biodegradable according to the OECD criteria. It has been shown that under special conditions (slightly alkaline adaptation or pH, a realistic condition of water below the environmental

12 / 16



REMOVIL VAC

Issued on 09/04/2020 - Rel. # 5 on 09/04/2020

13 / 16

In conformity to Regulation (EU) 2015/830

surface, the biodegradability of EDTA is considerably Therefore it can be concluded that EDTA is ultimately biodegradable under such environmental conditions.

12.3. Bioaccumulative potential

Related to contained substances: Sodium hydroxide: Not bioaccumulative

Tetrasodium ethylene diamine tetraacetate: Not bioaccumulative

12.4. Mobility in soil

Related to contained substances: Sodium hydroxide: Not applicable

Tetrasodium ethylene diamine tetraacetate:

Due to the ionic structure, no adsorption on the organic fraction of the soil or sediments is expected for EDTA (acid form) and its salt. The test substance will not evaporate from the surface of the water in the atmosphere. The test substance will preferably be distributed in the compartment water.

12.5. Results of PBT and vPvB assessment

No PBT/vPvB ingredient is present

12.6. Other adverse effects

No adverse effects

Regulation (EC) No 2006/907 - 2004/648

The (I) surfactant (s) content (s) in this preparation complies (comply) with (i) the biodegradability criteria as laid down in Regulation CE/648/2004 on detergents. All data are held at the disposal of the competent authorities of Member States and will be provided, at their direct request or at the request of a detergent manufacturer, to those authorities.

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Do not reuse empty containers. Dispose of them in accordance with the regulations in force. Any remaining product should be disposed of according to applicable regulations by addressing to authorized companies. Recover if possible. Operate according to local or national regulations

SECTION 14. Transport information



REMOVIL VAC

Issued on 09/04/2020 - Rel. # 5 on 09/04/2020

In conformity to Regulation (EU) 2015/830

14.1. UN number

ADR/RID/IMDG/ICAO-IATA: 3266

If subject to the following characteristics is ADR exempt: Combination packagings: per inner packaging 1 L per package 30 Kg Inner packaging placed in skrink-wrapped or stretch-wrapped trays: per inner packaging 1 L per package 20 Kg

14.2. UN proper shipping name

ADR/RID/IMDG: LIQUIDO INORGANICO CORROSIVO, BASICO, N.A.S. (Idrossido di sodio in miscela) ADR/RID/IMDG: CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Sodium hydroxide in mixture) ICAO-IATA: CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Sodium hydroxide in mixture)

14.3. Transport hazard class(es)

ADR/RID/IMDG/ICAO-IATA: Class : 8 ADR/RID/IMDG/ICAO-IATA: Label : 8 ADR: Tunnel restriction code : E ADR/RID/IMDG/ICAO-IATA: Limited quantities : 1 L IMDG - EmS : F-A, S-B

14.4. Packing group

ADR/RID/IMDG/ICAO-IATA: II

14.5. Environmental hazards

ADR/RID/ICAO-IATA: Product is not environmentally hazardous IMDG: Marine polluting agent : No

14.6. Special precautions for user

The transport must be carried out by authorized vehicles for the transport of dangerous goods in accordance with the requirements of the applicable Edition of the agreement A.D.R. and national provisions. The transport must be carried out in the original packaging and in packages that are made from materials resistant to content and not likely to generate with this dangerous reactions. The process of loading and unloading of dangerous goods have received adequate training on the risks presented by prepared and on possible procedures to be taken in the event of emergency situations

14.7. Transport in bulk according to Annex II of MARPOL73/78 and IBC Code

Transport in bulk is not foreseen





REMOVIL VAC

Issued on 09/04/2020 - Rel. # 5 on 09/04/2020

15 / 16

In conformity to Regulation (EU) 2015/830

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions relating to the product or contained substances (All. XVII Reg. EC 1907/2006): not applicable Substances in Candidate List (art. 59 Reg. EC 1907/2006): the product does not contain SVHC Substances subject to authorisation (Ann. XIV Reg. CEC 1907/2006): the product does not contain SVHC Reg. EC 648/04: see 2.2 Reg. (EU) n. 1169/2011: see 2.2 Reg (UE) 528/2012: see to 2.2

REGULATION (EU) No 1357/2014 - waste: HP5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity HP8 - Corrosive

15.2. Chemical safety assessment

No chemical safety assessment was carried out by the supplier

SECTION 16. Other information

16.1. Other information

Points modified compared to previous release: 2.2. Label elements

Description of hazard statements set out in paragraph 3

- H290 = May be corrosive to metals.
- H314 = Causes severe skin burns and eye damage.
- H318 = Causes serious eye damage.
- H302 = Harmful if swallowed.
- H332 = Harmful if inhaled.
- H373 = May cause damage to organs through prolonged or repeated exposure .

Classification based on data of all mixture components

Main normative references:

Reg. (CE) n. 1907 del 18/12/06 REACH (Registration, Evaluation and Authorisation of CHemicals) et seq.
Reg. (CE) 1272/2008 CLP (Classification Labelling and Packaging) et seq.
Regulation (EC) n. 648 of 31/03/04 (on detergents) et seq.
Regulation (UE) n. 1169/2011 (on the provision of food information to consumers)
Directive 2012/18/EU (on the control of major-accident hazards involving dangerous substances) et seq.
Regulation (UE) 528/2012 (Biocides) et seq.

Procedure used to classify under CLP mixture (Reg . EC 1272/2008):

Physical hazards: On the basis of experimental data H314 Skin. Corr. 1A: On the basis of experimental data / Calculation Method Other hazards: Calculation Method

Training required: This document must be submitted to the employer to determine the possible need for appropriate training for workers to ensure protection of human health and the environment.

n.a.: not applicable
n.d.: not available
ADR: Accord europèen relative au transport International des merchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
ATE: Acute Toxicity Estimat



REMOVIL VAC

Issued on 09/04/2020 - Rel. # 5 on 09/04/2020

In conformity to Regulation (EU) 2015/830

BFC: BioconCentration Factor BOD: Biochemical Oxigen Demand CAS: Chemical Abstract Service number CAP: Centre AntiPoison CE/EC number EINECS (European Inventory of existing Commercial Substances) e ELINCS (European List of notified Chemical Substances) CL50/LC50: Lethal Concentration 50 DL50/LD50: Lethal Dose 50 COD: Chemical Oxygen Demand DNEL: Derived No Effect Level EC50: half maximal Effective Concentration ERC: Enviroment Release Classes EU/UE: European Union IATA: International Air Transport Association ICAO: International Civil Aviation Organization IMDG: International Maritime Dangerous Goods code Kow: Octanol water partition coefficient NOEC: No Observed Effect Concentration **OEL: Occupational Exposure Limit** PBT: Persistent Bioaccumulative and Toxic PC: Product Categories PNEC: Predicted No Effect Concentration PROC: Process Categories RID: Règlement concernent le transport International ferroviaire des merchandises dangereuses (Regulations concerning International rail transport of dangerous goods) STOT: Target Organ Systemic Toxicity STOT (RE): Repeated Exposure STOT (SE): Single Exposure STP: Sewage Treatment Plants SU: Sector of Use SVCH: Substance of Very High Concern TLV: Threshold Limit Value vPvB: Very Persistent Very Bioaccumulative

References and Sources:

- ECHA Registered Substances:
- https://echa.europa.eu/web/guest/information-on-chemicals/registered-substances
- SDS supplier
- · GESTIS DNEL Database: http://www.dguv.de/ifa/gestis/gestis-dnel-datenbank/index-2.jsp
- · GESTIS International Limit Value: http://limitvalue.ifa.dguv.de

This msds was made in good faith by AEB technical Office on the basis of the information available at the date of the last revision. The person in charge must regularly inform the employees about the specific risks they encounter when using this substance/product. The information contained here relate only to the substance/the preparation indicated and may not apply if the product is used improperly or in combination with others. Nothing contained herein shall be construed as a guarantee, either express or implied. It is the responsibility of the user to ensure the opportunities and completeness of the information contained herein for their own particular use.

*** this tab annuls and replaces any previous edition. (IIXX)

Changes to the previous edition: label ements, exposure scenario updating, attached working instruction table

REMOVIL VAC

SUMI Safe Use of Mixtures Information



AISE_SUMI_IS_4_2

Version 1.1, August 2018

Industrial uses; Automated task; Semi-automated task; Dedicated equipment

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

The SUMI applies to industrial uses where products are used in closed process where opportunity for exposure arises. This Safe Use Information is based on the **AISE_SWED_IS_4_2**.

Operational Conditions

Maximum duration	480 minutes per day.
Range of application /	Indoor Use.
Process conditions	Process carried out at room temperature.
	In case of dilution, tap water at a maximum temperature of 45°C is used.
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per
	hour). No LEV required.

Risk Management Measures

Measures related to	Wear suitable gloves.	
personal protective equipment (PPE), hygiene and health evaluation	See section 8 of the SDS of this product for specifications.	
	Training of workers in relation to proper use and maintenance of PPEs must be ensured.	
Environmental	Prevent that undiluted product reaches surface waters.	
measures	If appropriate AISE SPERC 8a.1.a.v2 may apply : wide dispersive use resulting in release to municipal sewage treatment plant.	

Additional good practice advice

Don't eat or drink. Don't smoke. Don't use in proximity of open flame.	
Wash hands after use. Avoid contact with damaged skin. Do not mix with other products.	
Spillage instructions	Dilute with fresh water and mop up.
Hygiene practices	Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS.

Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

Disclaimer

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling.

If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself.

Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product.

This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk.

A.I.S.E. disclaims any liability to any person or entity for any loss, damage no matter of what kind (actual, consequential, punitive or otherwise), injury, claim, liability or other cause of any kind or character based upon or resulting from the use (even partly) of the content of this document.

REMOVIL VAC

SUMI Safe Use of Mixtures Information



AISE_SUMI_IS_8b_1

Version 1.1, August 2018

Transfer and dilution of concentrated product by using dedicated dosing system

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

This SUMI applies to industrial uses where products are transferred to or diluted in a dedicated dosing system. This Safe Use Information is based on the AISE_SWED_IS_8b_1_L and AISE_SWED_IS_8b_1_S

Operational Conditions

Maximum duration	60 minutes per day.
Range of application /	Indoor Use.
Process conditions	Process carried out at room temperature.
	In case of dilution, tap water at a maximum temperature of 45°C is used.
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per
	hour). No LEV required.

Risk Management Measures

Measures related to	Wear suitable gloves.
personal protective	See section 8 of the SDS of this product for specifications.
equipment (PPE),	
hygiene and health	
evaluation	
	Training of workers in relation to proper use and maintenance of PPEs
	must be ensured.
Environmental	Prevent that undiluted product reaches surface waters.
measures	If appropriate AISE SPERC 8a.1.a.v2 may apply: wide dispersive use
	resulting in release to municipal sewage treatment plant.

Additional good practice advice

Don't eat or drink. Don't smoke. Don't use in proximity of open flame.	
Wash hands after use. Avoid contact with damaged skin. Do not mix with other products.	
Spillage instructions	Dilute with fresh water and mop up.
Hygiene practices	Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS.

Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

Disclaimer

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling.

If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself.

Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product.

This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk.

A.I.S.E. disclaims any liability to any person or entity for any loss, damage no matter of what kind (actual, consequential, punitive or otherwise), injury, claim, liability or other cause of any kind or character based upon or resulting from the use (even partly) of the content of this document.

REMOVIL VAC

SUMI Safe Use of Mixtures Information



AISE_SUMI_IS_13_3_G

Version 1.1, August 2018

Industrial uses; Treatment of articles by dipping or pouring

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

This SUMI applies to industrial uses where articles are treated by dipping or pouring. This Safe Use Information is based on the **AISE_SWED_IS_13_3**.

Operational Conditions

Maximum duration	480 minutes per day.
Range of application /	Indoor Use.
Process conditions	Process carried out at room temperature.
	In case of dilution, tap water at a maximum temperature of 45°C is used.
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per
	hour). No LEV required.

Risk Management Measures

Measures related to	Wear suitable gloves and eye protection.
personal protective	See section 8 of the SDS of this product for specifications.
equipment (PPE),	
hygiene and health evaluation	
evaluation	
	Training of workers in relation to proper use and maintenance of PPEs
	must be ensured.
Environmental	Prevent that undiluted product reaches surface waters.
measures	If appropriate AISE SPERC 8a.1.a.v2 may apply: wide dispersive use
	resulting in release to municipal sewage treatment plant.

Additional good practice advice

Don't eat or drink. Don't smoke. Don't use in proximity of open flame.	
Wash hands after use. Avoid contact with damaged skin. Do not mix with other products.	
Spillage instructions	Dilute with fresh water and mop up.
Hygiene practices	Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS.

Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

Disclaimer

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling.

If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself.

Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product.

This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk.

A.I.S.E. disclaims any liability to any person or entity for any loss, damage no matter of what kind (actual, consequential, punitive or otherwise), injury, claim, liability or other cause of any kind or character based upon or resulting from the use (even partly) of the content of this document.

WORKING ISTRUCTION TABLE



This tab provides instructions for appropriate and safe use of products and proper management of emergency situations for cleaning staff/users.

Attached to MSDS rel#5 del 09/04/20

Use description	Use in batch and other process (synthesis) where opportunity for exposure arises [PROC4]; Transfer of substance or mixture (charging and discharging) at dedicated facilities [PROC8b]; Treatment of articles by dipping and pouring [PROC13]
Product name	REMOVIL VAC
Classification of the product (100%)	H290 - May be corrosive to metals. H314 - Causes severe skin burns and eye damage. H318 - Causes serious eye damage. H373 - May cause damage to organs through prolonged or repeated exposure (by inhalation).
Classification of the diluted product (maximum use	At maximux concentration of use (5%) the product is classified:
concentration)	H314 - Causes severe skin burns and eye damage. H318 - Causes serious eye damage.
Handling of the product (100%)	Avoid contact and inhalation of vapors Wear protective mask/gloves/clothing and eye/face protection. At work do not eat or drink.
Handling of the diluted product	Avoid contact and inhalation of vapors Wear protective gloves/clothing and eye/face protection. At work do not eat or drink.
DPI required concentrated use, spillage)	Chemical resistant protective gloves (EN 374-1/EN374-2/EN374-3), safety glasses (EN 166).
Diluited product	Chemical resistant protective gloves (EN 374-1/EN374-2/EN374-3), safety glasses (EN 166).

In case of emergency (accidents involving exposure to the product)	Immediately inform the customer. Immediately inform the employer. Contact Poisons Centres tel. number in 1.4 section of the MSDS
Accidental release large quantities measures: concentrated product	Wear mask,gloves, glasses and protective clothing (for specifications refer to section 8.2. SDS) Possibly absorb it with inert materia or sucked it. After wiping up, wash with water the area and materials involved
Diluited product	Wear mask, gloves, glasses and protective clothing (for specifications refer to section 8.2. SDS). Wash with water the area and materials involved
Storage of the product	Keep in original container closed tightly. Do not store in open or unlabelled containers. Keep containers upright and safe by avoiding the possibility of falls or collisions. Store in a cool and dry place, away from heat sources and direct exposure to sunlight.
In case of accidents, emergency or fire	Immediately inform the customer. Follow company emergency instruction.