



REMOX

.....
 Alkaline detergent with high causticity

→ DESCRIPTION

Remox is an high-alkalinity detergent capable of solubilizing, completely and rapidly removing all organic residues, leaving the treated surfaces perfectly shining without the slightest stain.

When mixed with Remoxan, it enables in just one operation to clean and sanitize heavily scaled and soiled surfaces. This combination eliminates the colouring matter and deposits left behind by tannins.

→ TECHNICAL CHARACTERISTICS

Physical appearance: colourless clear liquid
 pH (1% solution): 12,0 ± 0,5
 Relative density at 20°C: 1,25 ± 0,05

The above indicated chemical-physical data represent the typical product's characteristics drawn from the analysis carried out on the product. These values are not a specification.

→ INSTRUCTIONS FOR USE*

Use **Remox** at concentrations from 2 to 8%, according to the kind and degree of the contamination. We suggest temperatures above 50°C. Final rinsing with drinking water till any possible residue of detergent is completely eliminated.

→ FIELDS OF APPLICATION

For cleaning and decolorizing storage and fermentation tanks in wood, cement, stainless steel, fibreglass or lined with epoxy resins. For cleaning, decolorizing and deodorizing filters, pipes, dosing units, filling machines as well as other bottling equipment and pasteurizers.

→ COMPATIBILITY OF THE FORMULATION

Remox is compatible with most material normally present in food industries, if used according to the producer's indications. Do not use on aluminium, copper, zinc-plated iron, phenolic resins and nitro-varnished surfaces. In case of doubt, carry out a test on the single material before using the product with phenolic resins. In case of doubt, carry out a test on the single material before using the product.





REMOX

→ PRECAUTIONS FOR HANDLING AND STORAGE

Store the formulation far from extreme temperatures. Frost sensitive: keep at temperatures above 7°C. Consult the Material Safety Data Sheet.

→ TITRATION METHOD

Available on demand.

→ PACKAGING

25 kg net drums.
1100 kg net IBC.

*The indications have been established for general use conditions. For conditions differing from the norm, for example depending on the particular water hardness, the working method or cleaning problems, please consult us; our technical service will be pleased to advise you and to cooperate with you.

