

# MULTIFOAM & MULTIFOAM INOX

Multipurpose foam nebulizers  
for the washing and sanitizing of all surfaces



Reference: MULTIFOAM\_DEP\_EN\_0250917\_South\_Africa

# Multifoam & Multifoam Inox



## The range

Four models

### Multifoam L24-L50

Multipurpose low-pressure foam nebulizer with 24 or 50 liter tank.

### Multifoam Inox L24-L50

Multipurpose low-pressure foam nebulizer in stainless steel 18/8 with 24 or 50 liter tank.

**Multifoam** and **Multifoam Inox** can be used for multiple washing applications in all types of industries. It is professional equipment for the nebulization of detergents, sanitizers, lubricating oils and any other substance in liquid form.

The two equipment designed and developed by AEB enable:

- the cleaning with **foam detergents**;
- the nebulization of **conventional detergents**;
- the environmental sanitation with nebulization of **sanitizers and sanitizing detergents**.

## THE RANGE OF AEB FORMULATIONS IDEAL FOR USE WITH MULTIFOAM AND MULTIFOAM INOX



### Foam detergents

#### STERIFOAM

Neutral foam detergent with sanitizing activity not based on oxidants, for any type of surface.

#### AROFOAM

Alkaline foam detergent, for the daily cleaning of surfaces.

#### OLIFOAM

Medium alkalinity, liquid, solvented foam detergent, able to easily remove residues of grease, vegetable and mineral oil.

#### SANIFOAM

Alkaline foam detergent with high chlorine content, able to effectively remove various types of organic contamination.

#### VEROFOAM

Medium alkalinity foam detergent; it enables the effective removal of various types of organic contamination.

#### REMOFOAM

High alkalinity foam detergent; it effectively removes various types of organic contamination.

#### CEPOFOAM

Acid foam detergent for the effective removal of various types of inorganic contamination (limestone) even on very contaminated surfaces.

#### CELOFOAM

Acid descaling foam detergent, able to remove inorganic contaminations of various types (limestone) even on very contaminated surfaces working hot.

#### CELOFOAM SAN

Acid foam detergent with sanitizing action, able to effectively remove inorganic contaminations of various types (limestone) even on very contaminated surfaces working hot.

### Traditional detergents

#### CLEM

Concentrated, neutral, liquid, medium foaming detergent, suitable for all manual cleaning treatments.

#### DOMAL

Alkaline liquid detergent, suitable for the cleaning of aluminium materials in all fields of food processing and bottling of beverages.

### Sanitizers and sanitizing detergents

#### NEUTROSAN

Neutral liquid sanitizer that, thanks to the presence in the formula of polybiguanide hydrochloride (Biguanide), performs a broad-spectrum activity in the final treatment of hard surfaces.

#### QUATESAN

Neutral liquid sanitizer that, thanks to the presence in the formula of the quaternary ammonium salts, displays detaching and sanitizing characteristics and also carries out an anti-algae effect.

#### GLUTASAN

Neutral liquid sanitizer; it is a classical synergistic combination of glutaraldehyde and quaternary ammonium salts, forming a product with a broad spectrum of activity.

#### PERCISAN SF

Oxidizing foaming sanitizer for surfaces based on citric acid in hydrogen peroxide, with a broad spectrum of activity; it is recommended for the treatment of final sanitation of hard surfaces.

## Multifoam L24-L50

- **24 or 50 liter tank** that can be used up to a pressure of 10 bar (loaded with standard compressors)
- **Lance of 70 cm** consisting of: PVC pipe (5 meters for the model L24 and 10 meters for the model L50), two foaming nozzles and one spray nozzle
- **Self-lubricating wheels**
- **Safety valve** with direct discharge
- **Manometer** 0-12 bar
- **Level indicator**

The **internal and external coating with epoxy resins** allows the equipment to effectively **resist to any type of detergent or sanitizer**, both acid and alkaline, without danger of corrosion.

## Multifoam Inox L24-L50

Exclusively in stainless steel 18/8 AISI 304

- **24 or 50 litre tank** that can be used up to a pressure of 8 bar (loaded with standard compressors)
- **Lance of 70 cm** composed by: PVC pipe (5 meters for the model L24 and 10 meters for the model L50), two foaming nozzles and one spray nozzle
- **Self-lubricating wheels**
- **Safety valve** with direct discharge
- **Manometer** 0-12 bar
- **Level indicator**

Equipped with trolley for an easy handling, Multifoam Inox is made in stainless steel A304 to **avoid problems resulting from the corrosion of iron tanks and to withstand particularly aggressive chemicals\***.



\* Stainless steel series 300 (304-316) does not have a good degree of resistance against chlorine, therefore it is not recommended to place liquids containing this substance inside the tank.